424001-05 CURB RAMPS FOR SIDEWALKS

515001-02 NAME PLATE FOR BRIDGES

542301-01 PRECAST REINFORCED CONCRETE FLARED END SECTION

54240 METAL END SECTION FOR PIPE CULVERTS

602301-01 INLET, TYPE A

MEDIAN INLET FOR 600 MM (24") REINFORCED CONCRETE PIPE 604101

CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER 606001-03

635011-01 REFLECTOR MARKER AND MOUNTING DETAILS

664001-01 CHAIN LINK FENCE

701001-01 OFF-ROAD OPERATIONS, 2L, 2W, MORE THAN 4.5 M (15') AWAY

OFF-ROAD OPERATIONS, 2L, 2W, 4.5 m (15') TO 600 MM (24") FROM PAVEMENT EDGE EDGE 701006-02

701501-04 URBAN LANE CLOSURE, ZL, ZW, UNDIVIDED

LANE CLOSURE, MULTILANE IW OR 2W CROSSWALK OR SIDEWALK CLOSURE 701801-03

701901 TRAFFIC CONTROL DEVICES

SIGN PANEL MOUNTING DETAILS 720001 720006-01 SIGN PANEL ERECTION DETAILS

720011 METAL POSTS FOR SIGNS, MARKERS AND DELINEATORS

729001 APPLICATIONS OF TYPES A AND B METAL POSTS (FOR SIGNS & MARKERS)

805001 ELECTRICAL SERVICE INSTALLATION DETAILS 878001-06 CONCRETE FOUNDATION DETAILS

B.L.R. 23-2 TRAFFIC BARRIER TERMINAL TYPE I

## GENERAL NOTES

- THE NOMINAL THICKNESS HMA SURFACE COURSES ARE SHOWN ON THE TYPICAL SECTIONS, STANDARDS, SCHEDULES, OR SPECIAL DETAILS. THE CONSTRUCTED THICKNESS OF THE ABOVE ITEMS SHALL NOT BE LESS THAN 100 PERCENT OF THE NOMINAL THICKNESS AT ANY LOCATION.
- THE NOMINAL THICKNESS FOR BASE COURSES ARE SHOWN ON THE TYPICAL SECTIONS, STANDARDS, SCHEDULES, OR SPECIAL DETAILS. THE CONSTRUCTED THICKNESS OF THE ABOVE ITEMS SHALL NOT BE LESS THAN 90 PERCENT OF THE NOMINAL THICKNESS AT ANY LOCATION.
- 3. WHERE SECTION OR SUBSECTION MONUMENTS ARE ENCOUNTERED, THE ENGINEER SHALL BE NOTIFIED BEFORE SUCH MONUMENTS ARE REMOVED. THE CONTRACTOR SHALL PROTECT AND CAREFULLY PRESERVE ALL PROPERTY MARKERS AND MONUMENTS LINTIL THE OWNER AND AN AUTHORIZED SURVEYOR OR AGENT, HAS TNESSED OR OTHERWISE REFERENCED THEIR LOCATION.
- ALL ELEVATIONS SHOWN REFER TO THE U.S.G.S. DATUM AT SEA LEVEL, UNLESS OTHERWISE NOTED.
- UTILITIES ARE SHOWN IN ACCORDANCE WITH THE BEST AVAILABLE INFORMATION, AND THEIR TRUE LOCATION IS NOT GUARANTEED TO BE AS SHOWN ON THE PLANS. IT WILL BE THE CONTRACTOR'S RESPONSIBILITY TO DETERMINE THE EXACT LOCATION OF ALL UTILITIES AND CARRY OUT HIS OR HER OPERATIONS ACCORDINGLY.
- 6. THE FOLLOWING UTILITIES HAVE FACILITIES WITHIN THE LIMITS OF CONSTRUCTION:

CITY OF QUINCY	SANITARY SEWER	730 MAINE ST, QUINCY, IL	217-228-4555
CITY OF QUINCY	WATER	730 MAINE ST, QUINCY, IL	217-228-4580
AMERITECH	TELEPHONE	601 BROADWAY, QUINCY IL.	217-224-9961
MCLEOD USA	TELEPHONE	510 MAINE ST. QUINCY, IL	217-228-7900
AMEREN CIPS		700 JERSEY, QUINCY, IL	1-800-789-247
AMEREN CIPS	GAS	700 JERSEY, QUINCY, IL	217-257-7604
INSIGHT COMMUNICATIONS	CABLE	2930 STATE ST. QUINCY, IL	217-222-5388

- ADJUSTMENTS OF UTILITY LOCATIONS SHALL BE MADE BY THE OWNER, UNLESS OTHERWISE NOTED.
- 8. THE DEPTH OF DRAINAGE STRUCTURES MAY BE ADJUSTED VERTICALLY DUE TO CONFLICTS WITH OTHER UTILITY LINES AS APPROVED BY THE ENGINEER. THIS WORK WILL BE CONSIDERED INCIDENTAL TO THE UNIT PRICE BID FOR THE DRAINAGE STRUCTURE AND NO ADDITIONAL COMPENSATION WILL BE ALLOWED.
- 9. ANY REFERENCE TO A STANDARD IN THESE PLANS SHALL BE INTERPRETED TO MEAN THE EDITION, AS INDICATED BY THE SUB-NUMBER ON THE COVER SHEET.
- ALL DETAILS IN THESE PLANS SHALL GOVERN THE CONSTRUCTION OF THIS PROJECT, AND IN CASE OF CONFLICT WITH ANY STANDARD DRAWINGS INCLUDED, THE SAID DETAILS SHALL GOVERN.
- EXISTING GROUND ELEVATIONS AND TOPOGRAPHY WERE OBTAINED FROM AERIAL SURVEY AND 2 FOOT CONTOURS. FIELD CONDITIONS MAY VARY FROM THOSE SHOWN IN THE PLANS. THE CONTRACTOR SHALL VERIFY PROFILES AND ELEVATIONS BEFORE ORDERING STORM SEWERS, PIPE CULVERTS, AND INLETS. THE CONTRACTOR SHALL CONTACT THE ENGINEER WHEN DISCREPENCIES ARISE THAT PREVENT THE PROJECT FROM BEING CONSTRUCTED AS SHOWN IN THE PLANS.
- ······· 12. ALL PEDESTRIAN TRUSS SUPERSTRUCTURES SHALL BE WEATHERING STEEL CONFORMING TO AASHTO M270 GRADE 50W (M270M 345W).

## RATES OF APPLICATION TABLE

AGGREGATE (SURFACE, BASE, BASE, OR BACKFILL) SUBBASE GRANULAR MATERIAL, TYPE C STONE DUMPED RIPRAP

2.05 TON/CU YD 1.80 TON/CU YD 1.50 TON/CU YD

HOT-MIX ASPHALT:

HOT-MIX ASPHALT:
BITUMINOUS MATERIALS (PRIME COAT)
BITUMINOUS MATERIALS (PRIME COAT)
AGGREGATE PRIME COAT
HOT-MIX ASPHALT SURFACE / BINDER
HOT-MIX ASPHALT SURFACE MIX D OR E

0.00038 TON/SQ YD (ON PAVEMENT) 0.001425 TON/SQ YD (ON AGGREGATE) 0.002 TON/SQ YD 0.056 TON/SQ YD\*IN 0.060 TON/SQ YD\*IN

CONTRACT NO. 93454

SECTION COUNTY TOTAL SHEETS NO. 99-P4003-01-BT ADAMS 92 2 TO STA.

SEEDING AREAS:
NITROGEN FERTILIZER NUTRIENT
PHOSPHOROUS FERTILIZER NUTRIENT
POTASSIUM FERTILIZER NUTRIENT
AGRICULTURAL GROUND LIMESTONE

90 LBS/ACRE 90 LBS/ACRE
90 LBS/ACRE
90 LBS/ACRE
2 TON/ACRE
2 TON/ACRE
100 LBS/ACRE PER APPLICATION

MULCH
TEMPORARY EROSION CONTROL SEEDING SUPPLEMENTAL WATERING

SELECTIVE CLEARING

LUNIT = 1000 GALLON 1 UNIT = 1000 SQ FT

## COMMITMENTS

minimum minimu

THE ENTRANCE INTO THE LEWISTOWN HEET AND OIL COMPANY (HEETCO) PROPERTY OFF OF NORTH IZTH STREET SHALL NOT BE CLOSED TO TRAFFIC. NO EQUIPMENT, VEHICLES, OR MATERIALS MAY BE STORED ON THE HEETCO PROPERTY OUTSIDE THE PERMANENT EASEMENT. THE CONTRACTOR MAY UTILIZE THE CONSTRUCTION ACCESS POINT AT STATION 4-00 ON THE IZTH STREET BYPASS DURING NORMAL BUSINESS HOURS (8:00 AM TO 5:00 PM, MONDAY FRIDAY) GNUY. THE CONTRACTOR SHALL REPAIR ANY DAMAGE TO THE PRIVATE DRIVE CAUSED BY CONSTRUCTION ACTIVITIES AND SHALL TAKE CARE NOT TO TRACK MUD OR OTHER DEBRIS

The same of the sa

STANDARDS, GENERAL NOTES, AND APPLICATION RATES

99-P4003-01-BT QUINCY PARK DISTRICT, ADAMS COUNTY DRAWN BY SEB

SCALE: VERT. NONE HORIZ. DATE 2/1/2008

CHECKED BY

4/3/200 20.0000 20.0000 sea

DATE NAME SCALE NAME PLOT PLOT USER