NO SUBSTITUTIONS OR VARIANCES WILL BE PERMITTED TO ANY STANDARD NOTES OR ORDINANCES UNLESS APPROVED OTHERWISE IN WRITING PRIOR TO COMMENCING CONSTRUCTION ACTIVITY.

ALL TRAFFIC CONTROL AND OTHER ADVISORY SIGNS NEEDED FOR CONSTRUCTION ARE TO BE FURNISHED BY THE CONTRACTOR IN ACCORDANCE WITH ARTICLE 107.14 OF THE STANDARD

THE CONTRACTOR SHALL AT ALL TIMES PROVIDE PROTECTION FOR TRAFFIC AS CALLED FOR IN THE APPLICATION OF TRAFFIC CONTROL DEVICES, THE STANDARD SPECIFICATIONS, THE SPECIAL PROVISIONS AND THE PLANS

## UTILITIES

THE CONTRACTOR SHALL COOPERATE WITH THE VILLAGE OF LAKE IN THE HILLS, MCHENRY COUNTY AND STATE IF ANY UTILITY IMPROVEMENTS ARE REQUIRED BY THE VILLAGE. COUNTY OR STATE WITHIN THE DURATION OF THE CONTRACT.

THE CONTRACTOR SHALL BE RESPONSIBLE FOR CONTACTING THE OWNERS OF ALL UTILITIES PRIOR TO CONSTRUCTION TO DETERMINE THE LOCATION OF ALL EXISTING AND PROPOSED. UTILITY EQUIPMENT. THE CONTRACTOR SHALL COOPERATE WITH ALL UTILITY OWNERS AS PROVIDED FOR IN THE STANDARD SPECIFICATIONS IF UTILITY RELOCATION, ADJUSTMENT. OR PROTECTION IS NECESSARY.

THE LOCATION OF EXISTING DRAINAGE STRUCTURES, STORM SEWERS, WATER MAINS, SANITARY SEWERS, FIELD TILES AND ANY OTHER PUBLIC OR PRIVATE UTILITIES AS SHOWN ON THE PLANS IS APPROXIMATE AND NOT NECESSARILY COMPLETE: THEIR EXACT LOCATION IS TO BE DETERMINED IN THE FIELD BY THE CONTRACTOR. THIS WORK SHALL BE CONSIDERED INCLUDED IN THE COST OF THE CONTRACT.

THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROTECTION OF ALL UNDERGROLING AND SURFACE UTILITIES EVEN THOUGH THEY MAY NOT BE SHOWN ON THE PLANS. ANY UTILITY THAT IS DAMAGED DURING CONSTRUCTION SHALL BE RESTORED TO A CONDITION EQUAL TO THAT EXISTING BEFORE THE DAMAGE OCCURRED. THIS WORK SHALL BE ARRANGED BY THE UTILITY COMPANY AND SHALL BE AT THE CONTRACTOR'S EXPENSE.

IF EXISTING UTILITY LINES OF ANY NATURE ARE ENCOUNTERED WHICH CONFLICT IN LOCATION WITH NEW CONSTRUCTION, THE CONTRACTOR SHALL NOTIFY THE ENGINEER SO THAT THE CONFLICT MAY BE RESOLVED.

UNDER NO CIRCUMSTANCES SHALL THE CONTRACTOR OPERATE ANY VALVES OR HYDRANTS.

THE CONTRACTOR SHALL PROTECT AND CAREFULLY PRESERVE ALL SECTION OR SUBSECTION MONUMENTS, PROPERTY CORNERS, AND REFERENCE MARKERS UNTIL THE OWNER, THE OWNER'S AGENT, OR AN AUTHORIZED SURVEYOR HAS WITNESSED OR OTHERWISE REFERENCED THEIR

ALL RADII FOR PROPOSED CURB AND GUTTER ARE TO THE BACK OF CURB, UNLESS OTHERWISE NOTED. CURB AND GUTTER ELEVATIONS SHOWN AT POINTS OF CURVE, ETC., ARE BACK OF CURB, UNLESS OTHERWISE NOTED.

STRUCTURE OFFSET LOCATIONS GIVEN ON THE DETAILED PLANS ARE TO THE FOLLOWING POINTS:

A) STRUCTURES FALLING IN THE CURB LINE ARE MEASURED TO THE BACK OF CURB B) ALL OTHER STRUCTURES ARE MEASURED TO THE CENTER OF THE STRUCTURE

ALL ELEVATIONS ARE ON U.S.G.S. DATUM, NAVD 88.

ALL OFFSET LOCATIONS GIVEN ON THE DETAILED PLANS FOR STRUCTURES. EDGE OF PAVEMENT, ETC., ARE FROM THE CENTERLINES AS SHOWN ON THE PLANS.

# SEWERS AND WATER MAINS

ANY LOOSE MATERIAL DEPOSITED IN THE FLOW LINE OF DRAINAGE STRUCTURES WHICH OBSTRUCTS THE NATURAL FLOW OF WATER SHALL BE REMOVED AT THE CLOSE OF EACH WORKING DAY. PRIOR TO ACCEPTANCE OF THE IMPROVEMENT, ALL DRAINAGE STRUCTURES SHALL BE FREE OF DIRT AND DEBRIS. THIS WORK WILL NOT BE PAID FOR SEPARATELY. IT SHALL BE CONSIDERED INCLUDED IN THE COST OF THE CONTRACT.

WHEN EXISTING DRAINAGE FACILITIES ARE DISTURBED, THE CONTACTOR SHALL PROVIDE AND MAINTAIN IN AN OPERATING CONDITION TEMPORARY OUTLIETS AND CONNECTIONS FOR ALL DRAINS, SEWERS, AND CATCH BASINS. THE CONTRACTOR SHALL PROVIDE FACILITIES WHICH HAVE THE CAPACITY TO RECEIVE AND DISCHARGE THE STORM WATER FLOW RATES NORMALLY ACCEPTED AND RELEASED BY EXISTING DRAINAGE FACILITIES. THIS WORK WILE NOT BE PAID FOR SEPARATELY, BUT SHALL BE CONSIDERED INCLUDED IN THE COST OF THE CONTRACT.

THE COST OF INTERCONNECTIONS BETWEEN THE PROPOSED AND EXISTING SEWER SYSTEMS AND PROPOSED AND EXISTING WATER MAIN SYSTEMS SHALL BE INCLUDED IN THE VARIOUS UNIT PRICES ON THE ITEMS BEING CONNECTED.

ALL FRAMES WITH CLOSED LIDS TO BE FURNISHED AS PART OF THIS CONTRACT FOR ANY MANHOLE, CATCH BASIN OR INLET SHALL HAVE CAST INTO THE LID: "STORM". ANY ADDITIONAL COST FOR THIS REQUIREMENT SHALL BE CONSIDERED INCLUDED IN THE COST OF THE FRAME AND CLOSED LID PROVIDED.

FRAME ELEVATIONS GIVEN ON THE PLANS ARE ONLY TO ASSIST THE CONTRACTOR IN DETERMINING THE APPROXIMATE OVERALL HEIGHT OF THE STRUCTURE. FRAMES ON ALL STRUCTURES WILL BE ADJUSTED TO THE FINAL ELEVATION AND CROSS SLOPE OF THE AREA IN WHICH THEY ARE LOCATED, ALL FINAL ADJUSTMENTS OF FRAMES WHIL BE ACCOMPLISHED BY THE USE OF CONCRETE ADJUSTING RINGS SET IN BUTYL ROPE JOINT SEALANT; MORTAR JOINTS WILL NOT BE ALLOWED. HEIGHT OF ADJUSTING RINGS SHALL NOT EXCEED EIGHT INCHES (8"). THE COST OF THE ADJUSTMENT TO FINAL ELEVATION IS INCLUDED IN THE COST OF THE ITEM CONSTRUCTED.

ALL STORM SEWERS SHALL BE RCCP CLASS IV, UNLESS NOTED OTHERWISE ON THE PLAN.

ALL TRENCH BACKFILL QUANTITIES FOR STORM SEWER HAVE BEEN COMPUTED AND SHALL BE PAID FOR IN ACCORDANCE WITH THE STATE OF ILLINOIS, DEPARTMENT OF TRANSPORTATION, DIVISION OF HIGHWAYS, BUREAU OF CONSTRUCTION TRENCH BACKFILL

STORM SEWER, WATER MAIN AND SANITARY SEWER SHALL BE BACKFILLED IN ACCORDANCE WITH ARTICLE 550,07, METHOD 1 ONLY, OR AS DIRECTED BY THE ENGINEER, WITH THE FOLLOWING MODIFICATIONS.

TRENCH BACKFILL SHALL BE GRADATION CA-6. THE FINAL TRENCH BACKFILL SHALL BE PLACED IN 6" LIFTS AND SHALL BE COMPACTED IN PLACE TO NINETY FIVE PERCENT (95%) OF MAXIMUM DENSITY AT CPTIMUM MOISTURE AS DETERMINED BY THE MODIFIED PROCTOR

### SIGNS

PRIOR TO THE START OF CONSTRUCTION, THE CONTRACTOR AND ENGINEER SHALL INVENTORY THE LOCATION, SIZE, TYPE, AND CONDITION OF ALL EXISTING SIGNS. ANY SIGN DAMAGED DURING CONSTRUCTION SHALL BE REPLACED AT THE CONTRACTOR'S EXPENSE

ALL SIGNS SHALL BE ERECTED IN STRICT CONFORMANCE WITH SECTION 720 OF THE STANDARD SPECIFICATIONS AND BY STATE PREQUALIFIED CONTRACTOR PERSONNEL SUCH AS A SUBCONTRACTOR THAT SPECIALIZES IN TRAFFIC CONTROL AND SIGN PLACEMENT, TO ENSURE THIS OPERATION IS PERFORMED CORRECTLY THERE WILL BE A WALKTHROUGH ON THE JOB WITH THE ENGINEER AND MCHENRY COUNTY DOT MAINTENANCE PERSONNEL AS PART OF

ALL WORK INVOLVING SIGNS SHALL BE GOVERNED BY THE FOLLOWING REQUIREMENTS:

1. SIGNS SHALL NOT BE MOVED UNTIL PROGRESS OF WORK NECESSITATES IT

2. THE CONTRACTOR WILL BE REQUIRED TO TEMPORARILY RESET ALL SIGNS THAT INTERFERE WITH THEIR WORK DURING CONSTRUCTION OPERATIONS. ALL SUCH SIGNS MUST BE MAINTAINED STRAIGHT AND CLEAN FOR THE DURATION OF THE TEMPORARY SETTING. THE SIGNS MUST BE RE-ERECTED AT A TEMPORARY LOCATION IN A WORKMANLIKE MANNER AND BE VISIBLE TO TRAFFIC FOR WHICH IT IS INTENDED. THIS WORK WILL BE INCLUDED

ALL SIGNS SHALL BE INSTALLED OR RELOCATED IN PERMANENT LOCATIONS AS SHOWN ON THE PLANS ONCE THE ROADWAY IS COMPLETED. THIS WORK SHALL BE PAID FOR

4. ALL REMOVED SIGNS WILL BE RETURNED TO THE VILLAGE (600 HARVEST GATE, LAKE IN THE HILLS), COUNTY (16111 NELSON ROAD, WOODSTOCK) OR STATE, AS APPLICABLE.

5. LONGER POSTS MAY BE REQUIRED AT TEMPORARY OR PERMANENT SIGN LOCATIONS TO MAINTAIN PROPER SIGN HEIGHT.

# MISCELL ANEOUS

SAWING OF REMOVAL ITEMS AS NOTED ON THE PLANS, SPECIFIED IN THE STANDARD SPECIFICATIONS, OR AS REQUIRED BY THE ENGINEER SHALL BE INCLUDED IN THE COST OF THE ITEM BEING REMOVED.

THE THICKNESS OF ASPHALT MIXTURES SHOWN IN THE PLANS ARE NOMINAL. DEVIATIONS MAY OCCUR DUE TO IRREGULARITIES IN THE SURFACES OR BASES ON WHICH THE ASPHALT MIXTURES ARE TO BE PLACED.

PROTECTIVE COAT SHALL BE APPLIED TO ALL GUTTER FLAGS, FACE AND TOP OF CURB, TOP OF BICYCLE RACK CONCRETED PAD, AND AS DIRECTED BY THE ENGINEER.

THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING FRESH CONCRETE FROM DAMAGE AND VANDALISM, ANY DAMAGED OR VANDALIZED CONCRETE SHALL BE REMOVED AND REPLACED AT THE CONTACTOR'S EXPENSE.

THE CONTRACTOR SHALL BE REQUIRED TO MAKE ARRANGEMENTS FOR THE PROPER BRACING. SHORING AND OTHER REQUIRED PROTECTION OF ALL ROADWAYS, STRUCTURES, POLES, CABLES AND PIPE LINES, BEFORE CONSTRUCTION BEGINS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DAMAGE TO THE STREETS OR ROADWAYS AND ASSOCIATED STRUCTURES AND SHALL MAKE REPAIRS AS NECESSARY TO THE SATISFACTION OF THE ENGINEER AND COUNTY AT THEIR OWN EXPENSE. ANY SHEETING AND/OR SHORING USED FOR THIS IMPROVEMENT SHALL BE CONSIDERED INCLUDED IN THE COST OF THE CONTRACT.

THE CONTRACTOR SHALL PROTECT ALL EXISTING FACILITIES (E.G. CURB, PAVEMENT) THAT ARE NOT INDICATED TO BE REMOVED ON THE PLANS. ANY FACILITY THAT IS DAMAGED DURING CONSTRUCTION SHALL BE RESTORED TO A CONDITION EQUAL TO THAT EXISTING BEFORE THE DAMAGE OCCURRED.

EXISTING PAVEMENT THICKNESSES SHOWN ON THE PLANS ARE APPROXIMATE, BASED ON AVAILABLE INFORMATION AT THE TIME OF DESIGN. ANY ADDITIONAL COSTS REQUIRED BY THE CONTRACTOR DUE TO THICKNESSES OTHER THAN THOSE SHOWN ON THE PLANS WILL BE INCLUDED IN THE COST OF THE CONTRACT.

WHERE NEW WORK MEETS EXISTING FEATURES TO REMAIN, THE CONTRACTOR SHALL FIELD CHECK ALL DIMENSIONS AND ELEVATIONS BEFORE PROCEEDING WITH CONSTRUCTION. IMMEDIATELY NOTIFY THE ENGINEER OF ANY DISCREPANCIES.

THE CONTRACTOR WILL BE REQUIRED TO COMPLY WITH ALL STATE REGULATIONS REGARDING AIR, WATER AND NOISE POLLUTION. THE CONTRACTOR IS PROHIBITED FROM BURNING ANY MATERIAL WITHIN OR ADJACENT TO THE IMPROVEMENT.

THE CONTRACTOR SHALL PREPARE THE SUBGRADE IN ACCORDANCE WITH ARTICLE 301.03 OF THE STANDARD SPECIFICATIONS PRIOR TO THE REMOVAL OF ANY UNSTABLE MATERIALS.

ALL DISTURBED AREAS WITHIN THE PROJECT THAT ARE NOT OTHERWISE SURFACED SHALL BE CLEANED, LAYERED WITH TOPSOIL, AND SEEDED AS SHOWN IN THE PLANS. LIMITS SHOWN ON THE PLANS ARE THE MAXIMUM PAY WIDTHS FOR PAYMENT PURPOSES. ADDITIONAL AREAS DAMAGED BY MACHINERY, CONSTRUCTION EQUIPMENT, CONTRACTOR NEGLIGENCE OR OVER-EXCAVATION SHALL BE RESTORED TO A CONDITION EQUAL TO THAT EXISTING BEFORE THE DAMAGE OCCURRED AT THE COST OF THE CONTRACTOR.

THE CONTRACTOR SHALL DISPOSE OF AND REMOVE FROM THE SITE EACH DAY ALL CURB AND GUTTER, PAVEMENT AND ALL OTHER EXCAVATED MATERIAL NOT FOR SALVAGE. THE COST FOR HAULING AND TRUCKING TO DISPOSAL LOCATIONS WILL BE INCLUDED IN THE COST OF THE ITEM BEING REMOVED.

THE ACTUAL NEED FOR REMOVAL OF UNSTABLE SOILS AND REPLACEMENT WITH ACGREGATE SUBGRADE IMPROVEMENT WILL BE DETERMINED IN THE FIELD AT THE TIME OF CONSTRUCTION BY THE ENGINEER (BY USE OF CONE PENETROMETER IN CONJUNCTION WITH THE IDOT SUBGRADE STABILITY MANUAL). IF UNSTABLE SOILS ARE ENCOUNTERED, THE SOILS SHALL BE REMOVED AND REPLACED WITH AGGREGATE SUBGRADE IMPROVEMENT. IF UNSTABLE SOILS ARE NOT ENCOUNTERED. THEN THE QUANTITY WILL BE DEDUCTED FROM THE CONTRACT WITH NO ADDITIONAL COMPENSATION PAID TO THE CONTRACTOR. GEOTECHNICAL FABRIC FOR GROUND STABILIZATION SHALL BE PLACED AT ALL LOCATIONS REQUIRING REMOVAL AND DISPOSAL OF UNSUITABLE MATERIAL AND AGGREGATE SUBGRADE IMPROVEMENT AS APPROVED BY THE ENGINEER.

BITUMINOUS MATERIALS (PRIME COAT) SHALL BE APPLIED AT A RATE OF O.1 GALLONS PER SQUARE YARD ON ASPHALT AND 0.5 GALLONS PER SQUARE YARD ON AGGREGATE. BITUMINOUS MATERIALS SHALL BE SS-1 ON ASPHALT AND MC-30 ON AGGREGATE.

AT LOCATIONS WHERE THE PROPOSED CURB AND GUTTER IS TO BE CONSTRUCTED ACROSS TRENCHES OR WITHIN THREE FEET OF THE CLOSE EDGE OF ANY TRENCH, TWO (2) NO. 4 REINFORCEMENT BARS SHALL BE PLACED IN THE PROPOSED CLITTER. THESE REINFORCEMENT BARS SHALL NOT BE CONTINUOUS THROUGH TRANSVERSE EXPANSION JOINTS, BUT SHALL BE STOPPED 3" SHORT OF THE EXPANSION JOINT, COST OF THESE REINFORCEMENT BARS. COMPLETE IN PLACE, SHALL BE INCLUDED IN THE COST FOR THE CURB AND GUTTER.

THE ENGINEER AND COUNTY ARE NOT RESPONSIBLE FOR THE CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES OR PROCEDURES, TIME OF PERFORMANCE, PROCRAMS OR FOR ANY SAFETY PRECAUTIONS USED BY THE CONTRACTOR. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR EXECUTION OF THEIR WORK IN ACCORDANCE WITH THE CONTRACT DOCUMENTS AND SPECIFICATIONS.

THE CONTRACTOR SHALL COORDINATE THEIR WORK WITH THE WORK PERFORMED LINDER SEPARATE CONTRACT FOR IL 31 AND VIRGINIA ROAD IMPROVEMENTS CONTRACT NO. 63553.

IT IS THE CONTRACTOR'S RESPONSIBILITY TO ASCERTAIN EXISTING FIELD CONDITIONS
BEFORE BIDDING ON THIS CONTRACT, CONTRACT PLANS INDICATE EXISTING CONDITIONS ANTICIPATED UPON COMPLETION OF THE IL 31 AND VIRGINIA ROAD IMPROVEMENTS, AS SHOWN ON THE CONTRACT NO. 63553 PLANS.

SCALE: N/A

## SEWER STRUCTURE AND PIPE NOTATION

PIPE DIAMETER —— 12" STORM SEWER

SEWER TYPE —— TYPE 1 RCCP CL IV — PIPE CLASS

LENGTH —— 57 LF @ 2.68% —— SLOPE

TRENCH BACKFILL QUANTITY —— TB 14.3 CY, 5" —— TRENCH BACKFILL LENGTH

## SUPPLEMENTAL LEGEND

======== EXISTING CURB OR CURB & GUTTER BEREINSBERICHTER PROPOSED REVERSE PITCH GUTTER PROPOSED CURB OR CURB & GUTTER ----- 705 ----- PROPOSED INDEX CONTOUR 

## HIGHWAY STANDARDS

000001-06 STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS 280001-07 TEMPORARY EROSION CONTROL SYSTEMS 542301-03 PRECAST REINFORCED CONCRETE FLARED END SECTION 602001-02 CATCH BASIN TYPE A 602011-02 CATCH BASIN TYPE C 602301-03 INLET - TYPE A 602401-03 MANHOLE TYPE A 602416-03 MANHOLE TYPE A 8' DIAMETER 602601-02 PRECAST REINFORCED CONCRETE FLAT SLAB TOP 602701-02 MANHOLE STEPS 604001-03 FRAME AND LIDS TYPE 1 604036-02 GRATE TYPE 8 604051-03 FRAME AND GRATE TYPE 11 606001-05 CONCRETE CURB TYPE B AND COMBINATION CURB AND GUTTER 701101-03 OFF-RO OPERATIONS, MULTILANE, 15' (45 M) TO 24" (600 MM)

FROM PAVEMENT EDGE 701106-02 OFF-RD OPERATIONS, MULTILANE, MORE THAN 15' (45 M) AWAY 701421-05 LANE CLOSURE, MULTILANE, DAY OPERATIONS ONLY, FOR

SPEEDS > 45 MPH TO 55 MPH

701601-08 URBAN LAME CLOSURE, MULTILANE, 1W OR 2W WITH NONTRAVERSABLE MEDIAN 701901-02 TRAFFIC CONTROL DEVICES 720001-01 SIGN PANEL MOUNTING DETAILS 720006-03 SIGN PANEL ERECTION DETAILS

728001-01 TELESCOPING STEEL SIGN SUPPORT 731001-01 BASE FOR TELESCOPING STEEL SIGN SUPPORT

780001-03 TYPICAL PAVEMENT MARKINGS

COPYRIGHT 2011 ENGINEERING ENTERGUISES IN