



Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

April 16, 2024

SUBJECT: FAP Route 681 (IL 116)
Section (849E)MG, RS
Iroquois County
Contract No. 66N44
Item No. 54, April 26, 2024 Letting
Addendum A

NOTICE TO PROSPECTIVE BIDDERS:

Attached is an addendum to the plans or proposal. This addendum involves revised and/or added material.

1. Revised page 5 of the Special Provisions.
2. Revised sheet 2 of the Plans.

Prime contractors must utilize the enclosed material when preparing their bid and must include any changes to the Schedule of Prices in their bid.

Very truly yours,

A handwritten signature in black ink, appearing to read "Jack A. Elston".

Jack A. Elston, P.E.
Bureau Chief, Design and Environment

Removing the existing HMA surface to the required depth adjacent to structures in the pavement surface such as drain castings and utility covers shall be accomplished in a manner satisfactory to the Engineer using either machine or hand methods. Castings for existing utility or drainage structures within the pavement which are exposed to traffic after the pavement has been milled shall be protected according to Article 603.07.

After the hot-mix asphalt surface and aggregate base course has been removed to the required 4" depth the existing aggregate base shall be compacted to the satisfaction of the Engineer.

Disposal of Removed Materials. Disposal of removed materials shall be follows.

- (a) Hot-Mix Asphalt surface and aggregate base course materials shall be removed and **disposed of off the right of way at an approved disposal site.**
- (b) If earthen materials are encountered within the removal limits, earthen material must remain on site and be located at a location designated by the Field technician.

Method of Measurement. This work will be measured for payment as follows.

- (a) Contract Quantities. The requirement for use of contract quantities shall be according to Article 202.07(a).
- (b) Measured Quantities. The work in connection with the hot-mix asphalt surface and aggregate base course removal will be measured for payment in place and the area computed in square yards.

Basis of Payment. The work in connection with the removal of the hot-mix asphalt surface and aggregate base course to the required depth including all compaction efforts will be paid for at the contract unit price per square yard for HOT-MIX ASPHALT SURFACE REMOVAL, SPECIAL which shall include the removal and disposal of the existing variable depth hot-mix asphalt (HMA) and aggregate base surfaces.

BASE CSE. REMOVAL (SPECIAL)

Description. This work shall consist of the removal of existing aggregate base course in preparation for subsequent resurfacing.

Equipment. Equipment shall be according to the following.

Item	Article/Section
(f) Pneumatic-Tired Rollers.....	1101.01
(g) Vibratory Rollers (Note 1)	
(h) Mechanical Sweeper.....	1101.03
(i) Self-Propelled Milling Machine.....	1101.16

Note 1. The vibratory rollers and tampers shall meet the approval of the Engineer.

Revised April 16, 2024