

Å	
$ \begin{array}{c c} \hline & & & & \\ \hline & & & $	
	o of locking ne rail

TYPICAL END TREATMENT AT SIDEWALK OR MEDIAN

Shorter plates with a single row of studs at 12" cts. may be necessary on medians which are shallower than 9". See manufacturer's recommendation.

Notes:

The strip seal shall be made continuous and shall have a minimum thickness of I_{4} ". The configuration of the strip seal shall match the configuration of the Locking Edge Rails. Open or "webbed" strip seal gland configurations are not permitted. The gland shall be sized for a maximum rated movement of 4 inches.

The Locking Edge Rails depicted are conceptual only, except for the minimum dimensions shown. The actual configuration of the Locking Edge Rails and matching strip seal may vary from manufacturer to manufacturer. Flanged edge rails will not be allowed. Locking Edge Rails may be spliced at slope discontinuities.

The manufacturer's recommended installation methods shall be followed.

The joint opening and deck dimensions detailed on the superstructure are based on a rolled rail expansion joint. If the Contractor elects to use the welded rail expansion joint, the opening and deck dimensions shall be modified according to the dimensions detailed on this sheet. Required modifications shall be made at no additional cost to the State.

All steel components shall be galvanized after fabrication according to Article 520.03 of the Standard Specifications. Maximum space between rail segments at stage lines shall be $\frac{3}{16}$ ", sealed with a suitable sealant.

Parapet plates and anchorage studs for skews > 30° included in the cost of Preformed Joint Strip Seal.

The strip seal shall be continuous through the median barrier, with no upturns. See Detail 1 on Sht. S-33 for similar details.

BILL OF MATERIAL

Unif	Total
Foot	98.0
	Unit Foot

IIP SEAL	F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	345	8R-R	KANE	794	504
	SN 045-0077		CONTRACT	NO. 6	50H45
STATION 98+32.18	FED. RO	DAD DIST. NO. 7 ILLINOIS FED. AI	D PROJECT		

Flush