

DRAINAGE AND UTILITY PIPE TABLES

NO.	LENGTH (FOOT)	MATERIAL	TYPE	DIA. (IN)	SLOPE (%)	TBF (CU. YD.)
P-1	7	SS, CL A	2	12	3.14	0.0
P-2	11	SS, CL A	2	12	0.82	0.0
P-3	80	SS, CL A	2	12	0.70	50.6
P-4	35	SS, CL A	2	12	0.71	0.0
P-5	35	SS, CL A	2	12	1.00	0.0
P-6	11	SS, CL A	2	12	1.00	3.9
P-7	74	SS, CL A	2	12	1.00	46.8
P-8	11	SS, CL A	2	12	1.00	3.9
P-9	9	SS, CL A	2	12	1.00	0.0
P-10	24	SS, CL A	2	12	1.00	0.0
P-11	74	SS, CL A	2	12	1.00	28.3
P-12	76	SS, CL A	2	12	1.58	48.0
P-13	11	SS, CL A	2	12	2.00	0.0
P-14	10	SS, CL A	2	12	2.00	1.6
P-15	10	SS, CL A	2	12	1.00	0.0
P-16	30	SS, CL A	2	12	1.00	0.0
P-17	48	SS, CL A	2	12	1.00	14.2
P-18	10	SS, CL A	2	12	2.00	0.0
P-19	5	SS, CL A	2	12	2.00	0.0
P-20	3	SS, CL A	2	12	1.00	0.0
P-21	84	SS, CL A	2	12	1.00	37.2
P-22	84	SS, CL A	2	12	2.36	58.5
P-23	6	SS, CL A	2	12	2.00	0.0
P-24	20	SS, CL B	2	4	5.00	3.7
P-25	90	SS, CL A	2	12	1.00	71.3
P-26	5	SS, CL A	2	12	1.00	0.0
P-27	151	SS, CL A	2	24	0.96	86.0
P-28	25	SS, CL A	2	12	1.00	12.7
P-29	25	SS, CL A	2	12	1.00	6.5
P-30	6	SS, CL A	2	12	0.50	0.0
P-31	57	SS, CL A	2	12	0.61	17.0
P-32	34	SS, CL A	2	12	0.62	9.5
P-33	148	SS, CL A	2	21	0.25	67.0
P-34	3	SS, CL A	2	12	1.00	2.1
P-35	94	SS, CL A	2	12	1.00	36.0
P-36	36	SS, CL A	2	12	1.00	11.5
P-37	104	SS, CL A	2	24	0.25	45.5
P-38	10	SS, CL A	2	12	1.70	0.0
P-39	99	SS, CL A	2	12	2.00	72.1
P-40	154	SS, CL A	2	39	0.63	148.6
P-41	45	SS, CL A	1	36	0.44	0.0
P-42	73	SS, WM REQ	-	12	1.00	50.8
P-43	50	SS, CL A	2	12	1.12	41.2
P-44	104	SS, WM REQ	-	12	0.50	228.5
P-46	9	SS, CL A	2	15	2.00	0.0
P-47	28	SS, CL A	2	12	1.00	0.6
P-48	9	SS, CL A	2	12	1.00	0.6
P-49	105	SS, CL A	2	12	1.00	53.3
P-50	10	SS, WM REQ	-	12	1.00	2.9
P-51	62	SS, WM REQ	-	12	2.00	53.1
P-52	30	SS, CL A	2	12	2.00	31.0
P-53	14	SS, CL A	2	12	2.20	0.0
P-54	142	SS, CL A	2	36	0.53	0.0
P-55	11	SS, CL A	2	12	1.00	0.0
P-56	95	SS, WM REQ	-	12	1.00	96.6
P-57	21	SS, WM REQ	-	12	1.10	9.8
P-58	91	SS, WM REQ	-	12	1.25	74.4
P-59	11	SS, CL A	2	12	1.55	0.0
P-60	221	SS, CL A	2	36	0.53	63.3
P-61	10	SS, CL A	2	12	1.80	0.0
P-62	89	SS, CL A	2	12	2.00	77.6
P-63	33	SS, WM REQ	-	12	1.00	1.0
P-64	83	SS, CL A	2	12	1.00	31.8
P-65	7	SS, CL A	2	12	1.00	5.0
P-66	10	SS, CL A	2	12	2.00	2.7
P-67	6	SS, CL A	2	12	3.00	0.0
P-68	81	SS, WM REQ	-	12	0.84	31.0
P-69	78	SS, WM REQ	-	12	1.00	38.8
P-70	10	SS, CL A	2	12	2.00	0.0
P-71	248	SS, CL A	2	30	0.89	80.6
P-72	12	SS, CL A	2	12	1.08	3.5
P-73	70	SS, WM REQ	-	12	0.50	23.1
P-74	10	SS, CL A	2	12	3.00	0.6
P-75	65	SS, WM REQ	-	12	1.38	24.9
P-76	12	SS, CL A	2	12	1.00	1.4
P-77	321	SS, CL A	2	30	0.89	36.1
P-78	3	SS, CL A	2	12	2.00	0.0
P-79	10	SS, CL A	2	12	2.00	0.0
P-80	64	SS, WM REQ	-	12	1.31	24.5
P-81	64	SS, WM REQ	-	12	0.59	23.2
P-82	4	SS, CL A	2	12	1.00	0.0
P-83	9	SS, WM REQ	-	12	1.00	0.0
P-84	64	SS, WM REQ	-	12	0.70	19.1
P-85	342	SS, CL A	2	27	1.38	20.1
P-86	8	SS, WM REQ	-	12	0.80	0.0
P-87	64	SS, WM REQ	-	12	0.80	23.9
P-88	67	SS, CL A, EORS	2	30x19	1.00	0.0
P-89	154	SS, CL A, EORS	2	30x19	0.80	79.5
P-90	103	SS, CL A, EORS	2	30x19	0.75	59.4
P-91	32	SS, CL A	2	12	0.50	2.6
P-92	33	SS, CL A	1	12	0.50	7.4
P-93	169	SS, CL A, EORS	2	30x19	1.00	19.2
P-94	5	SS, WM REQ	-	12	2.00	0.0
P-95	249	SS, CL A	2	21	1.00	23.6

DRAINAGE AND UTILITY PIPE TABLES

NO.	LENGTH (FOOT)	MATERIAL	TYPE	DIA. (IN)	SLOPE (%)	TBF (CU. YD.)
P-96	4	SS, CL A	2	12	1.00	0.0
P-97	4	SS, CL A	2	12	1.50	0.0
P-98	221	SS, CL A	2	18	1.00	19.4
P-99	11	SS, CL A	2	30	2.71	0.0
P-100	9	SS, WM REQ	-	30	2.71	0.0
P-101	69	SS, CL A	2	30	3.24	3.9
P-102	104	SS, WM REQ	-	12	0.50	57.8
P-103	203	SS, CL A	2	15	1.00	217.2
P-104	31	SS, CL A	2	12	6.84	10.6
P-105	22	SS, CL A	2	12	4.50	17.1
P-106	54	SS, CL A	2	12	0.50	22.1
P-107	24	SS, CL A	2	12	1.00	9.2
P-108	28	SS, CL A	2	12	1.00	14.2
P-109	28	SS, CL A	2	12	1.07	9.5
P-110	30	SS, CL A	2	12	1.02	10.2
P-111	16	SS, CL A	2	12	0.50	0.0
P-112	314	SS, CL A	2	18	1.00	374.6
P-113	29	SS, CL A	2	12	7.48	14.7
P-114	31	SS, CL A	2	12	3.00	25.5
P-115	32	SS, CL A	2	12	1.00	11.9
P-116	30	SS, CL A	2	12	1.00	11.2
P-117	42	SS, CL A	2	12	3.93	14.3
P-118	39	SS, CL A	2	12	3.10	24.6
P-119	227	SS, CL A	2	24	0.33	238.1
P-120	47	SS, WM REQ	-	12	2.64	23.9
P-121	41	SS, WM REQ	-	12	1.73	14.4
P-122	47	SS, CL A	2	12	0.50	16.0
P-123	77	SS, CL A, EORS	2	38x24	0.33	79.9
P-124	52	SS, CL A	2	12	0.50	32.9
P-125	64	SS, WM REQ	-	12	0.50	19.3
P-126	38	SS, CL A	2	12	0.50	15.2
P-127	52	SS, CL A, EORS	2	38x24	0.33	77.9
P-128	52	SS, CL A	2	12	0.50	19.4
P-129	45	SS, WM REQ	-	12	0.50	17.2
P-130	90	SS, CL A, EORS	2	38x24	0.33	82.1
P-131	42	SS, WM REQ	-	12	0.50	12.6
P-132	41	SS, WM REQ	-	12	1.00	36.3
P-133	51	SS, WM REQ	-	12	0.50	19.5
P-134	11	SS, CL A	2	12	0.50	0.0
P-135	88	SS, WM REQ	-	12	0.50	66.9
P-136	56	SS, CL A	2	30	0.63	66.1
P-137	112	SS, CL A	2	30	0.63	57.7
P-138	8	SS, CL A	2	12	1.00	2.8
P-139	15	SS, CL A	2	30	0.63	66.1
P-140	15	SS, CL A	2	30	0.63	66.1
P-141	15	SS, CL A	2	30	0.63	66.1
P-142	31	SS, CL A	2	12	1.00	23.6
P-143	63	SS, CL A	2	12	1.00	40.8
P-144	47	SS, CL A	1	30	0.75	0.0
P-145	190	SS, CL A	2	30	1.30	157.3
P-146	15	SS, CL A	2	12	1.00	0.0
P-147	5	SS, CL A	2	12	1.00	0.0
P-148	93	SS, CL A	2	12	1.00	58.8
P-149	82	SS, CL A	2	12	1.00	31.4
P-150	5	SS, CL A	2	12	1.00	0.0
P-151	165	SS, CL A	2	27	1.20	0.0
P-152	9	SS, CL A	2	12	1.89	0.0
P-153	80	SS, CL A	2	12	2.01	65.9
P-154	220	SS, CL A	2	24	1.50	110.0
P-155	6	SS, CL A	2	12	1.00	0.0
P-156	69	SS, CL A	2	12	0.80	76.8
P-157	32	SS, CL A	2	12	0.80	0.0
P-158	64	SS, CL A	2	12	1.50	49.7
P-159	8	SS, CL A	2	12	1.50	0.0
P-160	9	SS, CL A	2	12	2.00	0.0
P-161	57	SS, CL A	2	12	2.00	47.9
P-162	311	SS, CL A	2	21	1.50	97.8
P-163	6	SS, CL A	2	12	1.00	0.0
P-164	52	SS, CL A	2	12	1.00	19.4
P-165	52	SS, CL A	2	12	2.00	42.8
P-166	9	SS, CL A	2	12	2.00	0.0
P-167	210	SS, CL A	2	18	1.80	74.0
P-168	63	SS, CL A	2	18	1.80	22.1
P-169	86	SS, CL A	2	12	1.00	46.7
P-170	35	SS, CL A	1	12	1.00	0.0
P-171	21	SS, CL A	1	36	0.11	0.0
P-172	94	SS, CL A	2	36	0.10	41.6
P-173	75	PRC BOX CUL	-	4'x2'	1.60	11.0

DRAINAGE AND UTILITY STRUCTURE TABLES

STRUCT. NO.	STATION	OFFSET	STRUCTURE TYPE	RIM	INVERT NORTH	SOUTH	EAST	WEST
S-1	109+62	42' RT	CB TA 4' DIA T24 F&G	874.95	-	-	869.95	-
S-2	110+00	56' LT	INLET TA T8G	873.60	870.60 (NE)	-	-	-
S-3	110+32	37.5' LT	CB TA 4' DIA T24 F&G	874.57	-	870.35 (SW)	870.25	-
S-4	110+60	37.5' RT	CB TA 4' DIA T24 F&G	874.53	-	-	869.59	869.69
S-5	111+26	55' LT	INLET TA T8G	874.57	870.57	-	-	-
S-6	111+57	37.5' LT	CB TA 4' DIA T24 F&G	874.14	870.03	870.22	869.93	-
S-7	111+57	37.5' RT	CB TA 4' DIA T24 F&G	874.24	870.11	-	869.09	869.19
S-8	111+57	51' RT	DRYWELL 5' DIA T8G	872.27	868.50	868.53	-	869.00
S-9	111+73	37.5' LT	CB TA 4' DIA T24 F&G	874.14	-	870.14	-	-
S-10	111+73	37.5' RT	CB TA 4' DIA T24 F&G	874.22	-	870.22	-	-
S-11	112+47	38' LT	CB TC T24 F&G	874.37	-	-	870.37	-
S-12	112+47	37.5' RT	CB TA 4' DIA T24 F&G	874.47	869.53 (NE)	-	-	869.63
S-13	112+72	51' RT	EX	874.37	868.25	868.25	-	869.29 (SW)
S-14	113+26	40' LT	CB TC T24 F&G	874.66	-	-	870.66	-
S-15	113+26	37.5' RT						