

plan

10-16-06 REVISED RR3 QUALITY & TO 2007 SPEC.

## NOTES:

- 1. FOR DITCH BOTTOM PROTECTED BY EXCELSIOR BLANKET, USE 400'(120m) SPACING. FOR SEEDED DITCH BOTTOM, USE 200'(60m) SPACING.
- 2. THIS WORK CONSISTS OF THE COMPLETE INSTALLTION OF EROSION CONTROL DITCH CHECK AT LOCATIONS AS SHOWN ON THE PLANS, OR AS DIRECTED BY THE ENGINEER. THE AGGREGATE GRADATION SHALL BE RR3 WITH A MINIMUM QUALITY OF CLASS B.

LOCATION	NUMBER		DITCH					
		SIDE DITCH		OF DITCH	FORE	BOTTOM	BACK	BERM
STATION	MEDIAN	LEFT	RIGHT	CHECKS	SLOPE	WIDTH	SLOPE	SLOPE
13+00 TEMP RUNAROUND		X	x	2	4	2	3	10
9+00 TEMP RUNAROUND		x	×	2	4	2	3	10
	-		ļ					
	1		<b></b>					
	-		<del> </del>					
4								
			<del> </del>					ļ
	_		ļ					ļ
	-		<b> </b>					ļ
	1		<del> </del>					
								1

## ESTIMATE QUANTITIES

	FORE SLOPE	DITCH BOTTOM	BACK SLOPE	BERM SLOPE	AGGREGATE DITCH CHECK EROSION CONTROL METRIC TONITON)
MEDIAN DITCH	1:6	24(600)		1:10	95(86)
SIDE DITCH	1:6	24(600)	1:4	1:10 & 1:2	50(45)
SIDE DITCH	1:6	24(600)	1:4	1:2 & 1:2	19(17)
SIDE DITCH	1:4	24(600)	1:3	1:10 & 1:2	18(16)
SIDE DITCH	1:4	24(600)	1:3	1:2 & 1:2	14(13)
NN797-7					

NOT TO SCALE

All slope ratios are expressed as units of vertical displacement to units of horizontal displacement (V:H).

All dimensions are in inches (millimeters) unless otherwise noted.

SECTION COUNTY TOTAL SHEET NO. EROSION CONTROL AGGREGATE DITCH CHECK McDONOUGH 103 68 CONTRACT NO. 68A40 CADD STD. 280101-D4 FED. ROAD DIST. NO. | ILLINOIS