COMMITMENTS

No commitments have been made for this project.

GENERAL NOTES

Plan dimensions and details relative to existing plans are subject to routine variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished based upon the unit price bid for the work.

ENVIRONMENTAL REVIEWS

Prior to the use of any proposed borrow areas, use areas (temporary access roads, detours, run-arounds, etc.) and/or waste areas, the Contractor shall file the required environmental resource request surveys according to Section 107.22 of the Standard Specifications. These surveys are required in order for the Department to conduct cultural and biological resource surveys for the proposed site.

Prior to any waste materials being removed from the construction site the required environmental resource surveys will need to be obtained and filed by the Contractor. Excess waste products removed from the construction site shall be disposed of as required in Section 202.03 of the Standard Specifications.

Any protruding metal bars shall be removed prior to the disposal of broken concrete at approved disposal sites.

The required environmental resource documentation shall include the following:

- * BDE Form 2289 (Environmental Survey Request)
- * A location map showing the size limits and location of the use area
- * Signed property owner agreement form-D4 PI0100
- * Color photographs depicting the use area
- * Borrow Area Entry Agreement form-D4 PI0101

Please note that a minimum of two weeks shall be allowed for the District to obtain the required environmental clearances.

Reinforcement bars shall conform to the requirements of ASTM A 706 Grade 60 (IL. Modified). See Special Provisions.

Reinforcement bars disignated (E) shall be epoxy coated.

UTILITIES - LOCATIONS /INFORMATION ON PLANS

The locations and aproximate depths of existing water mains, gas mains, sewers, electric power lines, telephone lines and other utilities as shown on the plans are based on careful field investigation and the best information available, but they are not guaranteed. It shall be the Contractor's responsibility to ascertain exact location from the utility companies and by field inspection.

JOB SPECIFIC NOTES

Cleaning and metallizing of the existing structural concrete surfaces shall be as specified in the Special Provisions for "Thermal Spraying (Metallizing) Bridge Concrete Surface".

All metallized surfaces shall be sealed with an IDOT approved sealer applied at a DFT of one to two mils thickness.

The metallizing Contractor's prequalifications and Applicator's certification are not required to be met for this project. A technical representative from the metallizing equipment manufacturer shall be onsite and readily available for technical guidance and consultation for the first three days of metallizing work on the project. If performance passes all QC/QA tests and is proved satisfactory to the Engineer, the representative will no longer be required onsite, but shall remain available for future consultation on this project.

TRAFFIC CONTROL PLAN

- 1. "LANE CLOSURE, 2L, 2W, BRIDGE REPAIR WITH BARRIER" traffic control standard and additional plan sheet(s) shall be used during construction of this project.
- 2. On-site adjustments of traffic lane taper lengths or signage locations may be used to compensate for distance from construction work area to side road entrances.

ENT DRAFT STUARTING SUURDIAT BRADET SN. 823-8820

ILE NAME =	USER NAME = \$USER\$	DESIGNED -	REVISED -	Γ
FILEL\$		DRAWN -	REVISED -	ı
	PLOT SCALE = \$SCALE\$	CHECKED ~	REVISED -	1
	PLOT DATE = \$DATE\$	DATE -	BEVISED -	1

FULTON 14 2
CONTRACT: 68A58