

SCHEDULE OF QUANTITIES

RESURFACING QUANTITIES												
LOCATION	STATION	TO	STATION	LENGTH (FOOT)	WIDTH (FOOT)	AREA (SQ YD)	COLD MIX AVG. THICKNESS (INCH)	40600100 BITUMINOUS MATERIALS PRIME COAT (GAL)	#5000400 COLD MIX ASPHALT MIXTURE (TON)	LR400300 BLOTTER AGGREGATE (TON)	40300305 POLY. BIT. MAT. (COVERS & SEAL COAT) (GAL)	40300600 SEAL COAT AGGREGATE (TON)
MAINLINE QUANTITIES												
	216+81.50	TO	269+04.00	5,222.5	20.0	11,605.6	2.25	1,160.6	1,175.1	87.0	6,383.1	145.1
	269+04.00	TO	272+42.00	338.0	20.0	751.1	2.25	75.1	76.1	5.6	413.1	9.4
	272+42.00	TO	278+85.00	643.0	20.0	1,428.9	2.25	142.9	144.7	10.7	785.9	17.9
	278+85.00	TO	284+93.00	608.0	20.0	1,351.1	2.25	135.1	136.8	10.1	743.1	16.9
	284+93.00	TO	298+10.00	1,317.0	20.0	2,926.7	2.25	292.7	296.3	22.0	1,609.7	36.6
	298+10.00	TO	302+30.00	420.0	20.0	933.3	2.25	93.3	94.5	7.0	513.3	11.7
	302+30.00	TO	311+07.00	877.0	20.0	1,948.9	2.25	194.9	197.3	14.6	1,071.9	24.4
	311+07.00	TO	317+94.00	687.0	20.0	1,526.7	2.25	152.7	154.6	11.5	839.7	19.1
	317+94.00	TO	331+41.00	1,347.0	20.0	2,993.3	2.25	299.3	303.1	22.5	1,646.3	37.4
	331+41.00	TO	332+91.00	150.0	24.0	400.0	2.25	40.0	40.5	3.0	220.0	5.0
	333+63.00	TO	335+13.00	150.0	24.0	400.0	2.25	40.0	40.5	3.0	220.0	5.0
	335+13.00	TO	372+80.00	3,767.0	20.0	8,371.1	2.25	837.1	847.6	62.8	4,604.1	104.6
SUB-TOTAL =								3,463.7	3,507.0	259.8	19,050.2	433.0
INCIDENTAL QUANTITIES												
PE	239+86.10	RT				46.1	1.875	4.6	3.9	0.3	25.4	0.6
FE	245+56.80	RT				33.3	1.875	3.3	2.8	0.2	18.3	0.4
FE	245+56.80	LT				25.6	1.875	2.6	2.2	0.2	14.1	0.3
PE/MBTO	257+39.70	RT				36.8	1.875	3.7	3.1	0.3	20.2	0.5
SIDEROAD	267+72.84	LT				45.6	1.875	4.6	3.8	0.3	25.1	0.6
SIDEROAD	267+75.68	RT				39.9	1.875	4.0	3.4	0.3	21.9	0.5
MBTO	271+20.00	RT				18.3	2.25	1.8	1.9	0.1	10.1	0.2
FE	279+73.80	LT				9.4	1.75	0.9	0.7	0.1	5.2	0.1
PE	280+79.70	RT				8.5	1.75	0.9	0.7	0.1	4.7	0.1
FE	294+02.00	RT				16.3	1.875	1.6	1.4	0.1	9.0	0.2
PE	300+45.90	LT				9.3	1.75	0.9	0.7	0.1	5.1	0.1
PE	300+74.60	RT				12.3	1.75	1.2	1.0	0.1	6.8	0.2
PE	301+11.00	RT				11.7	1.75	1.2	0.9	0.1	6.4	0.1
FE	307+40.70	RT				15.6	1.875	1.6	1.3	0.1	8.6	0.2
PE/MBTO	314+24.80	RT				18.2	1.75	1.8	1.4	0.1	10.0	0.2
SIDEROAD	320+54.02	LT				49.2	1.875	4.9	4.2	0.4	27.1	0.6
SIDEROAD	320+57.19	RT				40.4	1.875	4.0	3.4	0.3	22.2	0.5
PE/MBTO	323+36.60	RT				35.2	1.875	3.5	3.0	0.3	19.4	0.4
PE	324+48.00	RT				7.0	1.875	0.7	0.6	0.1	3.9	0.1
PE	335+47.90	LT				31.1	1.875	3.1	2.6	0.2	17.1	0.4
PE	340+93.60	RT				33.6	1.875	3.4	2.8	0.3	18.5	0.4
FE	340+93.60	LT				8.2	1.875	0.8	0.7	0.1	4.5	0.1
FE	368+12.00	RT				11.2	1.875	1.1	0.9	0.1	6.2	0.1
SUB-TOTAL =								56.3	47.4	4.2	309.5	7.0
TOTAL =								3,519.9	3,554.4	264.0	19,359.7	440.0
USE =								3,520.0	3,555.0	264.0	19,360.0	440.0