

ROADWAY SCHEDULE															
LOCATION	SUBBASE GRANULAR MATERIAL TYPE C	HOT-MIX ASPHALT BASE COURSE WIDENING 6"	AGGREGATE SURFACE COURSE TYPE B	BITUMINOUS MATERIAL (PRIME COAT)	AGGREGATE PRIME COAT	LEVELING BINDER (MACHINE METHOD) N50	LEVELING BINDER (MACHINE METHOD) N50 (SPECIAL)	HOT-MIX ASPHALT SURFACE REMOVAL BUTT-JOINT	TEMPORARY RAMP	HOT-MIX ASPHALT SURFACE COURSE MIX C, N50	BITUMINOUS MATERIAL PRIME COAT	INCIDENTAL HOT-MIX ASPHALT SURFACING	HOT-MIX ASPHALT SHOULDERS	HOT-MIX ASPHALT SHOULDERS 4.5"	HOT-MIX ASPHALT SHOULDERS 6"
	31101900	35600700	40200800	40600100	40600300	40600625	X4060605	40600982	40600990	40603310	40800010	44000100	48203100	48203015	48203021
	TON	SQ YD	TON	GAL	TON	TON	TON	SQ YD	SQ YD	TON	GAL	SQ YD	TON	SQ YD	SQ YD
FAS 680 CH4															
CL STA0+00 TO CL 103+45.47	122	212		3,336	44	1,627	841	176	35	2,030			1,078	5,400	1,429
CL 105+19.92 TO CL 187+38.79	57	39		2,648	36	1,293	386	138	35	1,610			1,022	4,517	898
SIDE ROADS											46	48			
ENTRANCES			415								142	167			
TOTAL	179	251	415	5,984	80	2,920	1,227	314	70	3,640	188	215	2,100	9,917	2,327

BITUMINOUS MATERIALS (PRIME COAT) 40600100 QUANTITY INCLUDES SEAL COAT REQUIRED FOR CENTERLINE-RUMBLE STRIP- 8" AND SHOULDER RUMBLE STRIP, 8"

EARTHWORK SUMMARY							
LOCATION	EARTH EXCAVATION	FROM EXC & GRADE SHLDS	SHRINKAGE FACTOR	% USED	EARTH EXCAVATION ADJUSTED FOR SHRINKAGE (25%)	EMBANKMENT REQUIRED	EARTHWORK BALANCE WASTE (+) OR SHORT AGE (-)
	CUBIC YARD	CUBIC YARD			CUBIC YARD	CUBIC YARD	CUBIC YARD
FAS 680 CH4							
CL STA0+00 TO CL 103+45.47	181	811	25.00%	100.00%	744	2,197	-1,453
CL 105+19.92 TO CL 187+38.79	34	651	25.00%	100.00%	514	691	-177
SIDE ROADS			25.00%	100.00%	0		0
ENTRANCES			25.00%	100.00%	0		0
CHANNEL EXCAVATION			25.00%	100.00%	0		0
	215	1,462			1,258	2,888	-1,630

20400800 FURNISHED EXCAVATION = 1,630 CU.YD.

PLOT DATE 12/1/2012 FILE NAME = 110030-plt-sched1.ecd.dgn



**EDGAR COUNTY
HIGHWAY DEPARTMENT**