

CONDUIT DETAILS,
IN RECONSTRUCTED CONCRETE
OR BITUMINOUS SHOULDER,
TRAVELED WAY OR RAMP AREA


305mm (MIN)

75mm

Edwards AND Kelcey

NOTES:

- PVC CONDUIT SHALL BE INSTALLED IN ACCORDANCE WITH SECTION 810 OF THE IDOT STANDARD SPECIFICATIONS.
- TRENCH AND BACKFILL SHALL BE FURNISHED AND INSTALLED IN ACCORDANCE WITH SECTION 815 OF THE IDOT STANDARD SPECIFICATIONS.
- WARNING TAPE SHALL BE ORANGE, 0.1mm FLEXIBLE POLYETHYLENE FILM WICH SHALL BE RESISTANT TO ACIDS, BASES, HYDROCARINS, AND WATER.
- TRENCH BOTTOM SHALL BE PREPARED TO ELIMINATE LUMPS. RIDGES, JAGGED EDGES, AND HOLLOWS UTILIZING BEDDING MATERIALS AS DIRECTED BY THE ENGINEER.



WARNING TAPE DETAIL

(BLACK LETTERS ON ORANGE BACKGROUND)

ITS SHEET 11 OF 13

TOTAL SHEET SHEETS NO.

COUNTY

F.A.I. RTE.

SECTION

REVISIONS
NAME DATE

CONDUIT DETAIL

SCALE

DATE 11/02/04

REVISIONS

ILLINOIS DEPARTMENT OF TRANSPORTATION

ITS PLAN

CONDUIT DETAIL

INTED: 11/05/2004