

BIT CON SURF CRSE, SUPER MIX "C", N50

SN 086-0023

STA 198+94.90 TO STA 199+44.90

STA 200+54.90 TO STA 201+04.90

SN 086-0024

STA 198+94.90 TO STA 199+44.90

STA 200+54.90 TO STA 201+04.90

C O N V E R S I O N F A C T O R S		
BITUMINOUS CONCRETE SURFACE COURSE, SUPERPAVE, MIX C, N50	0.056 TON/SQ YD/IN	TONS

M I X T U R E R E Q U I R E M E N T S			
THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT			
MIXTURE USE(S):	BC SC SUPER "C" N50	BIT SHLDR SUPER	BIT SHLDR SUPER 10" *
AC/PG	PG 64-22	PG 64-22	PG 64-22
RAP %: (MAX)	15%	15%	20%
DESIGN AIR VOIDS:	4% ● N DESIGN = 50	4% ● N DESIGN = 50	2% ● N DESIGN = 50

* NOTE: THE TOP 1 1/2" OF BIT SHLDR SUPER 10" SHALL
 BE PLACED USING THE MIX DESIGN SPECIFIED FOR
 THE BIT SHLDR SUPER TON ITEM

CONVERSION & MIXTURE TABLES
 FAI 72 OVER WALNUT CREEK
 SECTION (86-10B)I-1
 SCOTT COUNTY