INDEX OF SHEETS

	11. Total learners and the state of the stat		
SHEET NO.	DESCRIPTION		
1	COVER SHEET		
2	INDEX, GENERAL NOTES AND HIGHWAY STANDARDS		
3	SUMMARY OF QUANTITIES		
4	TYPICAL SECTIONS		
5	ALIGNMENT, TIES AND BENCHMARKS		
6-8	PLAN AND PROFILE		
9	EROSION CONTROL PLAN		
10-12	DRAINAGE PLAN AND PROFILE		
13	DETECTOR LOOP REPLACEMENT		
14-20	TRAFFIC SIGNAL PLANS		
21	REMOVAL PLAN		
22-29	CROSS SECTIONS		
30-32	SUE PLANS		
33	DRIVEWAY DETAILS-DISTANCE BETWEEN R.O.W. AND FACE OF CURB IS LESS THAN 15' (BD02)		
34	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT (BD22)		
35	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS AND DRIVEWAYS (TC10)		
36	ARTERIAL ROAD INFORMATION SIGN (TC22)		
37	DETECTOR LOOP INSTALLATION DETAIL FOR ROADWAY RESURFACING (TS07)		
38-43	STANDARD TRAFFIC SIGNAL DESIGN DETAILS (TS05)		

HIGHWAY STANDARDS

STD. NO.	HIGHWAY STANDARDS TITLE
280001-05	TEMPORARY EROSION CONTROL SYSTEMS
406201-01	MAILBOX TURNOUT
424001-05	CURB RAMPS FOR SIDEWALKS
442201 - 03	CLASS C AND D PATCHES
542301- <i>0</i> 3	PRECAST REINFORCED CONCRETE FLARED END SECTION
542311-02	GRATING FOR CONCRETE FLARED END SECTION (FOR 24" (600mm) THRU 54" (1350mm) PIPE)
602001 <i>-02</i>	CATCH BASIN, TYPE A
602301- <i>03</i>	INLET, TYPE A
602401-03	MANHOLE, TYPE A
602601- <i>02</i>	PRECAST REINFORCED CONCRETE FLAT SLAB TOP
602701-02	MANHOLE STEPS
604001-03	FRAME AND LIDS, TYPE 1
604036 <i>-02</i>	GRATE, TYPE 8
604091-02	FRAME AND GRATE, TYPE 24
606001-04	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
701006 <i>-03</i>	OFF-ROAD OPERATIONS, 2L, 2W, 15 FT (4.5m) TO 24" (600mm) FROM PAVEMENT EDGE
701101- <i>02</i>	OFF ROAD OPERATIONS, MULTILANE, 15' (4.5m) TO 24" (600mm) FROM PAVEMENT EDGE
701501 <i>-06</i>	URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED
701701- <i>0</i> 7	URBAN LANE CLOSURE, 1W OR 2W CROSSWALK OR SIDEWALK CLOSURE
701801- <i>04</i>	LANE CLOSURE, MULTILANE, INTERSECTION
701901-01	TRAFFIC CONTROL DEVICES
720001-01	SIGN PANEL MOUNTING DETAILS
720006-02	SIGN PANEL ERECTION DETAILS
728001-01	TELESCOPING STEEL SIGN SUPPORT
780001 - <i>0</i> 2	TYPICAL PAVEMENT MARKINGS
814001- <i>0</i> 2	HANDHOLES
857001- <i>01</i>	STANDARD PHASE DESIGNATION DIAGRAMS AND PHASE SEQUENCES
857006 -0/	SUPERVISED RAILROAD INTERCONNECT CIRCUIT
862001 - <i>01</i>	UNINTERRUPTIBLE POWER SUPPLY (UPS)

GENERAL NOTES

- BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "J.U.L.I.E."

 AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES AND THE CITY OF LOCKPORT AT 815-838-0549 FOR FIELD LOCATIONS OF SANITARY SEWER AND WATER MAIN. (48 HOUR NOTIFICATION IS REQUIRED).
- THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGE OF NORTH AURORA.
- 3. THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.
- 4. WHEN ARTIFICIAL LIGHTING IS USED IN NIGHT OPERATIONS THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISIBILTY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.
- THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM 72 HOURS PRIOR TO THE PLACEMENT OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.
- 6. THE CONTRACTOR SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM 72 HOURS IN ADVANCE OF BEGINNING WORK.
- ALL PAVEMENT MARKINGS SHALL BE PLACED THROUGHOUT THE PROJECT ACCORDING TO DISTRICT 1 TYPICAL PAVEMENT MARKING.
- 8. ALL HMA PAVEMENT PATCHING SHALL BE CLASS D.
- 9. ANY PAVEMENT MARKINGS AND RAISED REFLECTIVE PAVEMENT MARKERS
 OBLITERATED BY MILLING AND RESURFACING OPERATIONS ON SIDE STREETS AND
 ENTRANCES SHALL BE REPLACED AND PAID FOR IN KIND.
- 10. MATCH EXISTING PAVEMENT MARKINGS AT PROJECT LIMITS.
- 11. ALL PAVEMENT PATCHING LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.
- 12. DRAINAGE ADJUSTMENT, CLEANING OR RECONSTRUCTION LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.
- 13. THE CONTRACTOR SHALL BE REQUIRED TO PROVIDE ACCESS TO ABUTTING PROBERTY AT ALL TIMES DURING THE CONSTRUCTION OF THIS PROJECT
- 14. EXISTING BROKEN FRAMES AND LIDS SHALL BE REMOVED AND DISPOSED OF BY THE CONTRACTOR AND SHALL BE REPLACED AS DRIECTED BY THE ENGINEER.

 REPLACEMENT FRAMES AND LIDS WILL BE PAID FOR IN ACCORDANCE WITH ARTICLE 109.04 OF THE STANDARD SPECIFICATIONS UNLESS A SEPARATE PAY ITEM HAS BEEN PROVIDED.

FILE NAME =	USER NAME = _USER_	DESIGNED -	EF	REVISED	
\$FILEL\$		DRAWN	EF	REVISED -	
	PLOT SCALE = 50.0000 '/ IN.	CHECKED -	RS	REVISED	
	PLOT DATE = 2/10/2011	DATE	02-14-201	REVISED	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

IL 25 (RIVER ST.) — IL 56 TO 1–88					
INDEX OF	SHEETS, HIGHWAY	STANDARDS, AND	GENERAL NOTES	ľ	
SCALE: NTS	SHEET NO. 1 OF 1	SHEETS STA.	TO STA.	ľ	

-				T 0 T 11	01.55
	F.A.U.	SECTION	COUNTY	TOTAL	SHEE
	RIE.	02011011	000,111	SHEETS	NO
	2503	TWP-1-T	KANE	43	2
					L
			CONTRACT	NO. 6	OKO
	************	ILLINOIS FED. AI	D PROJECT		