TRAFFIC SIGNAL LEGEND

ITEM	DEMOVAL	EVICTING	DDUDUCEU	ITEM	DEMOVAL	EVICTING	DDODOCED	ITCM	DEMOVAL	EVICTING	DDODOCED
ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED	ITEM ELECTRIC CABLE IN CONDUIT, TRACER,	REMOVAL	EXISTING	PROPOSED
CONTROLLER CABINET	R			EMERGENCY VEHICLE LIGHT DETECTOR	e√ Ro-(J	⊗	≪	NO. 14 1/C, UNLESS NOTED OTHERWISE		1	 1
RAILROAD CONTROL CABINET	R			CONFIRMATION BEACON		0-()		COAXIAL CABLE			—©—
COMMUNICATIONS CABINET MASTER CONTROLLER	cc "	E C C	CC	HANDHOLE	R □						
MASTER MASTER CONTROLLER		EMMC	MC	HEAVY DUTY HANDHOLE	R	H	H	VENDOR CABLE FOR CAMERA			
UNINTERRUPTIBLE POWER SUPPLY	UPS R	EUPS	MMC UPS	DOUBLE HANDHOLE	R			COPPER INTERCONNECT CABLE,		<u> </u>	<u>—6</u>
SERVICE INSTALLATION,	R	P	- ≡ P	JUNCTION BOX	R		0	NO. 18 3 PAIR TWISTED, SHIELDED FIBER OPTIC CABLE			
(P) POLE OR (G) GROUND MOUNT				GALVANIZED STEEL CONDUIT IN TRENCH (T) OR PUSHED (P)				NO. 62.5/125, MM12F		— <u>[2</u> F)—	
TELEPHONE CONNECTION (P) POLE OR (G) GROUND MOUNT	R	P	<u> </u>	TEMPORARY SPAN WIRE, TETHER WIRE,	P			FIBER OPTIC CABLE NO. 62.5/125, MM12F SM12F		<u>—24F</u>	—24F)—
STEEL MAST ARM ASSEMBLY AND POLE	R	O	-	AND CABLE	, <u>n</u>	· '\		FIBER OPTIC CABLE NO. 62.5/125,			
ALUMINUM MAST ARM ASSEMBLY AND POLE	R	0		COMMON TRENCH			СТ	(NUMBER OF FIBERS & TYPE TO BE			
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE	R	0-×	• × · · · ·	COILABLE NONMETALLIC CONDUIT (EMPTY)			CNC	NOTED ON PLANS) GROUND ROD AT (C) CONTROLLER.			
STEEL COMBINATION MAST ARM	R R			SYSTEM ITEM		S S	S	(H) HANDHOLE, (P) POST, (M) MAST ARM,		Cull-o	c _{il} →
ASSEMBLY AND POLE WITH PTZ CAMERA	PIZM	PTZI	PTZ	INTERSECTION ITEM		I	ΙP	OR (S) SERVICE	DOF		
SIGNAL POST	R O	0	•	REMOVE ITEM RELOCATE ITEM	R			CONTROLLER CABINET AND FOUNDATION TO BE REMOVED	RCF		
TEMPORARY WOOD POLE (CLASS 5 OR BETTER) 45 FOOT (13.7m) MINIMUM	R⊗	⊗ 1	•	ABANDON ITEM	Δ			STEEL MAST ARM POLE AND	RMF		
GUY WIRE	R	>	>-	12" (300mm) TRAFFIC SIGNAL SECTION			R	FOUNDATION TO BE REMOVED	:		
SIGNAL HEAD	R 		 ▶					ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF		
SIGNAL HEAD CONSTRUCTION STAGES	72		2	12" (300mm) RED WITH 8" (200mm) YELLOW AND GREEN TRAFFIC SIGNAL FACE		R		STEEL COMBINATION MAST ARM ASSEMBLY			
(NUMBERS INDICATE THE CONSTRUCTION STAGES)		-					AND POLE WITH LUMINAIRE AND	RMF O⇒X		
SIGNAL HEAD WITH BACKPLATE	+ R	+1>	+►			R	R	FOUNDATION TO BE REMOVED			
SIGNAL HEAD OPTICALLY PROGRAMMED	R —⇒"P"	— >′′P′′	- ▶ "P"	SIGNAL FACE			G	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF O		
FLASHER INSTALLATION (S DENOTES SOLAR POWER)	R ○	0-t>"F"	•• "F"			★	∢ Y ∢ G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR		[IS]	IS
PEDESTRIAN SIGNAL HEAD	R -[]	-[]				R	R	SAMPLING (SYSTEM) DETECTOR			S
PEDESTRIAN PUSHBUTTON DETECTOR	R	(iii)	(a)	SIGNAL FACE WITH BACKPLATE.			Y				ات)
	R			"P" INDICATES PROGRAMMED HEAD		4 Y	∢ Y	EXISTING INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DET	ECTOR	P	
ACCESSIBLE PEDESTRIAN PUSHBUTTON DETECTO	OR @APS	@APS	(a) APS			(P)	∢ G	EXISTING PREFORMED INTERSECTION LOOP DETECTOR		ÎPPÎ	
ILLUMINATED SIGN "NO LEFT TURN"	R		(5)				"P"	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DET	ECTOR	, T	
ILLUMINATED SIGN	R			12" (300mm) PEDESTRIAN SIGNAL HEAD WALK/DON'T WALK SYMBOL		OW W		PREFORMED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR		PIS	PIS
"NO RIGHT TURN"				12" (300mm) PEDESTRIAN SIGNAL HEAD				PREFORMED SAMPLING (SYSTEM) DETECTOR		<u>PS</u>	PS
DETECTOR LOOP, TYPE I				INTERNATIONAL SYMBOL, OUTLINED					. A	\$ Ł	-
PREFORMED DETECTOR LOOP		e e	Р	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, SOLID			*	RAILROAD	SYMR	210	
	R	74		PEDESTRIAN SIGNAL HEAD, INTERNATIONAL				IIAILIIOAL	OTIVID)LO	
MICROWAVE VEHICLE SENSOR	R M)	M	M	SYMBOL, WITH COUNTDOWN TIMER		(€) C (5) D	₽ C ★ D			EXISTING	PROPOSED
VIDEO DETECTION CAMERA	R	[Vp	(V) •	RADIO INTERCONNECT	## *	##+0		RAILROAD CONTROL CABINET			₽ ~
VIDEO DETECTION ZONE								RAILROAD CANTILEVER MAST ARM		XOX X	X 0 X X X
	R			RADIO REPEATER	RERR	ERR	RR	FLASHING SIGNAL		X o X	XOX
PAN, TILT, ZOOM CAMERA	PTZ	PTZ)	PTZ	DENOTES NUMBER OF CONDUCTORS, ELECTRIC CABLE NO. 14, UNLESS NOTED OTHERWISE,		(5)					
WIRELESS DETECTOR SENSOR	RW	W	W	ALL DETECTOR LOOP CABLE TO BE SHIELDED				CROSSING GATE		X0 X >	XOX
WIRELESS ACCESS POINT	R			GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)				CROSSBUCK		≥	*
ILE NAME = USER NAME = galbanyr		DESIGNED - DAG/BCK DRAWN - BCK	REVISED -	CTATE	OF ILLINOIS	•		DISTRICT ONE	F.A.U. RTE.	SECTION	COUNTY TOTAL SHE
:\pw_work\pwidot\galbanjr\dØ194557\Distbtd.dgn PLOT SCALE = 50.0000		CHECKED - DAD	REVISED -	DEPARTMENT				STANDARD TRAFFIC SIGNAL DESIGN DETAILS	3565	B-R-2-RS TS-05	COOK 37 36 CONTRACT NO. 60K54