TRAFFIC SIGNAL LEGEND

	LOT SCALE = 50.0000 '/ IN. LOT DATE = 2/4/2011	CHECKED - DAD REVISED -			DEPARTMENT OF TRANSPORTATION			SCALE: NO	STANDARD TRAFFIC SIGNAL DESIGN DETAILS NE SHEET NO. 6 OF 6 SHEETS STA. TO STA.		75-05 DIST. NO. 1 ILLINOIS FEE	CONTRACT NO. 60
LE NAME = \pw_work\pwidot\abebawa\d0206185\Dist\$t	SER NAME = abebawa dgn	DRAWN - BCK REVISED -			STATE OF ILLINOIS				DISTRICT ONE			
WIRELESS ACCESS POINT					No. 6 SOLID COPPER (GREEN)			(1)				
WIRELESS DETECTOR SENSOR		R	W	, W	GROUND CABLE IN CONDUIT		~		CROSSBUCK		<u>}</u>	*
AN, TILT, ZOOM CAMERA	· F				DENOTES NUMBER OF CONDUCTORS, ELECTRIC CABLE NO. 14, UNLESS NOTED OTHERWISE, ALL DETECTOR LOOP CABLE TO BE SHIELDED				CROSSING GATE		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	X0X-
AN THE 700H OWER		R			RADIO REPEATER	RERR	ERR	RR	FLASHING SIGNAL		$\times \Theta \times$	X ⊕ X
IDEO DETECTION ZONE									RAILROAD CANTILEVER MAST ARM	<u> </u>	<u> </u>	X QX X
IDEO DETECTION CAMERA		R (V)1	(V)	()	RADIO INTERCONNECT	- - - - - - - - - - - - -			RAILROAD CONTROL CABINET			B-4
ICROWAVE VEHICLE SENSOR		R MJ	(M)	M	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER		(€) C ((8) D	₽ C			EXISTING	PROPOSED
PREFORMED DETECTOR LOOP			P	Р	INTERNATIONAL SYMBOL, SOLID		*	RAILROAD SYMBOLS				
ETECTOR LOOP, TYPE I					INTERNATIONAL SYMBOL, OUTLINED 12" (300mm) PEDESTRIAN SIGNAL HEAD			•				
LLUMINATED SIGN NO RIGHT TURN''		R			12" (300mm) PEDESTRIAN SIGNAL HEAD				PREFORMED SAMPLING (SYSTEM) DETECTOR		IPSI	PS
NO LEFT TURN"				•	12" (300mm) PEDESTRIAN SIGNAL HEAD WALK/DON'T WALK SYMBOL		ÓW (W)		PREFORMED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR		PIS	PIS
LLUMINATED SIGN		R	-	_			(°P''	('P''	EXISTING PREFORMED INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETEC	TOR	PPI	
PEDESTRIAN PUSHBUTTON DETECTOR ACCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR		₹ ⊚ aps	© @APS	●	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD		Y G Y	Y G 4 Y	EXISTING INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETEC	TOR	P	
		R ©							SAMPLING (SYSTEM) DETECTOR		[s]	S
PEDESTRIAN SIGNAL HEAD		R -	-0 .					R	(SYSTEM) DETECTOR			IS
LASHER INSTALLATION 5 DENOTES SOLAR POWER)		R ⊃-'⊳''F''	O-t>″F″	●→ "F"			(+ y) (+ g)	← Y ← G	INTERSECTION & SAMPLING		l're l	[tc]
GNAL HEAD OPTICALLY PROG	AMMED _	R -▷''P''	->″p″	— > "P"	SIGNAL FACE		(Y) G	Y G	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF		
NUMBERS INDICATE THE CONST IGNAL HEAD WITH BACKPLATE	RUCTION STAGE)	+ R + D	+->	+>			R	R	AND POLE WITH LUMINAIRE AND FOUNDATION TO BE REMOVED	RMF ○->X		
IGNAL HEAD IGNAL HEAD CONSTRUCTION S	AGES		>	→	12" (300mm) RED WITH 8" (200mm) YELLOW AND GREEN TRAFFIC SIGNAL FACE				FOUNDATION TO BE REMOVED STEEL COMBINATION MAST ARM ASSEMBLY			
UY WIRE		R	>	<u> </u>	12" (300mm) TRAFFIC SIGNAL SECTION		R	R	ALUMINUM MAST ARM POLE AND	RMF		
EMPORARY WOOD POLE (CLASS ETTER) 45 FOOT (13.7m) MINI	IUM	R⊗	\otimes	•	ABANDON ITEM	A			STEEL MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF		
GIGNAL POST	F 0D	R _O	0	•	REMOVE ITEM RELOCATE ITEM	R			CONTROLLER CABINET AND FOUNDATION TO BE REMOVED	RCF		
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH PT			Q———— PTZ11	PZ	INTERSECTION ITEM		I I	IP	OR (S) SERVICE		" "	**
ASSEMBLY AND POLE WITH LUN	INAIRE	×	O-)X	•*	SYSTEM ITEM		S 4	S	GROUND ROD AT (C) CONTROLLER, (H) HANDHOLE, (P) POST, (M) MAST ARM,		c _∥ ⊢⊷	C∥
LUMINUM MAST ARM ASSEMBL TEEL COMBINATION MAST ARM	Q				COMMON TRENCH COILABLE NONMETALLIC CONDUIT (EMPTY)			CT CNC	(NUMBER OF FIBERS & TYPE TO BE NOTED ON PLANS)			
TEEL MAST ARM ASSEMBLY A	Ů.		· ·	•	TEMPORARY SPAN WIRE, TETHER WIRE, AND CABLE	*		· · · · · · · · · · · · · · · · · · ·	NO. 62.5/125, MM12F SM12F FIBER OPTIC CABLE NO. 62.5/125,			
ELEPHONE CONNECTION P) POLE OR (G) GROUND MOUN		R	P	P T	IN TRENCH (T) OR PUSHED (P)				FIBER OPTIC CABLE		—24F)—	(24F)
SERVICE INSTALLATION, P) POLE OR (G) GROUND MOUN	•	<u>R</u>	- <u>-</u> -	<u> </u>	JUNCTION BOX GALVANIZED STEEL CONDUIT	R	(•	FIBER OPTIC CABLE NO. 62.5/125, MM12F		—(12F)—	
NINTERRUPTIBLE POWER SUPP	.Y	R UPS	EUPS	MMC UPS	DOUBLE HANDHOLE	R		KN	COPPER INTERCONNECT CABLE, NO. 18 3 PAIR TWISTED, SHIELDED		<u> </u>	-6-
IASTER CONTROLLER			EMMC	MC	HEAVY DUTY HANDHOLE	R	Н	H	VENDOR CABLE FOR CAMERA		——————————————————————————————————————	
OMMUNICATIONS CABINET		C C	ECC	СС	HANDHOLE	R .			COAXIAL CABLE			— <u>c</u>
MAILROAD CONTROL CABINET					CONFIRMATION BEACON	R _{o-0}	0-0	. •	NO. 14 1/C, UNLESS NOTED OTHERWISE			
ONTROLLER CABINET		R R			 EMERGENCY VEHICLE LIGHT DETECTOR	R _∞	\bowtie	, «	ELECTRIC CABLE IN CONDUIT, TRACER,		(1)	