

* Remove 7" of existing overlay and replace with 7" concrete slab as shown. Slope to match roadway. Cost of removal included with Partial Depth Removal (Variable Depth).

construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid

Reinforcement bars shall conform to the requirements of ASTM A 706 Gr 60.

420.09(e)(1) of the Standard Specifications. Cost included with Concrete

2 00272775								
Bar	No.	Size	Length	Shape				
a(E)	80	#7	10'-4''					
h(E)	60	#5	11'-8''	*******				
Bar Sp	Bar Splicers			30				
	Partial Depth Removal (Variable Depth)			48.0				
Reinforcement Bars. Epoxy Coated			Pound	2420				
	Concrete Superstructure		Cu. Yds.	9.4				

2 CULVERTS

TAILS	F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
N 4 8194	730	POSTING MITICATION FY2011-1	MCLEAN	23	16
2 SHEETS	ILLINOIS FED. AID PROJECT				