

STANDARD BAR SPLICER ASSEMBLY

	Minim	um Lap Leng	ths		
Bar size to be spliced	Table 1	Table 2	Table 3	Table 4	Table 5
3, 4	1'-5''	1'-11''	2'-1''	2'-4''	2'-3''
5	1'-9''	2'-5''	2'-7''	2'-11''	2'-10''
6	2'-1''	2'-11''	3'-1''	3'-6''	3'-4''
7	2'-9''	3′-10′′	4'-2''	4'-8''	4'-6''
8	3'-8''	5'-1''	5'-5''	6'-2''	5′-10′′
9	4'-7''	6'-5''	6'-10''	7'-9''	7'-5''

Table 1: Black bar, 0.8 Class C

Table 2: Black bar, Top bar lap. 0.8 Class C

 Table 3:
 Epoxy bar, 0.8 Class C

 Table 4:
 Epoxy bar, Top bar lap, 0.8 Class C

Table 5: Epoxy bar, Top bar lap, Class B

Threaded splicer bar length = min. lap length + I_2^{l} '' + thread length

* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.

Bar size	No. assemblies required	Table for minimum lap length
#5	24	Table 3
#6	12	Table 3
	size #5 #6	



INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt. "B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms. (E) : Indicates epoxy coating.

		Bridge Deck	Approach	Slab		
Re. Ba	inforcement rs	Threaded couplers (E)	Threaded spl. bar (E)	<u>'icer</u>		
ระกระระกระบาทการการการการการการการการการการการการการก	ł	<u>d splicer</u> 4′-0′′		5'-0''	Ē	
	MARKING CONTRACTOR		MBLY FOR #5 BAF		1	
		No. req	nuired =			
					1	
BSD-1		7-1-10			·····	
E NAME =	LISER N	IAME = teasleuck	DESIGNED - KLB	REVISED -	1	



File NAME USEX NAME Testinger DESTINED REVISED ci/pw.work/pwidot/tessleyck/d0209700/D 4494-sht-br/details-01/20048.dgn DRAWN - KLB REVISED - BAR SPLICER ASSEMBLY AND MECHANICAL S plo7 SCALE 200088 // IN. CHECKED MEA REVISED - DEPARTMENT OF TRANSPORTATION BAR SPLICER ASSEMBLY AND MECHANICAL S		932		
			*	Clork JI ZY
				CONTRACT NO. 74494
PLOT DATE = 2/18/2011 DATE - 12/07/2010 REVISED - SCALE: SHEET NO. 9 OF 10 SHEETS STA.	TO STA.		ILLINOIS FEI	D. AID PROJECT

VIIIII	////	1111	1111
6///////	111		////
Construction of the second sec			

Reinforcement bar -

└─ Reinforcement bar

STANDARD MECHANICAL SPLICER

Mechanical coupler (E)

Location	Bar size	No. assemblies required

NOTES

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.

All reinforcement shall be lapped and tied to the splicer bars. Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications, See special provision for Mechanical Splicers.

See approved list of bar splicer assemblies and mechanical splicers for alternatives.