

GENERAL NOTES

Reinforcement bars shall conform to the requirements of ASTM A 706 Gr 60. See Special Provisions.

Reinforcement bars designated (E) shall be epoxy coated. Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and

construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work. Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.

Joint openings shall be adjusted according to Article 520.04 of the Standard Specifications when the deck is poured at an ambient temperature other than 50° F.

TOTAL BILL OF MATERIAL

ITEM	UNIT	SUPER	SUB		TOTAL					
			Appr. Ftg.	Abuts.]					
rooving	Sq. Yd.	526			526					
stures	Cu. Yd.		15.0	8.2	23.2					
rstructure	Cu. Yd.	202.8			202.8					
t	Sq. Yd.	590			590					
ival	Cu. Yd.	202.6		8.2	210.8					
Bars, Epoxy Coated	Pound	31720	2640	1010	35370					
	Each	170		16	186					
nt Strip Seal	Foot	165			165					
es, Type II, 13 inches	Sq. Yd.	124			124					
e-Expansion Joint	Foot	166			166					
<i>``</i>	Each	159			159					
	Each	159			159					

EVATION VER CREEK	F.A.I. RTE.	SECTION	COUNTY	TOTAL	SHEET NO.
	70	3-48[-1	BOND	35	4
003-0010 (WB)	ļ	ILLINOIS FED. A	CONTRACT	NO. 7	5E23