

INTENTIONALLY LEFT BLANK


DISABLED RAMP DETAIL






SEE STANDARD 424001 FOR SIDE FLARE DETAIL & SEE PLANS FOR RAMP TYPE.

ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE NOTED.





SECTION B-B

NOTES: THIS DETAIL TO BE USED IN CONJUNCTION WITH STATE STANDARD 424001.

THE MAXIMUM ALLOWABLE CROSS SLOPE FOR SIDEWALK IS 2% (1/4"/FT).

THE MAXIMUM ALLOWABLE SIDEWALK GRADE IS 8% (1/12"/FT). IF SPACE
LIMITATIONS PROHIBIT THE USE OF THE 1:12 SLOPE, THEN SLOPES BETWEEN 1:10

ARE 1:12 ARE PERMITTED FOR A MAXIMUM RISE OF 150 (6). SLOPES 1:8 AND 1:10

ARE ALLOWED FOR A MAXIMUM RISE OF 75 (3). SLOPES STEEPER THAN 1:8 ARE

NOT PERMITTED.

THE DEPRESSED CURB IS NOT STANDARD. THE RISE IS 13(1/2) INSTEAD OF 40 (11/2).

REVISED - 9-19-05

DISABLED RAMP DETAIL 60.2



USER NAME = Steve Prange	DESIGNED	-	SJP / MNB	REVISED -
	DRAWN	-	ERD	REVISED -
PLOT SCALE = 50.0000 '/ IN.	CHECKED	-	SJP	REVISED -
PLOT DATE = 02/04/11	DATE	-	02/04/2011	REVISED -

CITY OF ROCKFORD MORGAN STREET BRIDGE

IDOT DO JOHN STANDARD DRANGNOS O	F.A. RTE.	
IDOT D2 /CITY STANDARD DRAWINGS - 3	5077	99
SCALE: N/A SHEET NO. 3 OF 15 SHEETS STA. TO STA.	EED BO	TOTAL GA