TRAFFIC SIGNAL LEGEND

ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED	<u>ITEM</u>	REMOVAL	EXISTING	PROPOSED
CONTROLLER CABINET	\bowtie R			EMERGENCY VEHICLE LIGHT DETECTOR	R ≪	\ll	₩	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE		1	1
RAILROAD CONTROL CABINET		R K	R	CONFIRMATION BEACON	$R_{\bullet-0}$	⊶	⊷ 4	. •		~	
COMMUNICATIONS CABINET	C C	ECC	CC	HANDHOLE	R 🖂			COAXIAL CABLE		—(c)—	C
MASTER CONTROLLER		EMC	MC		R	H	H	VENDOR CABLE FOR CAMERA		(\(\sigma\)	0
MASTER MASTER CONTROLLER	R	EMMC	MMC	HEAVY DUTY HANDHOLE	В		_	COPPER INTERCONNECT CABLE,			
UNINTERRUPTIBLE POWER SUPPLY	UPS	EUPS	UPS	DOUBLE HANDHOLE JUNCTION BOX	^K DD R		0	NO. 18 3 PAIR TWISTED, SHIELDED		<u> </u>	6
SERVICE INSTALLATION, (P) POLE OR (G) GROUND MOUNT	-□ ^R	-C-P	- 	GALVANIZED STEEL CONDUIT				FIBER OPTIC CABLE NO. 62.5/125, MM12F		— <u>12</u> F—	
TELEPHONE CONNECTION (P) POLE OR (G) GROUND MOUNT	R	P	P	IN TRENCH (T) OR PUSHED (P) TEMPORARY SPAN WIRE, TETHER WIRE,	R			FIBER OPTIC CABLE NO. 62.5/125, MM12F SM12F		——24F——	(24F)
STEEL MAST ARM ASSEMBLY AND POLE	R	0	•	AND CABLE				FIBER OPTIC CABLE NO. 62.5/125,			
ALUMINUM MAST ARM ASSEMBLY AND POLE	R	0		COMMON TRENCH			ст	(NUMBER OF FIBERS & TYPE TO BE		-	
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE	R _{O-} >	0-)\$	• ×	COILABLE NONMETALLIC CONDUIT (EMPTY)			CNC	NOTED ON PLANS) GROUND ROD AT (C) CONTROLLER.			
STEEL COMBINATION MAST ARM	R_	0	•	SYSTEM ITEM		S	S	(H) HANDHOLE, (P) POST, (M) MAST ARM,			c _H
ASSEMBLY AND POLE WITH PTZ CAMERA	Przh	ezh	PT.	INTERSECTION ITEM		I	IP	OR (S) SERVICE CONTROLLER CABINET AND	RCF		
SIGNAL POST	R _O	0	. •	REMOVE ITEM RELOCATE ITEM	R RL			FOUNDATION TO BE REMOVED			
TEMPORARY WOOD POLE (CLASS 5 OR BETTER) 45 FOOT (13.7m) MINIMUM	$\overset{R}{\otimes}$	\otimes	•	ABANDON ITEM	Α.			STEEL MAST ARM POLE AND	RMF		
GUY WIRE	>R	>	>_	12" (300mm) TRAFFIC SIGNAL SECTION		R	R	FOUNDATION TO BE REMOVED			
SIGNAL HEAD	R 					6	l-constant	ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF O		
SIGNAL HEAD CONSTRUCTION STAGES NUMBERS INDICATE THE CONSTRUCTION STAGE)			2	12" (300mm) RED WITH 8" (200mm) YELLOW AND GREEN TRAFFIC SIGNAL FACE				STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND	RMF		
SIGNAL HEAD WITH BACKPLATE	+t> ^R	+{>	+-			R	R	FOUNDATION TO BE REMOVED	<u></u>		
IGNAL HEAD OPTICALLY PROGRAMMED	R →"P"	—[>"P"	→ "P"	SIGNAL FACE		G	G	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF O		
FLASHER INSTALLATION S DENOTES SOLAR POWER)	R O- D ′′F′′	0-t>"F"	●→ "F"			→ G	← Y ← G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR		IS	15
PEDESTRIAN SIGNAL HEAD	R -	-[]	-1			R	R	SAMPLING (SYSTEM) DETECTOR		S	S
PEDESTRIAN PUSHBUTTON DETECTOR	R ⑥	©	®	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD		(Y) G	Y G	EXISTING INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECTO	D	[P]	kananani
ACCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	R APS	@APS	APS O O O O O O O O O O O O O			★ 9	← Y ← G	EXISTING PREFORMED INTERSECTION LOOP DETECTOR			
ILLUMINATED SIGN 'NO LEFT TURN''	R ©	9	9	12" (300mm) PEDESTRIAN SIGNAL HEAD		"P"	′′P′′	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECTO PREFORMED INTERSECTION AND SAMPLING	R	IPPI	•
LLUMINATED SIGN	R			WALK/DON'T WALK SYMBOL		OW W		(SYSTEM) DETECTOR		PIS	PIS
'NO RIGHT TURN''				12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, OUTLINED				PREFORMED SAMPLING (SYSTEM) DETECTOR		PSI	PS
DETECTOR LOOP, TYPE I		l					•				
PREFORMED DETECTOR LOOP		P	Р	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, SOLID		<u>*</u>	×	RAILROAD SYMBOLS			
MICROWAVE VEHICLE SENSOR	R M	M	M	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER		● C ★ D	₽ C *D			EXISTING	PROPOSED
VIDEO DETECTION CAMERA	R V	$\widehat{\mathbb{V}}$	\bigcirc	RADIO INTERCONNECT	##*O	##+0		RAILROAD CONTROL CABINET		R R	B C
VIDEO DETECTION ZONE				RADIO REPEATER	R ERR	ERR	RR	RAILROAD CANTILEVER MAST ARM	<u> </u>	COX X	I ei X I
PAN, TILT, ZOOM CAMERA	R PTZ]1	PZ1	PIZ.	DENOTES NUMBER OF CONDUCTORS, ELECTRIC	C1MY	<u> </u>		FLASHING SIGNAL		$X \rightarrow X$	X ⊙ X
VIRELESS DETECTOR SENSOR	RW	(W)	(W)	CABLE NO. 14, UNLESS NOTED OTHERWISE, ALL DETECTOR LOOP CABLE TO BE SHIELDED				CROSSING GATE		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	XOX
WIRELESS ACCESS POINT	R			GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)				CROSSBUCK		>	*
E NAME = USER NAME = steedpa		DESIGNED - DAG/BCK	REVISED					DISTRICT ONE	F.A.U. RTE.	SECTION	COUNTY TOTAL SHI
.pw_work\pwidot\steedpa\d0169821\DistStd.dgn PLOT SCALE = 50.0000 '/ 1		DRAWN - BCK CHECKED - DAD	REVISED -	STATE DEPARTMENT	OF ILLINOIS			STANDARD TRAFFIC SIGNAL DESIGN DETAILS	1362	3200 RS-3 TS-05	COOK 25 2