## INDEX OF SHEETS

## STATE STANDARDS

STATE OF ILLINOIS

**DEPARTMENT OF TRANSPORTATION** 

SHEET NO.	DESCRIPTION	STANDARD NO	<u>DESCRIPTION</u>	
and the second section of the section of the second section of the secti	TITLE SHEET	000001-05	TYPICAL SYMBOLS, ABBREVIAT	IONS AND PATTERNS
2	INDEX OF SHEETS, STATE STANDARDS & GENERAL NOTES	442201 - <b>0.3</b>	CLASS C AND D PATCHES	
3	SUMMARY OF QUANTITIES	604001- <i>0</i> 3	FRAME AND LIDS, TYPE 1	
4-5	EXISTING AND PROPOSED TYPICAL SECTIONS	606001 <i>-04</i>	CONCRETE CURB AND COMBINA	TION CONCRETE CURB AND GUTTER
6-10	ROADWAY AND PAVEMENT MARKING PLANS	701301 <i>-0</i> 3	LANE CLOSURE, 2L, 2W, SHORT	TIME OPERATIONS
11	DETECTOR LOOP REPLACEMENT PLANS	701501 <i>-05</i>	URBAN LANE CLOSURE, 2L, 2W	, UNDIVIDED
12	DRIVEWAY DETAILS, DISTANCE BETWEEN ROW AND FACE OF CURB < 15' (4.5 M)			ANE 2W WITH MOUNTABLE MEDIAN
13	DETAILS FOR FRAME AND LIDS ADJUSTMENT WITH MILLING		URBAN LANE CLOSURE, MULTIL	ANE INTERSECTION
14	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT		TRAFFIC CONTROL DEVICES	
15	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT		DETECTOR LOOP INSTALLATION	w
16	BUTT JOINT AND HMA TAPER DETAILS	** ***********************************	TYPICAL LAYOUT FOR DETECT	ION LOOPS
17	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS AND DRIVEWAYS			
18	TYPICAL APPLICATIONS: RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)			
19	DISTRICT ONE TYPICAL PAVEMENT MARKINGS			
20	TRAFFIC CONTROL AND PROTECTION OF TURN BAYS (TO REMAIN OPEN TO TRAFFIC)			
21	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC ST	AGING		
22	ARTERIAL INFORMATION SIGNING			
23	DISTRICT ONE STANDARD TRAFFIC SIGNAL DESIGN DETAILS			

## GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT (800) 892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE, AND GAS FACILITIES. (48 HOUR NOTIFICATION REQUIRED)

THE CONTRACTOR WILL NOT BE ABLE TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT THE WRITTEN PERMISSION OF THE DEPARTMENT.

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGE OF DOLTON AND CALUMET CITY.

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT) IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS UNLESS OTHERWISE SPECIFIED.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC, THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1½ INCHES WHERE THE SPEED LIMIT IS 45 MPH OR LESS, AND 1 INCH WHERE THE SPEED LIMIT IS OVER 45 MPH. WITH WRITTEN APPROVAL FROM THE RESIDENT ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM OF 1:3 (V:H).

WHEN ARTIFICIAL LIGHTING IS UTILIZED IN NIGHT OPERATIONS, THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISABILITY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.

ALL PAVEMENT PATCHING AND DRIVEWAY PAVEMENT REMOVAL LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXISTING PAVEMENT MARKING LINES (AND RAISED REFLECTIVE PAVEMENT MARKERS) IN ORDER THAT THESE LOCATIONS CAN BE RE-ESTABLISHED FOR STRIPING. EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY THE ENGINEER.

DOUBLE LANE MARKERS ARE TO BE USED AS SHOWN ON THE DISTRICT ONE DETAIL "TYPICAL APPLICATIONS - RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)" SNOWN IN THE PLANS.

THE RESIDENT ENGINEER SHALL CONTACT MS. PATRICE HARRIS, AREA TRAFFIC FIELD ENGINEER, AT (708) 597-9800 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF FINAL PAVEMENT MARKINGS.

THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO THE INSTALLATION OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.

FILE NAME =	USER NAME = kellers	DESIGNED -	REVISED -	·
c:\pw_work\PWIDOT\KELLERS\dØ1763Ø2\D127	010-sht-plan.dgn	DRAWN -	REVISED -	1
	PLOT SCALE = 50.0000 '/ IN.	CHECKED -	REVISED -	ı
	PLOT DATE = 2/1/2010	DATE -	REVISED -	ı

DISTRICT ONE DETECTOR LOOP INSTALLATION DETAILS FOR

ROADWAY RESURFACING

MICHIC	3AN	CITY ROAD	(154TH	ST. TO	COTTAGE	GROVE AV	E.)
NDEX	OF	SHEETS, STA	TE STAN	IDARDS	AND GE	NERAL NOT	ES
	. [	SHEET NO. OF	SHEETS	ST	Α.	TO STA.	

SCALE:

F.A.U. RTE.	SECTIO	ON		COUNTY	TOTAL SHEETS	SHEET NO.
3593	3256 A-	RS-1		соок	24	2
			T	CONTRACT	NO. 6	0380
 FED. R	OAD DIST. NO. 1 IL	LINOIS FED.	AID	PROJECT	-7	1