## INDEX OF SHEETS

## LIST OF STATE STANDARDS

STATE OF ILLINOIS

**DEPARTMENT OF TRANSPORTATION** 

SHEET NO.	DESCRIPTION		STANDARD NO.	DESCRIPTION	
1	COVER SHEET		000001- <i>05</i>	STANDARD SYMBOLS, ABBREVIATIONS	AND PATTERNS
2	INDEX OF SHEETS, STANDARDS, AND GENERAL NOTES		442201 <b>- 03</b>	CLASS C AND D PATCHES	
3	SUMMARY OF QUANTITIES	fe j	604001 <b>- 03</b>	FRAME AND LIDS, TYPE 1	
. 4-6	TYPICAL SECTIONS PLAN		606001- <b>04</b>	COMBINATION CONCRETE CURB AND GL	JTTER
7-10	ROADWAY & PAVEMENT MARKINGS PLANS		701301 <b>- 03</b>	LANE CLOSURE, 2L, 2W, SHORT TIME	OPERATIONS
11	DETECTOR LOOP REPLACEMENT PLANS		701311 <b>- 03</b>	LANE CLOSURE, 2L, 2W MOVING OPERA	ATIONS - DAY ONLY
	DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING		701501 <b>- 05</b>	URBAN LANE CLOSURE, 2L, 2W UNDIVI	DED
12	•		701606 <b>-<i>06</i></b>	LANE CLOSURE, MULTILANE, 2-W, WITH	H MOUNTABLE MEDIAN
13	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT	701701-		URBAN LANE CLOSURE, MULTILANE INTERSECTION	
14	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT BUTT JOINT AND HMA TAPER DETAILS		701901- <i>01</i>	TRAFFIC CONTROL DEVICES	
. 16	HMA TAPER AT EDGE OF P.C.C. PAVEMENT				
17	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS,	AND DRIVEWAY	S .		
18	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS (SNOW	/-PLOW RESISTA	NT)		
19	DISTRICT ONE TYPICAL PAVEMENT MARKINGS				
20	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN	TO TRAFFIC)			

## GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED).

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGE OF WILMETTE

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1 1/2 INCHES (40 MM) WHERE THE SPEED LIMIT IS 45 MPH (45 KM/H) OR LESS AND 1 INCH WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (45 KM/H). WITH WRITTEN APPROVAL FROM THE ENGINEER. A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HOT-MIX ASPHALT TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT MS. CORA MATHIS AREA TRAFFIC FIELD ENGINEER AT (847) 715-8428 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKING.

THE RESIDENT ENGINEER SHALL VERIFY ALL EXISTING PAVEMENT MARKINGS BEFORE MILLING

DO NOT SCALE PLANS FOR CONSTRUCTION DIMENSIONS

DOUBLE LANE MARKERS ARE TO BE USED AS SHOWN ON THE DISTRICT ONE DETAIL "TYPICAL APPLICATIONS - RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)" SHOWN IN THE PLANS.

ALL PAVEMENT PATCHING LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS

THE CONTRACTOR SHALL CONTACT THE DISTRICT ONE TRAFFIC CONTROL SUPERVISOR AT (847)705-4470
A MINIMUM OF 72 HOURS IN ADVANCE OF BEGINNING WORK.

THE CONTRACTOR SHALL BE REQUIRED TO PROVIDE ACCESS TO ABUTTING PROPERTY AT ALL TIMES DURING THE CONSTRUCTION OF THIS PROJECT.

	FILE NAME =	USER NAME = guillaumefp	DESIGNED	- '-	REVISED -
1	c:\pw_work\pwidot\guillaumefp\d0177764\D	32210-sht-plan.dgn	DRAWN	-	REVISED -
1		PLOT SCALE = 50.0000 '/ IN.	CHECKED	-	REVISED -
	·	PLOT DATE = 2/10/2010	DATE	••	REVISED -

PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING

DISTRICT ONE DETECTOR LOOP INSTALLATION DETAILS FOR ROADWAY RESURFACING

ARTERIAL ROAD INFORMATION SIGN

INDEX OF S	HEETS, LIST OF	STATE ST	ANDARDS	& GI
	CRAWFORD	AVE. AND	<b>GLEVIEW</b>	RD.
SCALE: 1"=50"	SHEET NO. 1 OF	1 SHEETS	STA.	