Feb-Ø1-2Ø1Ø 10:57:37AM



## STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION



## INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt. "B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms.

(E) : Indicates epoxy coating.

DESIGNED KTH	& A S S O C I A T E S, P. C.
CHECKED ADL	Engineers • Architects • Surveyors
DRAWN KTH	☐ 61 km²t 246 Sweet, kmsp,ll ↑6 (217)223-5878 - Fax (217)223-588 ☐ 481 Pers Greet Reck (Annola,M) ☐ 51 22 24682 ☐ 48 k44 Street, Sante M, Annola,N ☐ 48 k44 Street, Sante M, Sa
CHECKED ADL	Linternet Address STATE OF ILLINOIS DESIGN FIRM * 1842738
BSD-1	11-1-09

\$FILE\$

17 9



## STANDARD MECHANICAL SPLICER

NOTES

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi

All reinforcement shall be lapped and tied to the splicer bars. Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications. See special provision for Mechanical Splicers.

See approved list of bar splicer assemblies and mechanical splicers for

## BAR SPLICER ASSEMBLY AND MECHANICAL SPLICER DETAILS STRUCTURE NO. 001-0062 & 0063

SHEET NO.14	F.A. RTE.	SECTION			COUNTY	TOTAL SHEETS	SHEET NO.	
	172	1-4B-1			ADAMS	165	148	
17 SHEETS						CONTRACT	NO. 72	A09
	FED. RC	AD DIST.	NO.	ILLINOIS	FED. A	ID PROJECT		

Klingner & Associates P.C.