





TYPICAL PLACEMENT OF PRISMATIC CURB REFLECTORS



1. PRISMATIC REFLECTORS SHALL BE MONO-DIRECTIONAL AND POSITIONED SO THAT THE REFLECTIVE FACE IS FACING THE APPROACHING TRAFFIC.
2. PRISMATIC REFLECTORS SHALL BE SECURED IN PLACE WITH AN EPOXY ADHESIVE.
3. PRISMATIC REFLECTORS SHALL BE EITHER AMBER OR CRYSTAL IN COLOR.
4. REFER TO SCHEDULES FOR PRISMATIC REFLECTOR QUANTITIES.
5. USE A MINIMUM OF 3 REFLECTORS ON ISLAND NOSES.



NOT TO SCALE

• (51-24IRS-3 & (51-24-2IRS-1

DISTRICT 7 DETAIL NO. 78200300

FILE NAME =	USER NAME = swartzw	DESIGNED -	REVISED -
c:\pw\work\PWIDOT\SWARTZRW\d8138979\d7	4390-ahd-detail.dgn	DRAWN -	REVISED -
	PLOT SCALE = 50.0000' / IN.	CHECKED -	REVISED -
	PLOT DATE = 1/28/2010	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PRISMATIC CURB REFLECTOR

SCALE: NA SHEET NO. 5 OF 5 SHEETS STA. TO STA.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
327		LAWRENCE	49	42
CONTRACT NO. 74390				
FED. ROAD DIST. NO.		ILLINOIS FED. AID PROJECT		