INDEX OF SHEETS:

SHEET NO.	DESCRIPTION							
1	COVER SHEET							
2	INDEX OF SHEETS, STANDARDS, AND GENERAL NOTES							
3	SUMMARY OF QUANTITIES							
4-6	TYPICAL SECTIONS							
7-11	PROPOSED ROADWAY/PAVEMENT MARKING PLANS							
12-13	DETECTOR LOOP REPLACEMENT PLANS							
14	DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING							
15	PAVEMENT PATCHING FOR BITUMINOUS SURFACE PAVEMENT							
16	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT							
17	BUTT JOINT AND BITUMINOUS TAPER DETAILS							
18	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS							
19	RAISED REFLECTIVE PAVEMENT MARKERS (SNOW PLOW RESISTANT)							
20	DISTRICT ONE TYPICAL PAVEMENT MARKINGS							
21	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC)							
22	PAVEMENT MARKINGS, LETTERS AND SYMBOLS FOR TRAFFIC STAGING							
23	ARTERIAL ROAD INFORMATION SIGN							
24	DISTRICT ONE STANDARD TRAFFIC SIGNAL DESIGN DETAIL							
25	DETECTOR LOOP INSTALLATION DETAIL FOR ROADWAY RESURFACING							

STATE STANDARDS:

000001-05 STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS

442201-03 CLASS C AND D PATCHES

701301-03 LANE CLOSURE, 2L 2W, SHORT TIME OPERATIONS

701306-02 LANE CLOSURE, 2L 2W SLOW MOVING DAY ONLY OPERATIONS, FOR SPEEDS GREATER THAN OR EQUAL TO 45 MPH

701336-05 LANE CLOSURE, 2L, 2W WORK AREAS IN SERIES FOR SPEEDS GREATER THAN OR EQUAL TO 45 MPH

SCALE:

701501-05 URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED

701606-0 LANE CLOSURE, MULTILANE, 2-W, WITH MOUNTABLE MEDIAN

701701-00 URBAN LANE CLOSURE, MULTILANE INTERSECTION

701901-01 TRAFFIC CONTROL DEVICES

GENERAL NOTES:

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 1-800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED).

THE RESIDENT ENGINEER SHALL VERIFY THE LOCATIONS OF ALL EXISTING PAVEMENT MARKINGS PRIOR TO START OF CONSTRUCTION

3 METER (10 FEET) TRANSITION SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER AND MEDIAN ITEMS OF WORK TO EXISTING CURBS & GUTTERS AND MEDIANS IN THE FIELD, UNLESS OTHERWISE SHOWN. THE TRANSITIONS SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OF WORK SPECIFIED.

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGE OF PLAINFIELD.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSON FROM THE DEPARTMENT.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 40 MM (1 1/2 INCHES WHERE THE SPEED LIMIT IS 80 KM/H (45 MPH) OR LESS AND 25 MM (1 INCH) WHERE THE SPEED LIMIT IS GREATER THAN 80 KM/H (45 MPH)). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 75 MM (3 INCHES) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).

THE ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705- 4470 A MINIMUM OF 72 HOURS PRIOR TO THE PLACEMENT OF ANY TRAFFIC CONTROL DEVICES

PERMANENT PAVEMENT MARKINGS SHALL BE THERMOPLASTIC (OF THE EXTRUDED TYPE) AND SHOULD BE PLACED IN ACCORDANCE WITH "DISTRICT ONE TYPICAL PAVEMENT MARKINGS" DETAIL. TWO WEEKS PRIOR TO PLACING PERMANENT PAVEMENT MARKINGS, CONTACT MS. CORA MATHIS, AREA TRAFFIC FIELD TECHNICIAN AT (815) 485-6475

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

ı	FILE NAME =	USER NAME = byurish	DESIGNED -	REVISED -	
- 1	c:\pw_work\PWIDOT\BYUNSH\dms92972\sh_rd	wy.dgn	DRAWN -	REVISED -	STATE OF ILLINOIS
- 1		PLOT SCALE = 50.0000 '/ IN.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION
- [PLOT DATE = 3/26/2009	DATE -	REVISED -	

US 30) 	07	F.A.P RTE.	SE	CTION	COUNTY	TOTAL SHEETS	SHEET NO.
INDEX OF SHEETS, LIST OF		STANDARDS	349	15	RS-11	WILL	25	2
AND GENERAL	NOTES				CONTRACT	NO. 6	0E68	
LOUGET NO OF CHEETS STA TO STA			550	DOLD DICT HE	4 121 214220 000 144			