



### OPTION 1



(FOR BUTT JOINT AND HMA TAPER SEE DETAIL BELOW)

### OPTION 2

#### TYPICAL TEMPORARY RAMP




# TYPICAL BUTT JOINT AND HMA TAPER FOR MILLING AND RESURFACING


FILE NAME = JSER NAME = galbannb DESIGNED - M. DE YONG REVISED -R. SHAH 10-25-94 \pw\_work\PWIDOT\GALBANNB\dØ107599\ DRAWN REVISED A. ABBAS 03-21-97 CHECKED REVISED M. GOMEZ 04-06-01 DATE PLOT DATE = 3/30/2009 06-13-90 REVISED - R. BORO 01-01-07

### STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS

OTHERWISE SHOWN.





## TYPICAL BUTT JOINT AND HMA TAPER FOR RESURFACING ONLY

\* PC CONCRETE, HMA OR HMA RESURFACED PAVEMENT.

### NOTES

- A: MAINLINE ROADWAYS AND MAJOR SIDE ROADS.
- B: MINOR SIDE ROADS.
- C: THE TEMP. RAMP SHALL BE CONSTRUCTED IMMEDIATELY UPON REMOVAL OF THE EXISTING HMA SURFACE.
- D: THE BUTT JOINT SHALL BE CONSTRUCTED IMMEDIATELY PRIOR TO PLACING THE PROPOSED HMA COURSES.
- E: TAPER THE TEMP. RAMP AT A RATE OF 3'-0" (900 mm) PER 1 INCH (25 mm) OF MILLING THICKNESS.
- F: INSTALLATION AND REMOVAL OF THE 4'-6" (1.35 m) TEMP. RAMP IS INCLUDED IN COST OF HMA SURFACE REMOVAL BUTT JOINT
- G: SEE ARTICLE 406.08 AND 406.14 OF THE STANDARD SPECIFICATIONS FOR "HMA AND/OR PCC SURFACE REMOVAL, BUTT JOINT".
- \* SEE TYPICAL SECTIONS FOR MILLING THICKNESS.

### BASIS OF PAYMENT:

THE BUTT JOINT WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER SQUARE YARD (SQUARE METER)
FOR "HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT" OR FOR "PORTLAND CEMENT CONCRETE SURFACE REMOVAL - BUTT JOINT".