INDEX OF SHEETS

ĊUE	ET NO	PECOPARTION
SHE	ET NO.	DESCRIPTION
	1	COVER SHEET
	2	INDEX OF SHEETS, STATE STANDARDS, AND GENERAL NOTES
	3	SUMMARY OF QUANTITIES
	4-5	TYPICAL SECTIONS
	6-11	ROADWAY AND PAVEMENT MARKING PLANS
	12	DETECTOR LOOP REPLACEMENT PLANS
	13	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT
	14	BUTT JOINT AND HMA TAPER DETAILS
	15	TRAFFIC CONTROL AND PROTECTION FOR SIDEROADS, INTERSECTIONS, AND DRIVEWAYS
	16	TYPICAL APPLICATION FOR RAISED REFLECTIVE PAVEMENT MARKERS
	17	DISTRICT ONE TYPICAL PAVEMENT MARKINGS
	18	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS
	19	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING
	20	ARTERIAL ROAD INFORMATION SIGN
	21	DISTRICT ONE DETECTOR LOOP INSTALLATION DETAIL FOR ROADWAY RESURFACING

STATE STANDARDS

000001- <i>05</i>	STANDARD	SYMBOLS,	ABBREVIATIONS	AND	PATTERNS
-------------------	----------	----------	---------------	-----	----------

442201-03 CLASS C AND D PATCHES

701301-03 LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS

701306-02 LANE CLOSURE, 2L, 2W, SLOW MOVING OPERATION DAY ONLY FOR SPEEDS \geq 45 MPH

701311-03 LANE CLOSURE, 2L 2W, MOVING OPERATIOS, DAY ONLY

701606-00 URBAN LANE CLOSURE, MULTILANE 2W WITH MOUNTABLE MEDIAN

701701-04 URBAN LANE CLOSURE, MULTILANE INTERSECTION

701901-01 TRAFFIC CONTROL DEVICES

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOURS NOTIFICATION REQUIRED).

10 FEET (3 METER) TRANSITIONS SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER AND MEDIAN ITEMS OF WORK TO EXISTING CURB AND GUTTERS AND MEDIANS IN THE FIELD, UNLESS OTHERWISE SHOWN. THE TRANSITIONS SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OF WORK SPECIFIED.

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE CITY OF ELGIN AND VILLAGE OF HOFFMAN ESTATES.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC, THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1½ INCHES (40 MM) WHERE THE SPEED LIMIT IS 45 MPH (80 KM/H) OR LESS AND 1 INCH (25 MM) WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (80 KM/H). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES (75 MM) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT MR. WALTER CZARNY, AREA TRAFFIC FIELD ENGINEER AT (847) 715-8419 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKING.

THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MININMUM OF 72 HOURS PRIOR TO THE PLACEMENT OF TEMPORARY TRAFFIC CONTROL DEVICES.

THE RESIDENT ENGINEER SHALL DETERMINE THE LOCATIONS OF CLASS "D" PATCHES.

FILE, NAME = .	USER NAME = shiranisb	DESIGNED -	REVISED -	
c:\pw_work\PWIDOT\SHIRANISB\dms89101\sh_	-dwy.dgn	DRAWN -	REVISED -	l
	PLOT SCALE = 50.0000 '/ IN.	CHECKED -	REVISED -	
	PLOT DATE = 3/17/2009	DATE -	REVISED -	