INDEX OF SHEETS

DISTRICT ONE DETECTOR LOOP INSTALLATION DETAILS FOR

ROADWAY RESURFACING

STATE STANDARDS

SHEET N	10.	DESCRIPTION	STANDARD NO.	<u>DESCRIPTION</u>
1		TITLE SHEET	000001 <i>-05</i>	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
2		INDEX OF SHEETS, STATE STANDARDS, GENERAL NOTES AND MIX SHEDULE	442201-03	CLASS C AND D PATCHES
3		SUMMARY OF QUANTITIES	701301-03	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
4		EXISTING AND PROPOSED TYPICAL CROSS SECTIONS	701311- 03	LANE CLOSURE, 2L, 2W, MOVING DAY ONLY OPERATIONS
5 -	6	ROADWAY AND PAVEMENT MARKING PLANS	701501 <i>-05</i>	URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED
7		DETECTOR LOOP PLANS	701701-06	URBAN LANE CLOSURE, MULTILANE INTERSECTION
8		DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT	701901-01	TRAFFIC CONTROL DEVICES
10		CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT	886001- <i>01</i>	DETECTOR LOOP INSTALLATIONS TYPICAL LAYOUT FOR DETECTION LOOPS
11		BUTT JOINT AND HMA TAPER DETAILS	886006-27	TIPICAL LATOUT FOR BETECTION LOOPS
12		TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS		
13		TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)		
14		DISTRICT ONE TYPICAL PAVEMENT MARKINGS		
15		TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC)		
16		PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING		
17		ARTERIAL ROAD INFORMATION SIGN		

PLAN NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC. TELEPHONE AND GAS FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED)

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES WITHIN THE VILLAGES OF LAGRANGE PARK AND BROOKFIELD.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HOT-MIX ASPHALT TAPER DETAILS" SHEETS INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT MS. PATRICE HARRIS AREA TRAFFIC FIELD ENGINEER AT (708) 597-9800 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKING.

THE RESIDENT ENGINEER SHALL CONTACT THE DISTRICT ONE ARTERIAL TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO START OF WORK.

10 FEET (3 METERS) TRANSITION SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER TO EXISTING CURB AND GUTTERS IN THE FIELD, UNLESS OTHERWISE SHOWN. THE TRANSITION SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OR WORK SPECIFIED.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1½ INCHES (40MM) WHERE THE SPEED LIMIT IS 45 MPH (80 KM/H) OR LESS AND 1 INCH (25 MM) WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (80 KM/H). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES (75 MM) MAY BE ALLOWED IF THE EDGE OFTHE MILLING IS SLOPED A MINIMUM 1:3 (V:H).

FILE NAME =	USER NAME = bonksl	DESIGNED -	REVISED -
c:\pw_work\pwidot\banksl\dms89376\sh_rd	y.dgn	DRAWN -	REVISED -
•	PLOT SCALE = 50.0000 '/ IN.	CHECKED -	REVISED -
	PLOT DATE = 3/24/2009	DATE -	REVISED -

SCALE:

KEMMAN AVE. FROM 31ST STREET TO SHAWMUT AVE.	F.A.U. RTE.	SECTION	COUNTY	TOTAL	SHE	
INDEX OF SHEET, STATE STANDARDS & GENERAL NOTES		2714	0404 RS-10	COOK	18	1 3
INDEX OF SHELL, STATE STANDARDS & GENE				NO.	60F4	
ALE. SHEET NO DE SHEETS STA	TO STA	<u> </u>	THE THOUGHTON AT	O BOO IECT		