


(FOR BUTT JOINT AND HMA TAPER SEE DETAIL BELOW)


### OPTION 1



(FOR BUTT JOINT AND HMA TAPER SEE DETAIL BELOW)

### OPTION 2

### TYPICAL TEMPORARY RAMP





# TYPICAL BUTT JOINT AND HMA TAPER FOR MILLING AND RESURFACING

FILE NAME = DESIGNED - M. DE YONG REVISED R. SHAH 10-25-94 DRAWN REVISED A. ABBAS 03-21-97 PLOT SCALE = 50.0000 '/ IN. CHECKED REVISED M. GOMEZ 04-06-01 PLOT DATE = 3/23/2009 DATE 06-13-90 REVISED R. BORO 01-01-07

### STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

BUTT JOINT AND 2692 2008-065 RS COOK HMA TAPER DETAILS BD400-05 BD32 CONTRACT NO. 60F50 SCALE: NONE SHEET NO. 1 OF 1 SHEETS STA. TO STA.





## TYPICAL BUTT JOINT AND HMA TAPER FOR RESURFACING ONLY

\* \* PC CONCRETE, HMA OR HMA RESURFACED PAVEMENT.

#### NOTES

- A: MAINLINE ROADWAYS AND MAJOR SIDE ROADS.
- B: MINOR SIDE ROADS.
- C: THE TEMP, RAMP SHALL BE CONSTRUCTED IMMEDIATELY UPON REMOVAL OF THE EXISTING HMA SURFACE.
- D: THE BUTT JOINT SHALL BE CONSTRUCTED IMMEDIATELY PRIOR TO PLACING THE PROPOSED HMA COURSES.
- E: TAPER THE TEMP. RAMP AT A RATE OF 3'-0" (900 mm) PER 1 INCH (25 mm) OF MILLING THICKNESS.
- F: INSTALLATION AND REMOVAL OF THE 4'-6" (1.35 m) TEMP. RAMP IS INCLUDED IN COST OF HMA SURFACE REMOVAL - BUTT JOINT
- G: SEE ARTICLE 406.08 AND 406.14 OF THE STANDARD SPECIFICATIONS FOR "HMA AND/OR PCC SURFACE REMOVAL, BUTT JOINT".
- \* SEE TYPICAL SECTIONS FOR MILLING THICKNESS.
- \* \* \* \* 20'-0" (6.1 m) PER 1 (25) RESURFACING (NOTE "A") 10'-0" (3.0 m) PER 1 (25) RESURFACING (NOTE "B")

#### BASIS OF PAYMENT:

THE BUTT JOINT WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER SQUARE YARD (SQUARE METER)
FOR "HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT" OR FOR "PORTLAND CEMENT CONCRETE SURFACE REMOVAL- BUTT JOINT".

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.

TOTAL SHEE SHEETS NO.