## INDEX OF SHEETS

## SHEET NO DESCRIPTION

- 1 COVER SHEET
- 2 INDEX OF SHEETS, STATE STANDARDS AND GENERAL NOTES
- 3 SUMMARY OF QUANTITIES
- 4 TYPICAL SECTIONS
- 5-7 ROADWAY AND PAVEMENT MARKING PLAN
- 8 DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING (BD-8)
- 9 PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT (BD-22)
- 10 CURB AND GUTTER REMOVAL AND REPLACEMENT (BD-24)
- 11 BUTT JOINT AND HMA TAPER DETAILS (BD-32)
- 12 HMA TAPER AT EDGE OF P.C.C. PAVEMENT (BD-33)
- 13 TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS,
  INTERSECTIONS, AND DRIVEWAYS (TC-10)
- 14 TYPICAL APPLICATIONS RAISED REFLECTIVE
  PAVEMENT MARKERS (SNOW PLOW RESISTANT) (TC-11)
- 15 DISTRICT ONE TYPICAL PAVEMENT MARKINGS (TC-13)
- 16 ARTERIAL ROAD INFORMATION SIGN (TC-22)

## STATE STANDARDS

000001-05 STANDARD SYMBOLS, ABBREVIATIONS, AND PATTERNS

420001 - 07 PAVEMENT JOINTS

442201-03 CLASS C AND D PATCHES

606201-02 TYPE B GUTTER (INLET, OUTLET & ENTRANCE)

606211-03 OUTLETS TYPE 2 FOR TYPE B GUTTER

701301-03 LANE CLOSURE, 2L. 2W. SHORT TIME OPERATIONS

701306-02 LANE CLOSURE, 2L, 2W, SLOW MOVING OPERATIONS DAY ONLY, FOR SPEEDS  $\geq$  45 MPH

701311-03 LANE CLOSURE, 2L, 2W, MOVING DAY OPERATIONS-DAY ONLY

701901-0/ TRAFFIC CONTROL DEVICES

780001-02 TYPICAL PAVEMENT MARKINGS

## GENERAL NOTES

- BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE, AND GAS FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED)
- 2. 10 FEET (3 METER) TRANSITIONS SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER AND MEDIAN ITEMS OF WORK TO EXISTING CURB AND GUTTER AND MEDIANS IN THE FIELD UNLESS OTHERWISE SHOWN. THE TRANSITIONS SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OF WORK SPECIFIED.
- 3. THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES.
- 4. THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.
- 5. WHEN ARTIFICIAL LIGHTING IS USED IN NIGHT OPERATIONS THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISIBILITY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.
- 6. THE FOLLOWING RATES OF APPLICATION HAVE BEEN ASSUMED IN CALCULATING PLAN QUANTITIES:

BITUMINOUS MATERIALS (PRIME COAT)

0.0004 TONS/SQ YD

HOT-MIX ASPHALT SURFACE COURSE

112 LBS/SQ YD/INCH

HOT-MIX ASPHALT BINDER COURSE

112 LBS/SQ YD/INCH

- THE ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISORS AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO THE START OF WORK.
- 8. TWO WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKINGS THE ENGINEER SHALL CONTACT MS. CORA MATHIS, AREA TRAFFIC FIELD ENGINEER, AT (815) 485-6475.
- 9. WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1 1/2" (40 MM) WHERE THE SPEED LIMIT IS 45 MPH (80 KM/H) OR LESS AND 1" (25 MM) WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (80 KM/H). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3" (75 MM) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 3:1 (H:V).
- 10. BUTT JOINTS WILL BE INSTALLED AT THE END OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT). IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.
- 11. FOR PAVEMENT MARKING, REFER TO DISTRICT ONE TYPICAL MARKINGS FOR DETAILS SHOWN.
- 12. MATCH EXISTING PAVEMENT MARKINGS AT PROJECT LIMITS.
- 13. NO OVERNIGHT LANE CLOSURES SHALL BE ALLOWED.
- 14. ALL PATCHES OPENED ON A PARTICULAR DAY MUST BE FILLED THAT DAY TO THE TOP OF THE MILLED PAVEMENT SURFACE.

00	Ciorba Group, Inc.
	CONSULTING ENGINEERS
(	5507 North Cumberland Avenue, Suite 402
	Chicago, Illinois 60656

USER NAME = alau	DESIGNED	MWR	REVISED	-
	DRAWN	MWR	REVISED	-
PLOT SCALE = 1.00000 '/ IN.	CHECKED	<b>W</b> BL	REVISED	-
PLOT DATE = 4/2/2009	DATE	3/31/09	REVISED	-