INDEX OF SHEETS

LIST OF STATE STANDARDS

SHEET	DESCRIPTION	NO.	DESCRIPTION			
NO.	DESCRIPTION	000001-05	STANDARD SYMBOLS, ABBREVIATIONS, AND PATTERNS			
1	COVER SHEET	442201- <i>03</i> 701421- <i>02</i>	CLASS C AND D PATCHES LANE CLOSURE, MULTILANE, DAY OPERATIONS ONLY,			
2	INDEX OF SHEETS, STATE STANDARDS, PLAN NOTES	701606 <i>-06</i>	FOR SPEEDS > 45 MPH TO 55 MPH. URBAN LANE CLOSURE, MULTILANE, 2-WAY,			
3	SUMMARY OF QUANTITIES		WITH MOUNTABLE MEDIAN			
4 - 5	TYPICAL SECTIONS	701701-06	URBAN LANE CLOSURE, MULTILANE,			
4-5	TIPICAL SECTIONS	701901 <i>-01</i>	TRAFFIC CONTROL DEVICES			
6 - 11	ROADWAY AND PAVEMENT MARKING PLANS	886001 <i>-01</i>	DETECTOR LOOP INSTALLATIONS			
12 - 17	DETECTOR LOOP REPLACEMENT PLANS	886006 - 01	TYPICAL LAYOUT FOR DETECTION LOOPS			
18	DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH	MILLING				
19	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT					
20	CURB OR CURB AND GUTTER REMOVAL AND REPLACE	MENT				
21	BUTT JOINT AND HMA TAPER DETAILS					
22	H.M.A. TAPER AT EDGE OF P.C.C. PAVEMENT					
23	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROAD INTERSECITONS, AND DRIVEWAYS	S,				
24	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEME MARKERS (SNOW-PLOW RESISTANT)	NT				
25	DISTRICT ONE TYPICAL PAVEMENT MARKINGS					
26	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS REMAIN OPEN TO TRAFFIC)	(ТО				
27	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TR	AFFIC STAGING				
28	ARTERIAL ROAD INFORMATION SIGN					
29	DISTRICT ONE DETECTOR LOOP INSTALLATION DETA FOR ROADWAY RESURFACING	ILS				

PLAN NOTES - CITY OF CHICAGO

ALL CATCH BASINS IN THE CITY OF CHICAGO MUST MEET THE DEPARTMENT OF SEWERS' STANDARDS.

PERMITS FROM THE DEPARTMENT OF SEWERS ARE REQUIRED FOR ALL UNDERGROUND STORM, SANITARY OR COMBINED SEWER SYSTEM CONSTRUCTION, AND FOR ALL WORK INVOLVING ADJUSTMENT OF SEWER STRUCTURES. THE DEPARTMENT OF SEWERS' PERMIT MUST BE OBTAINED BY A LICENSED SEWER DRAIN LAYER PRIOR TO THE START OF CONSTRUCTION. THE LICENSED SEWER CONTRACTOR/SUBCONTRACTOR MUST SUBMIT TWO SETS OF PLANS APPROVED BY THE DEPARTMENT OF SEWERS FOR THE ISSUE OF THE SEWER PERMIT TO SUITE 410, 333 SOUTH STATE STREET, CHICAGO, IL 60604-3971. INSPECTION WILL BE PROVIDED BY THE DEPARTMENT OF SEWERS

IN CASE OF DAMAGE TO THE CITY OF CHICAGO SEWERS, PRIVATE AND PUBLIC DRAINS, SEWER STRUCTURES AND/OR BENCH MONUMENTS, THE CONTRACTOR SHALL IMMEDIATELY CONTACT THE DEPARTMENT OF SEWERS AT (312)747-7892 OR (312)747-7893.

BENCH MONUMENT LOCATIONS WITHIN THE LIMITS OF THE IMPROVEMENT CAN BE OBTAINED FROM THE DEPARTMENT OF SEWERS AT SUITE 410, 333 SOUTH STATE STREET, CHICAGO, IL 60604-3971, THE CONTRACTOR IS RESPONSIBLE FOR THE COST OF REPLACING ANY BENCH MONUMENT DAMAGED OR DESTROYED DURING CONSTRUCTION.

SIDEWALK ACCESSIBILITY RAMPS SHALL NOT BE CONSTRUCTED DIRECTLY OVER EXISTING OR PROPOSED DRAINAGE STRUCTURES. ALL BROKEN, CRACKED, WORN OR OTHERWISE DAMAGED OR BICYCLE UNSAFE FRAMES AND GRATES OR LIDS ON SEWER STRUCTURES SHALL BE REPLACED WITH NEW DEPARTMENT OF SEWERS' STANDARD FRAMES AND GRATES OR LIDS. OLD FRAMES AND GRATES OR LIDS SHALL BE DELIVERED TO THE DEPARTMENT OF SEWERS AT 39TH STREET AND ASHLAND AVENUE

CITY OF CHICAGO WATER VALVE VAULTS AND SEWER STRUCTURES SHALL NOT BE CLOSED, COVERED OR OTHERWISE OBSTRUCTED DURING CONSTRUCTION WITHOUT WRITTEN PERMISSION FROM THE CITY OF CHICAGO DEPARTMENT OF WATER AND/OR DEPARTMENT

CURB AND GUTTER CONSTRUCTION SHALL PROVIDE A MINIMUM CURB HEIGHT OF 75 MM (3")

PAVEMENT REPLACEMENT AROUND FRAMES AND GRATES OR LIDS WHERE DRAINAGE, WATER MAIN OR ELECTRICAL STRUCTURES ARE ADJUSTED OR RECONSTRUCTED, SHALL BE WITH CLASS SI CONCRETE.

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 OR "CUAN" (CHICAGO UTILITY ALERT NETWORK) AT 312-744-7000 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES, (48 HOURS NOTIFICATION IS REQUIRED).

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH THE UTILITY COMPANIES WITHIN THE VILLAGES OF OAK LAWN, EVERGREEN PARK, MERRIONETTE PARK AND CITY OF CHICAGO.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHOULD CONTACT MS. PATRICE HARRIS, AREA TRAFFIC ENGINEER, AT (708) 597-9800 PRIOR TO PLACING ANY PAVEMENT

THE CONTRACTOR SHALL CONTRACT THE DISTRICT ONE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO START OF WORK.

10 FEET (3 METERS) TRANSITIONS SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER AND MEDIAN ITEMS OF WORK TO EXISTING CURBS AND GUTTERS AND MEDIANS IN THE FIELD, UNLESS OTHERWISE SHOWN. THE TRANSITION SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OF WORK SPECIFIED.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1 1/2 INCHES (40MM) WHERE THE SPEED LIMIT IS 45 MPH (80 KM/H). WITH WRITEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES (75MM) MAY BE ALLOWED IFTHE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H)

STATE	OF	ILLINOIS
DEPARTMENT	OF	FRANSPORTATION

CRAWFORD AVE 103RD STREET TO 123RD STREET	F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
INDEX OF SHEETS, STATE STANDARDS AND GENERAL NOTES	3778	1316 RS-3	COOK	29	2
INDEA OF SHEETS, STATE STANDARDS AND DENETRE NOTES			CONTRACT	NO. 6	OC88
SCALE: NONE SHEET NO. OF SHEETS STA. TO STA.	ILLINOIS FED. AID PROJECT				