## INDEX OF SHEETS

DESCRIPTION	STANDARD NO.	DESCRIPTI
TITLE SHEET	000001 <i>-05</i> TYPICAL	SYMBOLS, ABBRE
INDEX OF SHEETS, STATE STANDARDS & GENERAL NOTES	442201-03 CLASS	C AND D PATCHES
SUMMARY OF QUANTITIES	604086-02 FRAME	AND GRATE, TYPE
EXISTING AND PROPOSED TYPICAL SECTIONS	606001- <b>04</b> CONCRE	TE CURB AND COM
ROADWAY AND PAVEMENT MARKING PLANS		
DETAILS FOR FRAME AND LIDS ADJUSTMENT WITH MILLING	701426-03 LANE CI	LOSURE, MULTILANE
PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT	701606- <b>06</b> URBAN 1	LANE CLOSURE. MU
CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT		
BUTT JOINT AND HMA TAPER		
TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS AND DRIVEWAYS		
TYPICAL APPLICATIONS: RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)	886006-01 <u>TYPICAL</u>	LAYOUT FOIL DET
DISTRICT ONE TYPICAL PAVEMENT MARKINGS		
TRAFFIC CONTROL AND PROTECTION OF TURN BAYS (TO REMAIN OPEN TO TRAFFIC)		
PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING		
ARTERIAL INFORMATION SIGNING		
DISTRICT 1 DETECTOR LOOP INSTALLATION DETAILS FOR ROADWAY RESURFACING		
	TITLE SHEET  INDEX OF SHEETS, STATE STANDARDS & GENERAL NOTES  SUMMARY OF QUANTITIES  EXISTING AND PROPOSED TYPICAL SECTIONS  ROADWAY AND PAVEMENT MARKING PLANS  DETAILS FOR FRAME AND LIDS ADJUSTMENT WITH MILLING  PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT  CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT  BUTT JOINT AND HMA TAPER  TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS AND DRIVEWAYS  TYPICAL APPLICATIONS: RAISED REFLECTIVE PAVEMENT  MARKERS (SNOW-PLOW RESISTANT)  DISTRICT ONE TYPICAL PAVEMENT MARKINGS  TRAFFIC CONTROL AND PROTECTION OF TURN BAYS (TO REMAIN OPEN TO TRAFFIC)  PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING ARTERIAL INFORMATION SIGNING  DISTRICT 1 DETECTOR LOOP INSTALLATION DETAILS FOR—	TITLE SHEET  INDEX OF SHEETS, STATE STANDARDS & GENERAL NOTES  SUMMARY OF QUANTITIES  EXISTING AND PROPOSED TYPICAL SECTIONS  ROADWAY AND PAVEMENT MARKING PLANS  DETAILS FOR FRAME AND LIDS ADJUSTMENT WITH MILLING  PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT  CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT  TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS AND DRIVEWAYS  TYPICAL APPLICATIONS: RAISED REFLECTIVE PAVEMENT  DISTRICT ONE TYPICAL PAVEMENT MARKINGS  TRAFFIC CONTROL AND PROTECTION OF TURN BAYS  (TO REMAIN OPEN TO TRAFFIC)  PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING  ARTERIAL INFORMATION SIGNING  DISTRICT 1 DETECTOR 100P INSTALLATION DETAILS FOR—

## STATE STANDARDS

## TION

REVIATIONS AND PATTERNS

23

MBINATION CONCRETE CURB AND GUTTER

DAY ONLY

NE, INTERMITTENT OR MOVING OPERATIONS

MULTILANE 2W WITH MOUNTABLE MEDIAN

MULTILANE INTERSECTION

ATION

TECTION LOOPS

## GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT (800) 892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE, AND GAS FACILITIES. (48 HOUR NOTIFICATION REQUIRED)

THE CONTRACTOR WILL NOT BE ABLE TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT THE WRITTEN PERMISSION OF THE DEPARTMENT.

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGES OF LINCOLNWOOD AND SKOKIE.

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT) IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS UNLESS OTHERWISE SPECIFIED.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC, THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1/2 INCHES WHERE THE SPEED LIMIT IS 45 MPH OR LESS, AND 1 INCH WHERE THE SPEED LIMIT IS OVER 45 MPH. WITH WRITTEN APPROVAL FROM THE RESIDENT ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM OF 1:3 (V:H).

WHEN ARTIFICIAL LIGHTING IS UTILIZED IN NIGHT OPERATIONS, THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISABILITY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.

ALL PAVEMENT PATCHING LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXISTING PAVEMENT MARKING LINES (AND RAISED REFLECTIVE PAVEMENT MARKERS) IN ORDER THAT THESE LOCATIONS CAN BE RE-ESTABLISHED FOR STRIPING. EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY THE ENGINEER.

DOUBLE LANE MARKERS ARE TO BE USED AS SHOWN ON THE DISTRICT ONE DETAIL "TYPICAL APPLICATIONS - RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)" SNOWN IN THE PLANS.

THE RESIDENT ENGINEER SHALL CONTACT MR. DON CHIARUGI, AREA TRAFFIC FIELD ENGINEER, AT (847) 705-4470 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF FINAL PAVEMENT MARKINGS.

THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO THE INSTALLATION OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.

FILE NAME =	USER NAME = yoonje	DESIGNED -	REVISED -		T				F.A.U.	SECTION	00111171	TOTAL	SHEET
c:\pw_work\PWIDDT\Y00NJE\d0136065\McLed	n.dgn	DRAWN -	REVISED -	STATE OF ILLINOIS	MCLEAN BLVD (SPRING ST. TO S. LANCASTER CIRCLE)			CIRCLE)	RTE.	SECTION	COUNTY	SHEETS	NO.
	PLOT SCALE = 50.0000 '/ IN.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION	INDEX OF SHEETS, STATE STANDARDS AND GENERAL NOTE:		RAL NOTES	2509	94RS	KANE	20	2	
	PLOT DATE = 4/18/2009	DATE -	REVISED ~	DEFERENCE OF THAIRD ON A TION	SCALE:	SHEET NO. OF SHEETS	STA.	TO STA	FED. ROAD DIST	NO. 1 THE INCIS FED. A	CONTRAC	T NO. 6	30H04