INDEX OF SHEETS

ARTERIAL ROAD INFORMATION SIGN

ROADWAY RESURFACING

21

DISTRICT ONE DETECTOR LOOP INSTALLATION DETAILS FOR

STATE STANDARDS

FOR SPEEDS > 45 MPH

	SHEET NO.	DESCRIPTION	STANDARD NO.	<u>DESCRIPTION</u>		
	1	TITLE SHEET	000001- <i>05</i>	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS		
	2	INDEX OF SHEETS, STATE STANDARDS, GENERAL NOTES AND MIX SHEDULE	442201 - 03	CLASS C AND D PATCHES		
	3	SUMMARY OF QUANTITIES	701011 <i>-02</i>	OFF-RD MOVING OPERATIONS 2L, 2W DAY ONLY FOR SPEEDS > 45 MPH		
	4 - 6	EXISTING AND PROPOSED TYPICAL CROSS SECTIONS	701301 -03	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS		
	7 - 8	ROADWAY AND PAVEMENT MARKING PLANS	701306 -<i>02</i>	LANE CLOSURE 2L, 2W SLOW MOVING OPERATIONS-DAY ONLY FOR SPEEDS		
	9 - 10	DETECTOR LOOP PLANS				
	11	DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING	701311- <i>03</i>	LANE CLOSURE 2L, 2W MOVING OPERATIONS-DAY ONLY		
	12	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT	701501- <i>05</i>	URBAN LANE CLOSURE, 2L, 2W UNDIVIDED		
	13	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT	701901 <i>-01</i>	TRAFFIC CONTROL DEVICES		
	14	BUTT JOINT AND HMA TAPER DETAILS	886001- <i>01</i>	DETECTOR LOOP INSTALLATIONS		
	15	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS	886006- <i>0</i> 4	TYPICAL LAYOUT FOR DETECTION LOOPS		
	16	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)				
	17	DISTRICT ONE TYPICAL PAVEMENT MARKINGS				
	18	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC)				
	19	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING				
	20	ADTEDIAL DOAD INCODUATION COM				

PLAN NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED)

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES WITHIN THE VILLAGES OF SOUTH CHICAGO HEIGHTS AND STEGER.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HOT-MIX ASPHALT TAPER DETAILS" SHEETS INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT MS. PATRICE HARRIS AREA TRAFFIC FIELD ENGINEER AT (708) 597-9800 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKING.

THE RESIDENT ENGINEER SHALL CONTACT THE DISTRICT ONE ARTERIAL TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO START OF WORK.

10 FEET (3 METERS) TRANSITION SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER TO EXISTING CURB AND GUTTERS IN THE FIELD, UNLESS OTHERWISE SHOWN. THE TRANSITION SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OR WORK SPECIFIED.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1½ INCHES (40MM) WHERE THE SPEED LIMIT IS 45 MPH (80 KM/H) OR LESS AND 1 INCH (25 MM) WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (80 KM/H). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES (75 MM) MAY BE ALLOWED IF THE EDGE OFTHE MILLING IS SLOPED A MINIMUM 1:3 (V:H).

FILE NAME =	USER NAME = banksl	DESIGNED -	REVISED -
c:\pw_work\pwidot\banksl\d0137355\D15670	9-sht-plan.dgn	DRAWN -	REVISED -
	PLOT SCALE = 50.0000 '/ IN.	CHECKED -	REVISED -
	PLOT DATE = 4/13/2009	DATE -	REVISED -