



- THERMOPLASTIC PAVEMENT MARKING LEGEND**
- |  |   |
|--|---|
| ① 4" DOUBLE SOLID YELLOW LINE (11' C-C)    | ⑧ 4" SINGLE SOLID YELLOW LINE                           |
| ② 4" WHITE LANE LINE (10' LINE, 30' SPACE) | ⑨ 4" YELLOW LANE LINE (10" LINE, 30' SPACE)             |
| ③ 6" SOLID WHITE LINE                      | ⑩ RAISED REFLECTIVE PAVEMENT MARKERS                    |
| ④ 24" SOLID WHITE STOP BAR                 | ⑪ 12" SOLID YELLOW DIAGONAL LINE, 45 DEGREES @ 75' O.C. |
| ⑤ LETTERS AND SYMBOLS                      | ⑫ 4" WHITE EDGE LINE                                    |
| ⑥ 6" DOTTED WHITE LINE (2' LINE, 6' SPACE) | ⑬ 12" SOLID WHITE DIAGONAL LINE, 45 DEGREES @ 75' O.C.  |
| ⑦ 6" SOLID WHITE LANE LINE                 |   |
- ◁ ONE-WAY CRYSTAL  
 ▲ ONE-WAY AMBER  
 ◆ TWO-WAY AMBER

DATE: 4/22/2008  
 FILE NAME: I:\11222615\11222615.dgn  
 USER: JRM  
 MODEL:



200 West Front Street  
Wheaton, IL 60187

DESIGNED - KSD	REVISED -
DRAWN - KSD	REVISED -
CHECKED - CMJ	REVISED -
DATE -	REVISED -

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

**HIGGINS ROAD  
ROADWAY AND PAVEMENT MARKING PLAN**

SCALE: 1" = 50'    SHEET NO. 3 OF 9 SHEETS    STA. 70+00 TO STA. 100+00

F.A.P. RTE. 341	SECTION 3077-RS	COUNTY KANE	TOTAL SHEETS 30	SHEET NO. 7
CONTRACT NO. 60H35				
FED. ROAD DIST. NO. 1   ILLINOIS FED. AID PROJECT				