GENERAL NOTES

ENGINEERS FIELD OFFICE

Add the following sentence to the end of paragraph 670.02 (i) and 670.04 (e): All of the telephone lines provided shall have unpublished numbers.

PAVING SURFACE COURSE

Continuous paving operations on the main roadway shall be maintained at all times during the construction of the hot-mix asphalt surface. No interruptions for side roads, entrances, turn lanes, etc. will be allowed.

BITUMINOUS MIXTURE REQUIREMENTS

The following mixture requirements are applicable for this project:

	ROUTE		SECTION	COUNTY	SHEET		
	F.A.	VAR	*	DEODIA	TOTAL	NO.	
	MKD.	US 150		PEORIA	100	9	
*/400V 400 400) DO 0 400 DO 0							

*(108X,130,102)RS-3;129RS-4,101RS-2

4/2/2009

Contract 68471 US 150 from Knox Cty line to IL 78(N)

Mixture Use(s):	Surface Course	Level Binder Course	Incidental Surface	Class D Patches	
AC/PG:	PG 64-22	SBS or SBR 70-22	PG 64-22	PG 64-22	
RAP% (Max): **	15%	0%	15%	25%	
Design Air Voids:	4.0% @ N=50	3.0% @ N=50	4.0% @ N=50	4.0% @ N=50	
Mixture Composition: (Gradation Mixture)	IL 9.5 or IL12.5	IL 4.75	IL 9.5 or IL12.5	IL 19.0	
Friction Aggregate:	Mixture D (dolomite only)	N.A.	Mixture C	Ń.A.	

** If RAP option is selected, the asphalt cement grade may need to be adjusted, this will be determined by the Materials Engineer.

COMMITMENTS

Commitments are not to be altered without the written approval of all parties to which the commitment was made. No commitments were made on this project.

CONTRACT NO. 68890

THIS SHEET FOR INFORMATION ONLY