



SUB-BASE GRANULAR MATERIAL, TYPE B MATERIAL WILL BE RE-USED AS SUB-BASE GRANULAR MATERIAL, TYPE B, 24", AS USED FOR ROADWAY CONSTRUCTION.

8.0' FROM OUTER EDGE OF UTILITY VARIES 8.0' FROM OUTER EDGE OF UTILITY

10% MAX.

10% MAX.

3.0' MIN.

PROPOSED ELEVATION, BOTTOM OF SUB-BASE GRANULAR MATERIAL, TYPE B 24"

EXISTING COMBINED SEWER PIPE

COMBINED SEWER CONSTRUCTION PROTECTION

(SEE COMBINED SEWER CROSSING STATIONS)

COMBINED SEWER CROSSING STATIONS:

1. NB I-57 STA. 192+25.30 (60")
2. NB I-57 STA. 231+94.12 / EB I-57 TO I-94 CONN. STA. 407+29.83 (5'-8" x 3'-7" BOX)
3. NB I-94 (BISHOP FORD) STA. 2038+68.07 (7'-6" x 6'-0" DOUBLE BOX)
4. NB I-94 STA. 2245+78.13 (48")
5. NB I-94 STA. 2266+11.42 (DOUBLE 48")
6. NB I-94 STA. 2279+47.75 (TRIPLE 48")

NOTES:

1. CONTRACTOR WILL PROVIDE A MINIMUM COVER, AS SHOWN ABOVE AT ALL TIMES DURING CONSTRUCTION AND PRIOR TO THE INSTALLATION OF THE PERMANENT PROTECTION SLAB AND/OR ROADWAY. CONSTRUCTION TRAFFIC SHALL NOT CROSS THE SEWER PIPE WITHOUT PROTECTION IN PLACE.
2. CONTRACTOR IS RESPONSIBLE FOR THE INTEGRITY OF SEWER PIPE THROUGH THE DURATION OF THE PROJECT, AND WILL NOT BE PAID FOR ANY REPAIRS REQUIRED, AS DETERMINED BY THE ENGINEER, TO THE PIPE, DUE TO CONSTRUCTION ACTIVITIES.

REVISIONS	
NAME	DATE