## INDEX OF SHEETS

SHEE	T NO.	DESCRIPTION
	1	COVER SHEET
	2	INDEX OF SHEETS, STATE STANDARDS, AND GENERAL NOTES
	3-4	SUMMARY OF QUANTITIES  TYPICAL SECTIONS
	5-7 8	ALIGNMENT, TIES AND BENCHMARKS PLAN
	9-11	EXISTING AND PROPOSED ROADWAY PLANS
	12-13	EXISTING AND PROPOSED ROADWAY PROFILE
	14-15	PROPOSED PAVEMENT MARKING PLANS
	16-21	PROPOSED TRAFFIC SIGNAL PLANS
	22	DETAILS FOR FRAMES AND LIDS ADJUSTMENTS WITH MILLING
	23	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT
	24	CURB AND CURB AND GUTTER REMOVAL AND REPLACEMENT
	25	BUTT JOINT AND HMA TAPER DETAILS
	26	TRAFFIC CONTROL AND PROTECTION FOR SIDEROADS, INTERSECTIONS, AND DRIVEWAYS
	27	TYPICAL APPLICATION FOR RAISED REFLECTIVE PAVEMENT MARKERS
	28	DISTRICT ONE TYPICAL PAVEMENT MARKINGS
		TRAFFIC CONTROL AND PROTECTION AT TURN BAYS
	30	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING
	31	ARTERIAL ROAD INFORMATION SIGN
	32	DISTRICT ONE DETECTOR LOOP INSTALLATION DETAIL FOR ROADWAY RESURFACING
	33-38	DISTRICT ONE STANDARD TRAFFIC SIGNAL DESIGN DETAILS

## STATE STANDARDS

000001-05	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
420001-07	PAVEMENT JOINTS
442201 <i>-03</i>	CLASS C AND D PATCHES
482011 <i>-03</i>	HMA SHOULDER STRIP/SHOULDER WITH RESURFACING OR WIDENING AND RESURFACING PROJECTS
604001 <i>-0</i> 3	FRAME AND LIDS, TYPE 1
606001 <i>-04</i>	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
606301- <i>04</i>	PC CONCRETE ISLANDS AND MEDIANS
630001 <i>-08</i>	STEEL PLATE BEAM GUARDRAIL
701101 <b>- 02</b>	OFF-RD OPERATION, MULTILANE, 15' (4.5 M) TO 24" (600 MM) FROM PAVEMENT EDGE
701201- <i>03</i>	LANE CLOSURE, 2L, 2W, DAY ONLY, FOR SPEEDS > 45 M
701501 <i>-05</i>	URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED
701601-06	URBAN LANE CLOSURE, MULTILANE, 1W OR 2W WITH NONTRAVERSABLE MEDIAN
701606-06	URBAN LANE CLOSURE, MULTILANE, 2W WITH MOUNTABLE MEDIAN
701701-06	URBAN LANE CLOSURE, MULTILANE INTERSECTION
701901-0!	TRAFFIC CONTROL DEVICES

## GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOURS NOTIFICATION REQUIRED).

10 FEET (3 METER) TRANSITIONS SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER AND MEDIAN ITEMS OF WORK TO EXISTING CURB AND GUTTERS AND MEDIANS IN THE FIELD, UNLESS OTHERWISE SHOWN. THE TRANSITIONS SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OF WORK SPECIFIED.

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGE OF MATTESON.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC, THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1/2 INCHES (40 MM) WHERE THE SPEED LIMIT IS 45 MPH (80 KM/H) OR LESS AND 1 INCH (25 MM) WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (80 KM/H). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES (75 MM) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT MS. PATRICE HARRIS, AREA TRAFFIC FIELD ENGINEER AT (708) 597-9800 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKING.

THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MININMUM OF 72 HOURS PRIOR TO THE PLACEMENT OF TEMPORARY TRAFFIC CONTROL DEVICES.

THE RESIDENT ENGINEER SHALL DETERMINE THE LOCATIONS OF CLASS "D" PATCHES.

THE RESIDENT ENGINEER SHALL VERIFY THE LOCATIONS OF ALL EXISTING PAVEMENT MARKINGS PRIOR TO MILLING OR RESURFACING.

BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXITSTING PAVEMENT MARKING LINES (AND RAISED REFLECTIVE MARKERS) IN ORDER THAT THESE LOCATIONS CAN BE RE-ESTABLISHED FOR STRIPING, EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY THE ENGINEER.

1				:
ł	FILE NAME =	USER NAME = shiranish	DESIGNED -	REVISED -
- 1	c:\pw_work\PWIDOT\SHIRANISB\dØ107234\PII	B907-Design.dan	DRAWN -	REVISED -
1		PLOT SCALE = 50.000 '/ IN.	CHECKED -	REVISED -
١		PLOT DATE = 3/10/2010	DATE: -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SCALE:

	EX OF SHEETS, LIST OF STATE STANDARDS & GENERAL NOTES			F.A.P. RTE.	SECTION	COUNTY	SH	
INDEX OF				353	23-N-3	соок		
	US ROUTE	30 AT	RIDGELAND	AVENUE			CONTRACT	NO
	CHEET NO	OF	CHEETS STA	TO STA.	FED. R	OAD DIST. NO. 1 ILLINOIS FED.	AID PROJECT	1