EXISTING DECK BEAM

NOTES

Detail I - With Bar Splicer or Couplers: Connect one (1) 1''x7''x10''' steel //2 to the top layer of couplers with 2-58" \$\phi\$ bolts screwed to coupler at approximate & of each barrier panel.

Detail II - With Extended Reinforcement Bars:


Connect one (1) 1"x7"x 10" steel 12 to the concrete slab or concrete wearing surface with $2^{-5}8'' \phi$ Expansion Anchors or cast in place inserts spaced between the top layer of reinforcement at approximate & of each barrier panel.

Cost of anchorage is included with Temporary Concrete Barrier. The I" x 7" x 10" plate shall not be removed until stage II construction forms and all reinforcement bars are in place and the concrete is ready to be placed.


SECTIONS THRU SLAB OR DECK BEAM


*** Dimension shown is minimum required embedment into concrete. If hot-mix asphalt wearing surface is present, minimum embedment shall be in addition to wearing surface depth.

**** If existing deck beam is to remain in place after stage construction, embedment shall only be into wearing surface and not into existing deck beam concrete.



NEW SLAB





STEEL RETAINER & 1" x 7" x 10"

**Wood blocks may be omitted when required to provide minimum stage traffic lane width. When the wood blocks are omitted, the concrete barrier shall be in direct contact with the steel retainer plate.

TEMPORARY CONCRETE BARRIER FOR STAGE CONSTRUCTION

									<u> </u>		
-	SHEET NO. 4	F.A.S RTE	A.S. SECTION						COUNTY	TOTAL SHEETS	SHEET NO.
		739	739 1-2BR						GREENE	150	86
١	21 SHEETS			S.N.	031-0	040	CONTRACT NO. 76410				10
	L 1	FED.	ROAD	DIST.	NO.	ILLINOIS	FED.	AID	PROJECT		
₹	COM										

DESIGNED B.G.H. L.D.G. CHECKED K.H.L. DRAWN B.G.H. CHECKED

R-27

when "A" is greater than 3'-6".

^{*} Required only with Detail II