INDEX OF SHEETS

1 TITLE SHEET 2 INDEX OF SHEETS, STATE STANDARDS AND GENERAL NOTES 3 SUMMARY OF QUANTITIES 4 GENERAL LOCATION MAP 5 PATCHING SCHEDULE 6 FREEWAY ENTRANCE AND EXIT RAMP CLOSURE DETAILS 7 FREEWAY SINGLE & MULTI-LANE WEAVE 8-9 MULTI-LANE FREEWAY PAVEMENT MARKING DETAILS 10 FREEWAY SHOULDER CLOSURES AND PARTIAL RAMP CLOSURES

STATE STANDARDS

STANDARD NO.

DESCRIPTION

000001-05 TYPICAL SYMBOLS, ABBREVIATIONS AND PATTERNS
420001-07 PAVEMENT JOINTS
421001-02 BAR REINFORCEMENT FOR CRC PAVEMENT
442001-04 CLASS A PATCHES
701400-03 APPROACH TO LANE CLOSURE, FREEWAY/EXPRESSWAY
701401-05 LANE CLOSURE, FREEWAY/EXPRESSWAY
701446-01 TWO LANE CLOSURE, FREEWAY/EXPRESSWAY

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "C.U.A.N." (CHICAGO UTILITY ALERT NETWORK) AT (312) 744-7000 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS UTILITIES (48 HOUR NOTIFICATION IS REQUIRED).

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE CITY OF CHICAGO.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE (OR TOLLWAY) PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

WHEN ARTIFICIAL LIGHTING IS UTILIZED IN NIGHT OPERATIONS, THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISIBILITY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.

ANY PAVEMENT MARKINGS AND RAISED REFLECTIVE PAVEMENT MARKERS OBLITERATED BY MILLING AND RESURFACING OPERATIONS ON SIDE STREETS AND ENTRANCES SHALL BE REPLACED AND PAID FOR IN KIND.

BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXISTING PAVEMENT MARKING LINES (AND RAISED REFLECTIVE PAVEMENT MARKERS) IN ORDER THAT THESE LOCATIONS CAN BE RE-ESTABLISHED FOR STRIPING. EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY THE ENGINEER.

ALL PAVEMENT PATCHING LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

THE CONTRACTOR SHALL CONTACT THE DISTRICT ONE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4155 A MINIMUM OF 72 HOURS IN ADVANCE OF BEGINNING WORK.

THE EXISTING ROADWAY TYPICAL SECTION IS ASSUMED TO BE 10 INCH CONTINUOUSLY REINFORCED CONCRETE PAVEMENT.

THE CONTRACTOR IS REQUIRED TO GET THE PROPER PERMITS FROM THE CITY OF CHICAGO PRIOR TO THE START OF ANY WORK.

CLASS PP-3 PORTLAND CEMENT CONCRETE IS TO BE USED FOR ALL CLASS A PATCHES.

1	FILE NAME =	USER NAME = wilgreendp	DESIGNED -	REVISED - 5/1/09 - DW
i	o:\pw.work\PWIDOT\WILGREENDP\dØ1251Ø9\D		DRAWN -	REVISED -
		PLOT SCALE = 100.0000 '/ IN.	CHECKED -	REVISED -
		PLOT DATE = 5/1/2009	DATE -	REVISED -

701901-01 TRAFFIC CONTROL DEVICES

SCALE: