


WITH NONSIGNALIZED INTERSECTION



- 1. DISTANCE TO BE SHOWN ON SIGN MEASURED FROM A POINT 6 FEET (1,8 m) FROM THE RAIL CLOSEST TO THE INTERSECTION TO THE STOP LINE OR CROSSMALK, WHICHEVER IS CLOSEST, ROUNDED DOWN TO THE MEAREST 5 FEET (1,6 m), WHERE THERE IS NO STOP LINE, MEASURE TO POINT WHERE THE DRIVER HAS A VIEW OF APPROACHING TRAFFIC.
- THE CLEARANCE SIGN IS ALSO TO BE USED AS AN INTERIM MEASURE AT LOCATIONS WITH INTERCONNECTED INTERSECTION TRAFFIC SIGNALS WHERE IT IS PLANNED TO CHANGE THEM TO NEAR-SIDE SIGNALS AT A FUTURE THEM. IN THIS CASE, THE DISTANCE TO BE SHOWN ON THE SIGN IS MEASURED FROM THE EDGE OF THE STRIPCD-OUT AREA INSTEAD OF G-FEET FROM THE RAIL. THE SIGN IS TO BE REMOVED WHEN THE NEAR-SIDE SIGNALS ARE INSTALLED AND THE PAVEMENT MARKINGS EXTEND TO THE INTERSECTION.

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.

SIGNING AND PAVEMENT MARKINGS TREATMENT FOR RAILROAD CROSSINGS

USER NAME = USER NAME = Plotted by Administrator					
COLUMBUS DRIVE FROM 87TH STRE	TREET TO WESTERN AVENUE	3578	3178 RS-2	соок	27 24
PLUI SCALE = 25.00000 7 IN. CHECKED NEVISED DEPARIMENT OF TRANSPORTATION				CONTRACT NO. 60G8	