## INDEX OF SHEETS

#### SHEET NO. DESCRIPTION

- 1 TITLE SHEET
- 2 INDEX OF SHEETS, STATE STANDARDS, AND GENERAL NOTES
- 3 SUMMARY OF QUANTITIES
- 4 TYPICAL SECTIONS PLAN
- ROADWAY & PAVEMENT MARKING PLANS
- 17-28 DETECTOR LOOP REPLACEMENT PLANS
- 29 DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING
- PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT
- 31 CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT
- 32 BUTT JOINTS AND HMA TAPER DETAILS
- 33 STEEL PLATE BEAM GUARDRAIL ADJACENT TO CURB AND GUTTER AND STABILIZATION AT TBT TY. 1 SPL.
- TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS 34
- TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)
- 36 DISTRICT ONE TYPICAL PAVEMENT MARKINGS
- 37 TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC)
- PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING
- ARTERIAL ROAD INFORMATION SIGN
- 40 DISTRICT ONE STANDARD TRAFFIC SIGNAL DESIGN DETAILS DETECTOR LOOPS
- 41 DISTRICT ONE DETECTOR LOOP INSTALLATION DETAILS FOR ROADWAY RESURFACING

# LIST OF STATE STANDARDS

### STANDARD NO. DESCRIPTION

000001-05STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS

420001-07 CLASS C AND D PATCHES

606001-04 COMBINATION CONCRETE CURB AND GUTTER

630001-08 STEEL PLATE BEAM GUARDRAIL

630101-08 GUARDRAIL MOUNTED ON EXISTING CULVERTS

630301-05 SHOULDER WIDENING FOR TYPE 1 (SPECIAL) GUARDRAIL TERMINALS

631011-05 TRAFFIC BARRIER TERMINAL, TYPE2

635006-03 REFLECTOR AND TERMINAL MARKER PLACEMENT

653011-02REFLECTOR MARKER AND MOUNTING DETAILS

701301-03 LANE CLOSURE 2L, 2W SHORT TIME OPERATIONS

701311-03 LANE CLOSURE 2L, 2W MOVING OPERATIONS - DAY ONLY

701601-06URBAN LANE CLOSURE, MULTILANE, 1W OR 2W WITH NONTRAVERSABLE MEDIAN

701602-04 URBAN LANE CLOSURE, MULTILANE, 1W OR 2W WITH BIDIRECTIONAL LEFT TURN LANE

701606-06URBAN LANE CLOSURE, MULTILANE, 2W WITH MOUNTABLE MEDIAN

701701 OURBAN LANE CLOSURE MULTILANE INTERSECTION

701901-01 TRAFFIC CONTROL DEVICES

886001-0/ DETECTOR LOOP INSTALLATION

886006-01 TYPICAL LAYOUT FOR DETECTOR LOOPS

### GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 1-800-892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOURS NOTIFICATION IS REQUIRED).

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES, THE CITY OF ZION AND THE VILLAGES OF WINTHROP HARBOR AND BEACH PARK

TRANSITIONS SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER AND MEDIAN ITEMS OF WORK TO EXISTING CURB & GUTTER AND MEDIANS IN THE FIELD, UNLESS OTHERWISE SHOWN, THE TRANSITION SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OF WORK SPECIFIED.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND BITUMINOUS TAPER DETAILS".

NO PERMANENT LANE CLOSURES WILL BE ALLOWED. MILLING, RESURFACING, STRUCTURE ADJUSTMENTS, AND PATCHING OPERATIONS WILL BE DONE WITH DAY TIME CLOSURES ONLY

THE RESIDENT ENGINEER SHALL CONTACT MS. DEBBIE HANLON, AREA TRAFFIC FIELD ENGINEER AT (847) 438-2300 A MINIMUM OF 72 HOURS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT

THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470. A MINIMUM OF 72 HOURS PRIOR TO THE INSTALLATION OF ANY TEMPORARY TRAFFIC CONTROL DEVICES

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC, THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1-1/2 INCHES WHERE THE SPEED LIMIT 45 MPH OR LESS AND 1 INCH WHERE THE SPEED LIMIT IS GREATER THAN 45MPH. WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).

ALL PAVEMENT PATCHING LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS.

DOUBLE LANE MARKERS ARE TO BE USED AS SHOWN ON THE DISTRICT ONE DETAIL "TYPICAL APPLICATIONS - RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)" SHOWN IN THE PLANS.

PAVEMENT MARKING TAPE, TYPE III SHALL BE USED FOR SHORT TERM PAVEMENT MARKINGS ON ALL FINAL SURFACES. THE COST OF THE PAVEMENT MARKING TAPE, TYPE III

THE RESIDENT ENGINEER SHALL VERIFY ALL EXISTING PAVEMENT MARKINGS BEFORE MILLING

DO NOT SCALE PLANS FOR CONSTRUCTION DIMENSIONS

LIMITS OF RESURFACING ON ALL SIDE STREETS ARE TO BE AT THE RADUIS RETURN OR AS DIRECTED BY THE ENGINEER

REV. 5-20-09

SECTION COUNTY