

**GENERAL NOTES**

- ALL CONSTRUCTION SHALL BE DONE IN ACCORDANCE WITH THE DETAILS IN THE PLANS, THE SPECIAL PROVISIONS INCLUDED IN THE CONTRACT DOCUMENTS, AND THE LATEST EDITION OF THE FOLLOWING STATE OF ILLINOIS SPECIFICATIONS: "THE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION" (REFERRED TO AS THE "STANDARD SPECIFICATIONS"), THE "SUPPLEMENTAL SPECIFICATIONS AND RECURRING SPECIAL PROVISIONS", THE "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND HIGHWAYS" AND THE "MANUAL OF TEST PROCEDURES FOR MATERIALS".
- UTILITY LOCATIONS HAVE NOT BEEN SHOWN ON THESE PLANS. THE CONTRACTOR SHALL HAVE THE RESPECTIVE UTILITY COMPANIES FIELD LOCATE ALL THEIR FACILITIES PRIOR TO BEGINNING CONSTRUCTION. THE CONTRACTOR SHALL ALSO VERIFY THE DEPTHS OF THE EXISTING UTILITIES IF NECESSARY. ANY RELOCATION OR LOWERING OF UTILITIES SHALL BE COORDINATED BY THE CONTRACTOR
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROTECTION OF ALL UNDERGROUND OR SURFACE UTILITIES EVEN THOUGH THEY MAY NOT BE SHOWN ON THE PLANS. ANY UTILITY THAT IS DAMAGED DURING CONSTRUCTION SHALL BE REPAIRED OR REPLACED AT THE CONTRACTOR'S EXPENSE TO THE SATISFACTION OF THE ENGINEER OR VILLAGE.
- THE CONTRACTOR SHALL NOTIFY THE VILLAGE SUPERINTENDENT OF PUBLIC WORKS AND THE ENGINEER AT LEAST 48 HOURS IN ADVANCE OF BEGINNING WORK TO OBTAIN VILLAGE UTILITY LOCATIONS AND SHALL COORDINATE ALL CONSTRUCTION OPERATIONS WITH THE VILLAGE SUPERINTENDENT OF PUBLIC WORKS AND THE ENGINEER.
- MATERIALS RESULTING FROM THE REMOVAL OF PAVEMENT, DRIVEWAYS, CURB AND GUTTER, HOT-MIX ASPHALT SURFACES, SIDEWALKS AND EXCAVATION FOR NEW SIDEWALKS ETC. SHALL BE REMOVED AT THE END OF EACH DAY TO AN APPROVED SITE. IN THE JUDGMENT OF THE VILLAGE, SHOULD IT BE NECESSARY TO REMOVE SUCH MATERIALS, THE VILLAGE WILL HAVE THE MATERIAL REMOVED AND THE CONTRACTOR WILL BE BILLED (CHARGED) ACCORDINGLY.
- THE CONTRACTOR MAY OBTAIN MUNICIPAL WATER IN BULK, AT NO CHARGE, AS LONG AS THERE IS NOT A "WATERING BAN" IN EFFECT. THE INDISCRIMINATE USE OF FIRE HYDRANTS IS STRICTLY PROHIBITED. WATER FOR CONSTRUCTION SHALL BE METERED OR OTHERWISE ACCOUNTED FOR AND A DAILY LOG MAINTAINED. THE CONTRACTOR SHALL PROVIDE THE WATER TRUCK AND DRIVER REQUIRED TO OBTAIN AND TRANSPORT THIS WATER. THE VILLAGE RESERVES THE RIGHT TO RESTRICT OR REFUSE THE USE OF VILLAGE WATER IF DEEMED NECESSARY.
- IT WILL BE THE CONTRACTOR'S RESPONSIBILITY TO NOTIFY RESIDENTS AND THE VILLAGE WHEN ACCESS TO THEIR DRIVEWAYS WILL BE TEMPORARILY CLOSED DUE DRIVEWAY REPLACEMENT. THE CONTRACTOR SHALL DISTRIBUTE NOTICES PROVIDED BY THE VILLAGE TO RESIDENTS. EVERY EFFORT SHALL BE MADE TO ACCOMMODATE ACCESS TO THESE PROPERTIES INCLUDING KNOCKING ON DOORS WHEN DRIVEWAYS ARE ABOUT TO BE CLOSED.
- THE CONTRACTOR SHALL PROTECT AND CAREFULLY PRESERVE ALL SECTION OR SUBSECTION MONUMENTS OR PROPERTY OR REFERENCE MARKERS UNTIL THE OWNERS, HIS AGENT OR AN AUTHORIZED SURVEYOR HAS WITNESSED OR OTHERWISE REFERENCED THEIR LOCATIONS.
- THE CONTRACTOR SHALL NOTIFY IDOT BUREAU OF MATERIALS (PHONE 847-705-4337) AT LEAST 24 HOURS PRIOR TO THE PLACEMENT OF HMA OR CONCRETE.
- ANY SIGNS OR MAILBOXES THAT ARE IN CONFLICT WITH THE PROPOSED CONSTRUCTION SHALL BE REMOVED AND REPLACED IN ACCORDANCE WITH VILLAGE STANDARDS AND INCLUDED IN THE COST OF THE CONTRACT. MAIL SERVICE SHALL BE MAINTAINED AT ALL TIMES.
- EXISTING PAVEMENT, DRIVEWAY PAVEMENT, CURB AND GUTTER AND SIDEWALK TO REMAIN IN PLACE SHALL BE SAW CUT FULL DEPTH TO PROVIDE A NEAT VERTICAL FACE BETWEEN THE PROPOSED AND EXISTING AND SHALL BE INCLUDED IN THE COST OF THE CONTRACT.
- IN AREAS WHERE THE EXISTING DRIVEWAY (HOT-MIX ASPHALT OR GRAVEL), SIDEWALK, OR CURB AND GUTTER IS TO BE REMOVED AND REPLACED, THE REMOVAL AND DISPOSAL OF ANY ADDITIONAL MATERIAL REQUIRED TO ESTABLISH THE PROPOSED DRIVEWAY, SIDEWALK, OR CURB AND GUTTER SUBGRADE ELEVATION SHALL BE INCLUDED IN THE PAY ITEMS, HMA SURFACE REMOVAL OF THE TYPE SPECIFIED, SIDEWALK REMOVAL OR COMBINATION CONCRETE CURB AND GUTTER REMOVAL AND REPLACEMENT.
- RESERVED.
- THE PRIME COAT APPLICATION RATE SHALL BE 0.1 GAL/SY. THE MC-30 PRIME COAT APPLICATION RATE SHALL BE 0.3 GAL/SY.
- THE LOCATIONS OF THE CLASS D PATCHES SHALL BE DETERMINED BY THE ENGINEER IN THE FIELD.
- ALL AGGREGATE USED ON THIS PROJECT SHALL BE CRUSHED MATERIAL.
- THE QUANTITIES FOR PATCHING WILL NOT EXCEED THE AMOUNT LISTED IN THE SUMMARY OF QUANTITIES.
- THE DAYS PAVING OPERATION SHALL RESULT IN A SINGLE TRANSVERSE JOINT. ANY COLD LONGITUDINAL JOINTS WILL NOT BE ACCEPTED. PROVIDING A SINGLE TRANSVERSE JOINT SHALL BE ACCOMPLISHED BY PAVING ONE LANE OF SUFFICIENT LENGTH THAT WILL ALLOW FOR THE PAVING OF THE ADJACENT LANE IN THE SAME DAY.
- FOR STEEL BARS CERTIFICATION, PLEASE CONTACT IDOT BUREAU OF MATERIALS AT (847) 705-4361.

- ON STREETS TO BE FULL WIDTH MILLED (2" OR MORE), THE STRUCTURES IN THE PAVEMENT SHALL BE ADJUSTED IN ACCORDANCE WITH THE IDOT DETAIL "DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING". THIS WORK SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR FRAME AND LIDS TO BE ADJUSTED (SPECIAL).
- THE CONTRACTOR SHALL UTILIZE A MECHANICAL SWEEPER TO CLEAN STREETS AFFECTED BY CONTRACTORS OPERATIONS, INCLUDING HAUL ROUTES, AT LEAST TWICE PER WEEK AND ADDITIONALLY AS DIRECTED BY THE ENGINEER. THIS WORK SHALL BE INCLUDED IN THE COST OF CONSTRUCTION.
- NO DAMAGE TO PARKWAYS IS PLANNED AS PART OF THESE IMPROVEMENTS EXCEPT WHERE NEW SIDEWALK IS INSTALLED OR EXISTING SIDEWALK IS PERMANENTLY REMOVED. ANY AND ALL RESTORATION OF DAMAGED PARKWAYS SHALL CONSIST OF NECESSARY SUB-GRADE MATERIAL AS APPROVED BY THE ENGINEER, TOPSOIL 4-INCH AND NATIVE SOD IN ACCORDANCE WITH SECTION 1081.03. RESTORATION SHALL BE INCLUDED IN THE PAY ITEM WHICH CAUSED THE DISTURBANCE EXCEPT WHERE NEW SIDEWALK IS INSTALLED OR EXISTING SIDEWALK IS PERMANENTLY REMOVED. FOR THESE ITEMS, RESTORATION WILL BE PAID FOR AS PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH, SPECIAL OR SIDEWALK REMOVAL (SPECIAL).
- PORTIONS OF EXISTING BARRIER CURB AND CURB AND GUTTER WITHIN THE PROJECT LIMITS ARE PAINTED. IF PAINTED BARRIER CURB OR CURB AND GUTTER REQUIRES REMOVAL AND REPLACEMENT, THE REPLACEMENT CURB SHALL BE PAINTED TO MATCH THE COLOR OF THE CURB AND GUTTER REMOVED. SAMPLES OF THE PAINT SHALL BE PROVIDED TO THE ENGINEER PRIOR TO APPLICATION TO ENSURE COMPLIANCE WITH THE MANUFACTURERS RECOMMENDATIONS. NO PAINTING SHALL OCCUR UNTIL THE PAINT AND APPLICATION IS APPROVED BY THE ENGINEER. PAINTING SHALL BE INCLUDED IN THE PAY ITEM COMBINATION CONCRETE CURB AND GUTTER REMOVAL AND REPLACEMENT OR CONCRETE CURB, TYPE B.
- CURB AND GUTTER SHALL BE DEPRESSED AT DRIVEWAYS AND SIDEWALK RAMPS IN ACCORDANCE WITH THE IDOT HIGHWAY STANDARDS. SIDEWALK RAMPS FOR ACCESS FOR THE DISABLED SHALL BE PROVIDED AT THE PROPOSED CROSSWALKS IN ACCORDANCE WITH THE IDOT HIGHWAY STANDARDS OR AS DETERMINED BY THE ENGINEER.
- PORTLAND CEMENT CONCRETE SIDEWALK SHALL BE THICKENED TO 6-INCHES AT LOCATIONS WHERE THE SIDEWALK CROSSES PRIVATE DRIVEWAYS AND 8-INCHES WHERE THE SIDEWALK CROSSES COMMERCIAL DRIVEWAYS. TRANSVERSE EXPANSION JOINTS 3/4-INCH SHALL BE PLACED EVERY 50 FEET OR AS DETERMINED BY THE ENGINEER. TRANSVERSE CONTRACTION JOINTS SHALL BE PLACED EVERY 5-FEET.
- THE DISTRICT 1 DETAIL FOR COMBINATION CONCRETE CURB AND GUTTER REMOVAL AND REPLACEMENT SHOWN IN THE PLANS SHALL BE MODIFIED AS SHOWN IN THE CURB DETAIL ON THE MISCELLANEOUS DETAIL SHEET, TO INCLUDE THE FOLLOWING (THESE REQUIREMENTS SHALL APPLY TO REPLACED BARRIER CURB). THE WORK SHALL INCLUDE SAW-CUTTING AND REMOVING THE EXISTING PAVEMENT A MINIMUM OF 6 INCHES MEASURED FROM THE EXISTING EDGE OF PAVEMENT, AND FILLING THE 6-INCH GAP WITH CLASS SI CONCRETE TO AN ELEVATION 2 1/2 INCHES BELOW THE PROPOSED CURB AND GUTTER FLAG. IF THE CONCRETE IS PLACED HIGHER THAN 2-1/2" FROM THE GUTTER FLAG FOR STREETS TO BE RESURFACED, THE CONTRACTOR WILL BE REQUIRED TO GRIND ADDITIONAL CONCRETE TO THE REQUIRED 2-1/2" DEPTH. REMOVAL OF UNSUITABLE SUB-BASE MATERIAL, AS DIRECTED BY THE ENGINEER, SHALL BE INCLUDED IN THE COST OF COMBINATION CONCRETE CURB AND GUTTER REMOVAL AND REPLACEMENT, REGARDLESS OF DEPTH. THE AREA BEHIND THE PROPOSED CURB AND GUTTER SHALL BE RESTORED WITH NATIVE SOD IN ACCORDANCE WITH ARTICLE 1081.03 RATHER THAN SALT TOLERANT SOD (WHERE APPLICABLE).
- WORK AND MATERIALS REQUIRED TO INSTALL 1-INCH UNIT DUCT SHALL BE INCLUDED IN THE PAY ITEM DETECTOR LOOP REPLACEMENT.
- AN MFT PROJECT ON LINCOLN AVENUE WILL OCCUR PRIOR TO OR CONCURRENTLY WITH THIS STP (LAPP) PROJECT. THE MFT PROJECT WORK ZONE WILL OVERLAP A PORTION OF THE STP (LAPP) PROJECT WORK ZONE. COORDINATION SHALL BE REQUIRED BETWEEN THE CONTRACTOR OF THE STP (LAPP) IMPROVEMENTS AND THE CONTRACTOR OF THE MFT IMPROVEMENTS.
- THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO THE PLACEMENT OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.

**INDEX OF SHEETS**

SHEET NO.	TITLE
1	COVER SHEET
2	INDEX OF SHEETS, HIGHWAY STANDARDS, GENERAL NOTES AND LEGEND
3	SUMMARY OF QUANTITIES
4	TYPICAL SECTIONS AND HOT-MIX ASPHALT MIXTURE REQUIREMENTS
5	TYPICAL SECTIONS AND HOT-MIX ASPHALT SURFACE REMOVAL AND RESURFACING DETAIL
6	TYPICAL SECTIONS
7	SCHEDULE OF QUANTITIES
8	SCHEDULE OF QUANTITIES AND CONSTRUCTION SCHEDULE
9 - 10	PLAN - LINCOLN AVENUE
11 - 12	PAVEMENT MARKING PLAN - LINCOLN AVENUE
13	MISCELLANEOUS DETAILS
14	DISTRICT 1 DETAIL - BD-01 DRIVEWAY DETAILS - DISTANCE BETWEEN R.O.W. AND FACE OF CURB & EDGE OF SHOULDER > 15' (4.5m)
15	DISTRICT 1 DETAIL - BD-02 DRIVEWAY DETAILS - DISTANCE BETWEEN R.O.W. AND FACE OF CURB < 15' (4.5m)
16	DISTRICT 1 DETAIL - BD-08 DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING
17	DISTRICT 1 DETAIL - BD-22 PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT
18	DISTRICT 1 DETAIL - BD-24 CURB AND CURB AND GUTTER REMOVAL AND REPLACEMENT
19	DISTRICT 1 DETAIL - BD-32 BUTT JOINTS AND HMA TAPER DETAILS
20	DISTRICT 1 DETAIL - TC-10 TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS
21	DISTRICT 1 DETAIL - TC-13 DISTRICT ONE TYPICAL PAVEMENT MARKINGS
22	DISTRICT 1 DETAIL - TC-16 DISTRICT ONE PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING
23	DISTRICT 1 DETAIL - TC-18 SIGNING FOR FLAGGING OPERATIONS AT WORK ZONE OPENINGS
24	DISTRICT 1 DETAIL - TC-22 ARTERIAL ROAD INFORMATION SIGN
25	DISTRICT 1 DETAIL - TC-23 TYPICAL SUPPLEMENTAL SIGNING AND PAVEMENT MARKING TREATMENT FOR RAILROAD CROSSINGS
26	DISTRICT 1 DETAIL - TS-07 DETECTOR LOOP INSTALLATION DETAILS FOR ROADWAY RESURFACING

**HIGHWAY STANDARDS**

000001-05	STANDARD SYMBOLS, ABBREVIATIONS, AND PATTERNS
406201-01	MAILBOX TURNOUT
424001-05	CURB RAMPS FOR SIDEWALKS
442201-03	CLASS C AND D PATCHES
482011-03	HMA SHLD. STRIPS/SHLDS. WITH RESURFACING OR WIDENING AND RESURFACING PROJECTS
606001-04	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
701301-03	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
701311-03	LANE CLOSURE, 2L, 2W MOVING OPERATIONS
701501-05	URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED
701801-04	LANE CLOSURE MULTILANE 1W OR 2W CROSSWALK OR SIDEWALK CLOSURE
701901-01	TRAFFIC CONTROL DEVICES
780001-02	TYPICAL PAVEMENT MARKINGS
886001-01	DETECTOR LOOP INSTALLATIONS
886006-01	TYPICAL LAYOUTS FOR DETECTION LOOPS
BLR-24-2	MAILBOX TURNOUT FOR LOCAL ROADS

**LEGEND**

	BUTT JOINT OR DRIVEWAY BUTT JOINT		DOMESTIC WATER SERVICE BOX TO BE ADJUSTED		RIM RIM ELEVATION
	FRAME AND LIDS TO BE ADJUSTED (SPECIAL)		VALVE BOX TO BE ADJUSTED		EOP EDGE OF PAVEMENT
	FRAME AND LIDS TO BE ADJUSTED (SPECIAL)		COMBINATION CONCRETE CURB AND GUTTER REMOVAL AND REPLACEMENT		BC BACK OF CURB
	DOMESTIC WATER SERVICE BOX TO BE ADJUSTED (SPECIAL)		CONCRETE CURB TYPE B OR CONCRETE CURB TYPE B (SPECIAL)		BW BACK OF WALK
	VALVE BOX TO BE ADJUSTED (SPECIAL)		EXISTING ELEVATION		DWY DRIVEWAY
			PROPOSED ELEVATION		EX EXISTING

COPYRIGHT © 2009 BY BAXTER & WOODMAN, INC. ... ILLINOIS LICENSE NO. ... 3/10/2009

	DESIGNED - REW	REVISED - IDOT REVIEW 02-09-09	<b>VILLAGE OF FOX RIVER GROVE, ILLINOIS LINCOLN AVENUE STP (LAPP) IMPROVEMENTS</b>	<b>INDEX OF SHEETS, HIGHWAY STANDARDS, GENERAL NOTES AND LEGEND</b>		F.A.U. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	DRAWN - CJC	REVISED - IDOT REVIEW 03-04-09		SCALE: NONE	STA.	TO STA.	0015	08-00020-00-RS	McHENRY	26
	CHECKED - RWL	REVISED -				FED. ROAD DIST. NO. C-91-201-09		CONTRACT NO. 63162		
	DATE - 12-12-08	FILE - 080923-GEN.NOTES.sht				ILLINOIS FED. AID PROJECT M-9003 (167)				