

Sheet S13 of S25 RTE.


RTE. SECTION COUNTY TOTAL SHEETS NO. 309. LITRIB. WHITESIDE. 376. 53. FED. ROAD DIST. NO. 2 ILLINOIS FED. AID PROJECT

Contract #64B74





See sheet of for scupper location relative to parapet.



SECTION B-B

Drill and tap 8 holes for $\frac{1}{2}$ "-13 bolts on an $8\frac{3}{4}$ " ϕ bolt circle. (2 blind holes are $1\frac{1}{4}$ " deep, 6 thru holes)

VIEW C-C

6" I.D.

7" O.D.

DOWNSPOUT

10" O.D. 6" I.D. Notes:

All cast iron parts shall be gray iron conforming to the requirements of AASHTO M 105, Class 35B.

Bolts, anchor studs, washers and nuts shall conform to the requirements of ASTM A 307 and shall be galvanized according to AASHTO M 232.

Downspouts located on the exterior side of a painted steel fascia beam shall be painted with the finish coat specified for the exterior side of the fascia beam.


As an alternate, boits, anchor studs, washers and nuts may be stainless steel according to Article 1006.29(d) of the Standard Specifications.

Structural steel weldments of equal sections and of the same configuration may be substituted for the cast iron scupper frame. Fillet or full penetration welds shall be used for the weldments. Details shall be submitted to the Engineer for approval. Structural steel weldments shall not be substituted for the cast iron scupper grate. Structural steel frames and downspouts shall be galvanized according to AASHTO M111.


The Contractor shall take appropriate measures to assure that Protective Coat is not applied to the scupper.

Cost of the Grate, Frame, Downspout, Anchor Studs, Bolts, Washers and Nuts including complete installation of the scupper shall be paid for at the contract unit price each for Drainage Scupper, DS-12.

Alternate fiberglass downspout conforming to ASTM D 2996 with a short-time rupture strength hoop tensile stress of 30,000 psi min. may be used in lieu of the cast iron or steel equivalent.



BOLT HOLE DETAIL



BILL OF MATERIAL

	ITEM			UNIT	QUANTITY
Di	rainage	Scupper,	DS-12	Each	2

DRAINAGE SCUPPER, DS-12

U.S. RTE. 30/IL RTE. 78 OVER ROCK CREEK F.A.P. ROUTE 309, SECTION (17R)B WHITESIDE COUNTY STATION 1037+84.35 STRUCTURE NO. 098-0113

DATE: December 18, 2008

DRAWN BY: D. Schettler CHECKED BY: A. Yargicoglu

PATRICK

ENGINEERING INC.

LISLE, ILLINOIS