



FAP 614 - TYPICAL SECTION #4

STA 859+00.00 TO STA 860+46.00  
STA 860+46.00 TO STA 860+76.00 - PR BR APPR PAVT (SPECIAL) (SEE DETAILS)  
STA 860+76.00 TO STA 864+06.50 - PR SN 063-0500 - SEE STRUCTURE DETAILS  
STA 864+06.50 TO STA 864+36.50 - PR BR APPR PAVT (SEE DETAILS)  
STA 864+36.50 TO STA 864+42.50 - PR BRIDGE APPROACH PAVT CONNECTOR (SEE DETAILS)

LEGEND

- ①

EX PCC PAVEMENT (9-6-9)
- ②

EX BASE COURSE WIDENING, 8"
- ③

EX HMA RESURFACING, 6" (± 2")
- ④

EX HMA SHOULDER/WIDENING, 12" ±
- ⑤

PR HMA SURFACE REMOVAL - VAR. DEPTH
- ⑥

PR ROCKFILL - SPECIAL
- ⑦

PR EARTH EMBANKMENT
- ⑧

PR STONE DUMPED RIPRAP, CLASS A4
- ⑨

PR TOP SOIL PLACEMENT, 4"
- ⑩

PR LIME MODIFIED SOILS, 12"
- ⑪

PR SUB-BASE GRANULAR MATERIAL, TYPE A, 12"
- ⑫

PR HMA FULL DEPTH PAVEMENT, 13 1/2"
- ⑬

PR HMA BASE COURSE/WIDENING, 12"
- ⑭

PR SUB-BASE GRANULAR MATERIAL, TYPE C, VAR. DEPTH
- ⑮

PR LEVELING BINDER (MACHINE METHOD), VAR. DEPTH  
- WHEN LESS THAN 2 1/4" THICK  
PR HMA BINDER COURSE, VAR. DEPTH  
- WHEN GREATER THAN AND EQUAL TO 2 1/4" THICK
- ⑯

PR HMA SURFACE COURSE, 1 1/2"
- ⑰

PR HMA SHOULDERS, 6"
- ⑱

PR HMA SHOULDERS, 8"
- ⑲

PR HMA SHOULDERS, VAR. DEPTH
- ⑳

PR AGGREGATE SHOULDER, TYPE B, 3" (MIN.) & VAR DEPTH
- ㉑

PR PAVEMENT MARKING, LINE - 5"
- ㉒

PR REMOVAL AND DISPOSAL OF UNSUITABLE MATERIAL

NOTE: EX PAVEMENT AND EX BRIDGE ARE NOT SHOWN ON TYPICAL SECTION, BUT REQUIRE REMOVAL

STA 859+00.00 TO STA 859+31.00 - EX PAVEMENT REMOVAL  
STA 859+31.00 TO STA 864+09.00 - EX SN 063-0007 REMOVAL  
STA 864+09.00 TO STA 865+00.00 - EX PAVEMENT REMOVAL

S-1 REFERS TO STAGE I  
S-2 REFERS TO STAGE II  
S-3 REFERS TO STAGE III