



FAP 614 - TYPICAL SECTION #5

STA 867+00.00 TO STA 868+50.00 - TRANS. HMA SHLD. WIDTHS FROM 7.0' TO 4.0'
 STA 868+50.00 TO STA 870+99.99 - USE 4.0' WIDE HMA SHLDS INSTEAD OF 7.0' WIDE

* SEE SCHEDULES FOR PROPOSED LOCATIONS

LEGEND

- | | |
|--|---|
| ① EX PCC PAVEMENT (9-6-9) | ⑮ PR LEVELING BINDER (MACHINE METHOD),
VAR. DEPTH |
| ② EX BASE COURSE WIDENING, 8" | - WHEN LESS THAN 2 1/4" THICK |
| ③ EX HMA RESURFACING, 6" (± 2") | PR HMA BINDER COURSE, VAR. DEPTH |
| ④ EX HMA SHOULDER/WIDENING, 12" ± | - WHEN GREATER THAN AND EQUAL TO |
| ⑤ PR HMA SURFACE REMOVAL - VAR. DEPTH | 2 1/4" THICK |
| ⑥ PR ROCKFILL - SPECIAL | ⑯ PR HMA SURFACE COURSE, 1 1/2" |
| ⑦ PR EARTH EMBANKMENT | ⑰ PR HMA SHOULDERS, 6" |
| ⑧ PR STONE DUMPED RIPRAP, CLASS A4 | ⑱ PR HMA SHOULDERS, 8" |
| ⑨ PR TOP SOIL PLACEMENT, 4" | ⑲ PR HMA SHOULDERS, VAR. DEPTH |
| ⑩ PR LIME MODIFIED SOILS, 12" | ⑳ PR AGGREGATE SHOULDER, TYPE B, 3" (MIN.)
& VAR DEPTH |
| ⑪ PR SUB-BASE GRANULAR MATERIAL, TYPE A, 12" | ㉑ PR PAVEMENT MARKING, LINE - 5" |
| ⑫ PR HMA FULL DEPTH PAVEMENT, 13 1/2" | ㉒ PR REMOVAL AND DISPOSAL OF UNSUITABLE
MATERIAL |
| ⑬ PR HMA BASE COURSE/WIDENING, 12" | |
| ⑭ PR SUB-BASE GRANULAR MATERIAL,
TYPE C, VAR. DEPTH | |

S-1 REFERS TO STAGE I
 S-2 REFERS TO STAGE II
 S-3 REFERS TO STAGE III