



FAP 614 - TYPICAL SECTION #8

STA 879+00.00 TO STA 895+50.00
STA 895+50.00 TO STA 897+00.00 - TRANS. HMA SHLD. WIDTHS FROM 3.0' TO 6.0';
MAINTAIN 10.0' TOTAL SHLD. WIDTH AND 4.0' AGG. SHLD. WIDTH

LEGEND

- (1) EX PCC PAVEMENT (9-6-9)
- (2) EX BASE COURSE WIDENING, 8"
- (3) EX HMA RESURFACING, 6" (\pm 2")
- (4) EX HMA SHOULDER/WIDENING, 12" \pm
- (5) PR HMA SURFACE REMOVAL - VAR. DEPTH
- (6) PR ROCKFILL - SPECIAL
- (7) PR EARTH EMBANKMENT
- (8) PR STONE DUMPED RIPRAP, CLASS A4
- (9) PR TOP SOIL PLACEMENT, 4"
- (10) PR LIME MODIFIED SOILS, 12"
- (11) PR SUB-BASE GRANULAR MATERIAL, TYPE A, 12"
- (12) PR HMA FULL DEPTH PAVEMENT, 13 1/2"
- (13) PR HMA BASE COURSE/WIDENING, 12"
- (14) PR SUB-BASE GRANULAR MATERIAL, TYPE C, VAR. DEPTH

- (15) PR LEVELING BINDER (MACHINE METHOD), VAR. DEPTH
- WHEN LESS THAN 2 1/4" THICK
PR HMA BINDER COURSE, VAR. DEPTH
- WHEN GREATER THAN AND EQUAL TO 2 1/4" THICK
- (16) PR HMA SURFACE COURSE, 1 1/2"
- (17) PR HMA SHOULDERS, 6"
- (18) PR HMA SHOULDERS, 8"
- (19) PR HMA SHOULDERS, VAR. DEPTH
- (20) PR AGGREGATE SHOULDER, TYPE B, 3" (MIN.) & VAR DEPTH
- (21) PR PAVEMENT MARKING, LINE - 5"
- (22) PR REMOVAL AND DISPOSAL OF UNSUITABLE MATERIAL

S-1 REFERS TO STAGE I
S-2 REFERS TO STAGE II
S-3 REFERS TO STAGE III

