

 LAYOUT
 Rod
 09/12/08

 DRAWN
 Rod
 09/30/08

 REVIEWED
 TEH
 09/30/08

SHEET	NO.	30
86 <b>сн</b>		

ROUTE NO.	SECTION	COUNTY		TOTAL SHEETS	SHEE NO.
FAP Rte 614	144(B-1)	Cass &	Mason	351	166
FED. ROAD DIST. NO. 7		ILLINOIS	FED. AID PROJECT-		

Contract #72A76

Notes:

All cast iron parts shall be gray iron conforming to the requirements of AASHTO M 105, Class 35B.

Bolts, anchor studs, washers and nuts shall conform to the requirements of ASTM A 307 and shall be galvanized according to AASHTO M 232.

Scuppers need not be painted.

As an alternate, bolts, anchor studs, washers and nuts may be stainless steel according to Article 1006.29(d) of the Standard Specifications.

Structural steel weldments of eaual sections and of the same configuration may be substituted for the cast iron scupper frame. Fillet or full penetration welds shall be used for the weldments. Details shall be submitted to the Engineer for approval. Structural steel weldments shall not be substituted for the cast iron scupper grate. Structural steel frames and downspouts shall be galvanized according to AASHTO M111.

The Contractor shall take appropriate measures to assure that Protective Coat is not applied to the scupper.

Cost of the Grate, Frame, Downspout, Anchor Studs, Bolts, Washers and Nuts including complete installation of the scupper shall be paid for at the contract unit price each for Drainage Scupper, DS-11.

Alternate fiberglass downspout conforming to ASTM D 2996 with a short-time rupture strength hoop tensile stress of 30,000 psi min. may be used in lieu of the cast iron or steel equivalent.

