BILL OF MATERIALS

			TOTAL	IDOT UNDERPASS	CDOT OVERPASS
	ITEM	UNIT	QUANTITY		QUANTITY
	IDOT	FOOT	518	518	
	CONDUIT ATTACHED TO STRUCTURE, I" DIA., PVC COATED GALVANIZED STEEL	1001	010	310	
	CONDUIT ATTACHED TO STRUCTURE, 2° DIA., PVC COATED GALVANIZED STEEL	FOOT	140	140	
	CONDUIT ATTACHED TO STRUCTURE, 3" DIA., PVC COATED GALVANIZED STEEL	FQOT	952	952	
	RINCTION BOX, STABILESS STEEL, ATTACHED TO STRUCTURE 6" X 6" X 4"	EACH	12	12	
	JUNCTION BOX, STAINLESS STEEL, ATTACHED TO STRUCTURE, 12" X 10" X 6"	EACH	6	6	
	JUNCTION BOX, STAINLESS STEEL, ATTACHED TO STRUCTURE, 24" X 24" X 10"	EACH	2	2	
(UNIT DUCT, 660V, 3-IC-NO.2, L'C-NO.4 GROUND, (XLP-TYPEUSE), 1-I/F DIA. POLYET/PYLENE	FOOT	102	102)
۶	CHI DOC; OVI, O K TOOL LEGIST SIGNED AND TO BE SOON				
ζ	UNIT DUCT, 600V, 3-1C NO.2, 1/C NO.4 GROUND, (XLP-TYPE USE), 1 1/2" DIA. POLYETHYLENE	FOOT	242	242)
Λ	ELECTRIC CABLE IN CONDUIT, 600V (XLP-TYPE USE) 1/C NO, 10	FOOT	2786	2786	
	ELECTRIC CABLE IN CONDUIT, 660V (XLP-TYPE USE) 1/C NO. 4	FOOT	932	932	
	ELECTRIC CABLE IN CONDUIT, 600V (XLP-TYPE USE) I/C NO. 2	FOOT	2500	2500	
	REMOVE ELECTRIC CABLE FROM CONDUIT	FOOT	5982	5982	
*	MAINTENANCE OF LIGHTING SYSTEM	CALMO	6	6	
*	REMOVE CONDUIT ATTACHED TO STRUCTURE	FOOT	2083	2083	
*	REMOVE EXISTING JUNCTION BOX	EACH	30	30	
*	PROTECTION AND MAINTENANCE OF EXISTING UNDERPASS LIGHTING	LSUM	1	1	
	CDOT	FOOT	237	1	237
	UNDERGROUND CONDUIT, PVC, 2" DIA.	<u> </u>			
	CONDUIT ATTACHED TO STRUCTURE, 2" DIA., GALVANIZED STEEL.	FOOT	634		634
	CONDUIT EMBEDDED IN STRUCTURE, 2" DIA., PVC	FOOT	221		221
*	REMOVE EXISTING STREET LIGHTING EQUIPMENT	LSUM	1		1
*	MAINTENANCE OF STREET LIGHTING SYSTEM (CITY OF CHICACO)	LSUM	1		1
*	PAINT EXISTING STREET LIGHT/TRAFFIC EQUIPMENT COMPLETE	EACH	1		1
*	CABLE IN CONDUIT, TRIPLEX, 2-I/C NO. 6 AND I-I/C NO. 8 GROUND	FÓOT	2692		2692
*	RACK, SECONDARY-AERIAL, 2-WIRI:	EACH	1		1
*	POLE, STEEL, 326°, ANCHOR BASE, 11 1/2° B.C., 7 GAUGE (INSTALL ONLY)	EACH	4		4
*	MAST ARM, STEEL, STREET LIGHTING, 8 POOF (INSTALL ONLY)	EACH	9		9
*	MAST ARM, STEEL, STREET LIGHTING, 15 FOOT (INSTALL ONLY)	EACH	4		4
*	LUMINAIRE, STREET LIGHT, CERAMIC METAL HALIDE, 210 WATT, 240 VOLT, ARTERIAL SEMI-CUTOFF (INSTALL ONLY)	EACH	15		15
	SURP APPLAZ JONO C	FOOT	260	 	260
*	WIRE, AERIAL, I/C NO. 6 INDICATE SPECIAL PROVISION	1.20	J	.t	<u> </u>

Α	B	B	R	E	VI	A	T	0	N	S

ABBREVIATION	DESCRIPTION
AC	ALTERNATING CURRENT
A/C	AERIAL CABLE
AFG	ABOVE FINISHED GRADE
CB	CIRCUIT BREAKER
CKT	CIRCUIT
CM	CENTIMETER
CP	CONTROL PANEL
CT.	CURRENT TRANSFORMER
DA	DAVIT ARM
DC	DIRECT CURRENT
DÍA	DIAMETER
DP	DISTRIBUTION PANEL
E	EXISTING UNIT TO REMAIN
ECA	ELECTRIC CABLE ASSEMBLY
FT	FEET OR FOOT
FL	FUSE
GND	GROUND
HID	HIGH INTENSITY DISCHARGE
JВ	JUNCTION BOX
KVA	KILOVOLT-AMPERE
K₩	KILOWATTS
M	METER
MA	MAST ARM
MM	MILLIMETER
M.H.	MOUNTING HEIGHT
MW	MESSENGER WIRE
NO. •	NUMBER
Р	PROPOSED
PB	PUSH BUTTON
PNL	PANEL
PVC	POLYVINYL CHLORIDE
PVCC RGC	PVC COATED RIGID GALVANIZED CONDUIT
PT	POTENTIAL TRANSFORMER
R	EXISTING UNIT TO BE REMOVED
	(OWNER SALVAGED U.N.O.)
RR	EXISTING UNIT TO BE REMOVED AND
	REINSTALLED
RECP	RECEPTACLE
RGC	RIGID GALVANIZED CONDUIT
SEL SW	SELECTOR SWITCH
SPARE	SPARE
SPACE	SPACE
\$5	STAINLESS STEEL
STA	STATION
UD	UNIT DUCT
U.N.O.	UNLESS NOTED OTHERWISE
₩P	WOOD POLE
XFMR	TRANSFORMER
HPS	HIGH PRESSURE SODIUM
LPS	LOW PRESSURE SODIUM
LTFM	LIQUID TIGHT FLEXIBLE METALLIC

GENERAL NOTES

1. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO ASCERTAIN EXISTING FIELD CONDITIONS BEFORE BIDDING ON THIS PROJECT, SPECIFICALLY AS THEY RELATE TO LUMP SUM ITEMS AND UNIT PRICE ITEMS.

ALL NEW CONDUITS, JUNCTION BOXES AND APPURTENANCES ARE INDICATED DIAGRAMMATICALLY ON THE DRAWINGS, THE ACTUAL LOCATIONS IN THE FIELD SHALL MEET WITH APPROVAL OF THE ENGINEER. 2.

THE ELECTRICAL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE LATEST CODES, STANDARDS AND THE IDOT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION ADOPTED JANUARY 1, 2012, AND SUPPLEMENTAL SPECIFICATIONS AND SPECI

THE SCALE SHOWN ON PLAN DRAWINGS APPLIES ONLY TO THE FULL SIZE PLANS AND NOT TO REDUCED SIZE PLANS.

THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE ESTABLISHMENT OF THE FINISHED GRADE. THE ENGINEER MAY ASSIST THE CONTRACTOR, AS APPLICABLE, BUT THE RESPONSIBILITY FOR COORDINATION OF THE FINISHED GRADE WITH THE TOP OF THE FOUNDATION HEIGHTS AND THE LIKE SHALL REMAIN WITH THE CONTRACTOR.

THE CONTRACTOR SHALL FURNISH AND INSTALL LUMINAIRE LAMPS IN ACCORDANCE WITH THE SUPPLIER'S RECOMMENDATIONS AND IN ACCORDANCE WITH THE SPECIFICATIONS. THE COST OF THIS WORK AND MATERIAL SHALL BE INCLUDED IN THE APPLICABLE LUMINAIRE PAY ITEM. SEPARATE PAYMENT WILL NOT BE MADE.

ALL LUMINAIRES SHALL BE ORIENTED WITH THE OPTICS PERPENDICULAR TO THE ROADWAY UNLESS NOTED OTHERWISE OR DIRECTED BY THE ENGINEER. THE LUMINAIRES MAY REQUIRE NIGHT-TIME OPTICAL ADJUSTMENT UPON INSPECTION BY THE ENGINEER. THIS WORK SHALL BE CONSIDERED INCLUDED IN THE APPLICABLE LUMINAIRE PAY ITEMS. SEPARATE PAYMENT WILL NOT BE MADE.

CONDUITS AND UNIT DUCTS SHALL BE INSTALLED AT A MINIMUM 30 INCH DEPTH BELOW GRADE AND POSITIONED IN THE FIELD TO AVOID CONFLICT WITH ROADWAY UNDERDRAINS AND OTHER EXISTING AND PROPOSED UTILITIES. THE CONTRACTOR SHALL INCREASE DEPTH OF UNIT DUCT AND CONDUIT AS REQUIRED AT NO ADDITIONAL COST OF THE STATE. THE CONTRACTOR SHALL COGRDINATE RACEWAY DEPTH WITH THE ELECTRICAL DETAILS AND THE ENGINEER.

THE CONTRACTOR SHALL MAKE SPECIAL NOTE OF THE SPECIFIED REQUIREMENTS FOR BURIED WARNING TAPE, AS PART OF THE UNDERGROUND CONDUIT OR UNIT DUCT. THE INSTALLATION OF THE TAPE SHALL BE INSPECIED BY THE ENGINEER PRIOR TO BACKFILLING OR DURING PLOWING OPERATIONS, AS APPLICABLE.

10. WHERE THE CONTRACTOR'S EXCAVATION MEETS AN OBSTRUCTION, THE CONTRACTOR SHALL NOTIFY THE ENGINEER FOR DIRECTION IN WRITING PRIOR TO FURTHER EXCAVATION. THE CONTRACTOR SHALL RESTORE ANY DAMAGE TO EXISTING SYSTEMS OR UTILITIES AND REMOVE EXISTING OBSTRUCTIONS AND FOUNDATIONS TO THE SATISFACTION OF THE ENGINEER, THIS WORK SHALL BE CONSIDERED INCIDENTAL TO THE APPROPRIATE PAY ITEM.

INDEX OF DRAWINGS:

DRAWING NO.	STANDARD NO.	TITLE
E-1	-	GENERAL NOTES, ABBREVIATIONS, INDEX OF DRAWINGS AND SCHEDULE OF QUANTITIES
E-2	•	PROPOSED UNDERPASS LIGHTING PLAN
E-3	-	EXISTING UNDERPASS LIGHTING REMOVAL AND TEMPORARY LIGHTING PLAN
E-4	-	CONDUIT TRANSITION DETAILS
£-5	-	CONDUIT MOUNTING DETAILS ALONG BRIDGE
E-6	8E-902	IDOT DISTRICT 1 STANDARD DETAIL
E-7	-	ELECTRICAL GENERAL NOTES
E-8	826	COOT STANDARD DETAILS
E-9	-	UNDERGROUND CONDUIT FACILITIES
E-10	-	STREET LIGHTING REMOVAL AND INSTALLATION PLAN
E-11	753, 620	CDOT STANDARD DETAILS
E-12	762	COOT STANDARD DETAILS
E-13	840	COOT STANDARD DETAILS

E-1

COOK 142 52

REVISED A- ADDENDUM 1 5/23/14 SINGH USER NAME * mgorvido
PLOT SCALE * 2,80888811,882888 DESIGNED - BN ORAWN - AM REVISED CHECKED -KCP REVISED SHICH - ASSOCIATE INC CONSULTING ENGINEESS PLOT DATE = 22-MAY-2014 13:22 REVISED - 4/25/2014 DATE

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

COUNTY TOTAL SHEET NO. 63rd STREET OVER DAN RYAN EXPRESSWAY (1-90 /94) SECTION GENERAL NOTES, ABBREVIATIONS, INDEX OF DRAWINGS AND 94 1920-8 CONTRACT NO. 60J15 SCHEDULE OF QUANTITIES FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT SCALE: N.T.S. SHEET NO. 1 OF 13 SHEETS STA.