INDEX OF SHEETS

- 1 COVER SHEET
- 2 INDEX OF SHEETS, HIGHWAY STANDARDS, GENERAL NOTES, AND PROJECT SPECIFIC NOTES
- 3 SUMMARY OF QUANTITIES
- 4-8 EXISTING TYPICAL SECTIONS
- 9 SCHEDULE OF QUANTITIES
- 10 LINE DIAGRAM

HIGHWAY STANDARDS

701001-02 701006-05 701301-04 701336-06 701901-03

PROJECT SPECIFIC NOTES

The engineer shall notify Anna Ghidina (309-671-4466) two weeks before project completion so she can coordinate the installation of pavement markings.

GENERAL NOTES

PROPERTY OWNER ACCESS REQUIREMENTS

Access must be maintained to all existing properties during construction per Article 107.09 unless arrangements are made in writing by the Contractor with the property owners with a copy to the Engineer for short-term closures.

ENVIRONMENTAL REVIEWS

Prior to the use of any proposed borrow areas, use areas (temporary access roads, detours, run-arounds, etc.) and/or waste areas, the Contractor shall file the required environmental resource request surveys according to Section 107.22 of the Standard Specifications. These surveys are required in order for the Department to conduct cultural and biological resource surveys for the proposed site.

Prior to any waste materials being removed from the construction site the required environmental resource surveys will need to be obtained and filed by the Contractor. Excess waste products removed from the construction site shall be disposed of as required in Section 202.03 of the Standard Specifications.

Any protruding metal bars shall be removed prior to the disposal of broken concrete at approved disposal sites.

The required environmental resource documentation shall include the following:

- BDE Form 2289 (Environmental Survey Request)
- BDE Form 2290 (Waste/Use Area Review)
- A location map showing the size limits and location of the use area
- Color photographs depicting the use area
- Borrow Area Entry Agreement form-D4 PI0101

Please note that a minimum of four weeks shall be allowed for the District to obtain the required environmental clearances and six weeks for the required borrow site environmental clearances.

HOT-MIX ASPHALT MIXTURE REQUIREMENTS

Mixture Uses:	PARTIAL DEPTH PATCHING
RAP % (Max):	15%
AC/PC	64-22
Design Air Voids	4.0% @ N=50
Mixture Composition	IL 9.5
Friction Aggregate	MIX D

Notes: Individual lift thickness of each mix type will be no less than 3 times nominal maximum aggregate size and no more than 6 times nominal maximum aggregate size. COMMITMENTS

No commitments have been made for this project

FILE NAME :	USER NAME = aubrayes	DESIGNED -	REVISED -		INDEX OF SHEETS, HIGHWAY STANDARDS, GENERAL NOTES, AND PROJECT SPECIFIC NOTES					F.A.P. RTF.	SECTION	COUNTY TOTAL SHEET
IL 116 Spring Road Repair 2014.dgn		DRAWN -	REVISED -	STATE OF ILLINOIS						669	171-1: 161-3: 15-1	PEORIA 10 2
]	PLOT SCALE + 100.0000 1/ In.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION	AND PROJECT SPECIFIC RULES					CONTRACT NO. 68883		
0=foult	PLOT DATE + 4/9/2014	DATE -	REVISED -		SCALE:	SHEET	OF	SHEETS STA.	TO STA.		ILLINOIS FED.	ALD PROJECT

