SCHEDULE OF QUANTITIES

HOT–MIX ASPHALT (SHEET 2 OF 3)

NORTHBOUND RAMPS

	STATION	WIDTH AT LOCATION (FOOT)	TO	STATION	WIDTH AT LOCATION (FOOT)	LENGTH (FOOT)	AVERAGE WIDTH (FOOT)	AREA (SQ YD)	INSIDE SHOULDER WIDTH AT LOCATION (FOOT)	OUTSIDE SHOULDER WIDTH AT LOCATION (FOOT)	SHOULDER AREA (SQ YD)	BINDER THICKNESS (INCH)	POLYMER BINDER THICKNESS (INCH)	POLYMER SURFACE THICKNESS (INCH)	SHOULDER THICKNESS (INCH)	* BITUMINOUS MATERIALS (PRIME COAT) 40600100 (GALLON)	HOT-MIX ASPHALT BINDER COURSE, IL-19.0, FG, N90 40603092 (TON)	POLYMERIZED HOT-MIX ASPHALT BINDER COURSE, IL-19.0, FG, N90 40603243 (TON)	POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N90 40603545 (TON)	HOT-MIX ASPHALT SHOULDERS 48203100 (TON)
NORTHBOUND RAMPS																				
I-55 B	21+11.00	16.0		24+37.44	16.0	326.44	16.0	580.3	0.0	6.0	217.6	3.75	2.25	2.00	8.00	181.4	121.9	73.1	65.0	97.5
I-55 B	24+37.44	18.0		32+87.44	0.0	850.00	9.0	850.0	0.0	6.0	566.7	3.75	2.25	2.00	8.00	340.0	178.5	107.1	95.2	253.9
I-55 B	18+71.00	16.0		19+31.00	16.0	60.00	16.0	106.7	4.0	6.0	66.7	0.00	0.00	2.00	2.00	17.3	0.0	0.0	11.9	7.5
I-55 B	19+31.00	16.0		19+61.00	16.0	30.00	16.0	53.3	4.0	6.0	33.3	0.00	0.00	2.50	2.50	8.7	0.0	0.0	7.5	4.7
I-55 B	19+61.00	16.0		20+28.50	16.0	67.50	16.0	120.0	4.0	6.0	75.0	0.00	2.13	2.00	4.13	39.0	0.0	14.3	13.4	17.3
I-55 B	20+28.50	16.0		21+11.00	16.0	82.50	16.0	146.7	4.0	6.0	91.7	2.38	2.25	2.00	6.63	71.5	19.5	18.5	16.4	34.0
GORE	21+11.00	16.0		23+37.44	4.0	226.44	10.0	0.0	0.0	0.0	251.6	0.00	0.00	0.00	8.00	75.5	0.0	0.0	0.0	112.7
GORE	23+37.44	4.0		24+37.44	2.0	100.00	3.0	33.3	0.0	0.0	0.0	3.75	2.25	2.00	0.00	10.0	7.0	4.2	3.7	0.0
TR 181B	8+79.00	16.0		11+95.91	16.0	316.91	16.0	563.4	0.0	6.0	211.3	3.75	2.25	2.00	8.00	176.1	118.3	71.0	63.1	94.7
TR 181B	11+95.91	17.0		20+45.89	0.0	849.98	8.5	802.8	0.0	6.0	566.7	3.75	2.25	2.00	8.00	330.5	168.6	101.1	89.9	253.9
TR 181B	6+39.00	16.0		6+99.00	16.0	60.00	16.0	106.7	4.0	6.0	66.7	0.00	0.00	2.00	2.00	17.3	0.0	0.0	11.9	7.5
TR 181B	6+99.00	16.0		7+29.00	16.0	30.00	16.0	53.3	4.0	6.0	33.3	0.00	0.00	2.50	2.50	8.7	0.0	0.0	7.5	4.7
TR 181B	7+29.00	16.0		7+96.50	16.0	67.50	16.0	120.0	4.0	6.0	75.0	0.00	2.13	2.00	4.13	39.0	0.0	14.3	13.4	17.3
TR 181B	7+96.50	16.0		8+79.00	16.0	82.50	16.0	146.7	4.0	6.0	91.7	2.38	2.25	2.00	6.63	71.5	19.5	18.5	16.4	34.0
GORE	8+79.00	16.0		10+95.91	4.0	216.91	10.0	0.0	0.0	0.0	241.0	0.00	0.00	0.00	8.00	72.3	0.0	0.0	0.0	108.0
GORE	10+95.91	4.0		11+95.91	2.0	100.00	3.0	33.3	0.0	0.0	0.0	3.75	2.25	2.00	0.00	10.0	7.0	4.2	3.7	0.0
TR 181C	0+00.00	0.0		2+94.75	17.0	294.75	8.5	278.4	0.0	6.0	196.5	3.75	2.25	2.00	8.00	114.6	58.5	35.1	31.2	88.0
TR 181C	2+94.75	16.0		6+55.00	16.0	360.25	16.0	640.4	0.0	6.0	240.2	3.75	2.25	2.00	8.00	200.1	134.5	80.7	71.7	107.6
TR 181C	6+55.00	16.0		7+37.50	16.0	82.50	16.0	146.7	4.0	6.0	91.7	2.38	2.25	2.00	6.63	71.5	19.5	18.5	16.4	34.0
TR 181C	7+37.50	16.0		8+05.00	16.0	67.50	16.0	120.0	4.0	6.0	75.0	0.00	2.13	2.00	4.13	39.0	0.0	14.3	13.4	17.3
TR 181C	8+05.00	16.0		8+35.00	16.0	30.00	16.0	53.3	4.0	6.0	33.3	0.00	0.00	2.50	2.50	8.7	0.0	0.0	7.5	4.7
TR 181C	8+35.00	16.0		8+95.00	16.0	60.00	16.0	106.7	4.0	6.0	66.7	0.00	0.00	2.00	2.00	17.3	0.0	0.0	11.9	7.5
GORE	2+94.75	1.0		3+94.75	6.3	100.00	3.7	40.7	0.0	0.0	0.0	3.75	2.25	2.00	0.00	12.2	8.6	5.1	4.6	0.0
GORE	3+94.75	6.3		6+55.00	20.0	260.25	13.2	0.0	0.0	0.0	380.7	0.00	0.00	0.00	8.00	114.2	0.0	0.0	0.0	170.6
															TOTALS	2,046.4	861.4	580.0	575.7	1,477.4

* APPLICATION RATE FOR BITUMINOUS MATERIALS (PRIME COAT) IS 0.1 GAL/SQ YD FOR EACH COAT.
RUBBLIZED PAVEMENT WILL NOT BE PRIMED.

SOUTHBOUND

		STATION	WIDTH AT LOCATION (FOOT)	TO	STATION	WIDTH AT LOCATION (FOOT)	LENGTH (FOOT)	AVERAGE WIDTH (FOOT)	AREA (SQ YD)	INSIDE SHOULDER WIDTH AT LOCATION (FOOT)	OUTSIDE SHOULDER WIDTH AT LOCATION (FOOT)	SHOULDER AREA (SQ YD)	BINDER THICKNESS (INCH)	POLYMER BINDER THICKNESS (INCH)	POLYMER SURFACE THICKNESS (INCH)	SHOULDER THICKNESS (INCH)	* BITUMINOUS MATERIALS (PRIME COAT) 40600100 (GALLON)	HOT-MIX ASPHALT BINDER COURSE, IL-19.0, FG, N90 40603092 (TON)	POLYMERIZED HOT-MIX ASPHALT BINDER COURSE, IL-19.0, FG, N90 40603243 (TON)	POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N90 40603545 (TON)	HOT-MIX ASPHALT SHOULDERS 48203100 (TON)
CLASS A VARIABLE DEPTH PATCH	SB URBAN	235+16.00	24.0		235+76.00	24.0	60.00	24.0	160.0	6.0	10.0	106.7	0.00	0.00	0.00	0.00	0.0	0.0	0.0	0.0	0.0
TRANSITION	SB RURAL	235+76.00	24.0		236+06.00	24.0	30.00	24.0	80.0	6.0	10.0	53.3	0.00	0.00	2.50	2.50	13.3	0.0	0.0	11.3	7.5
TRANSITION	SB RURAL	236+06.00	24.0		236+73.50	24.0	67.50	24.0	180.0	6.0	10.0	120.0	0.00	2.13	2.00	4.13	60.0	0.0	22.1	20.4	27.7
TRANSITION	SB RURAL	236+73.50	24.0		237+56.00	24.0	82.50	24.0	220.0	6.0	10.0	146.7	2.38	2.25	2.00	6.63	110.0	31.1	28.6	24.9	54.4
TRANSITION	SB RURAL	237+56.00	24.0		288+45.00	24.0	5,089.00	24.0	13570.7	6.0	10.0	9047.1	3.75	2.25	2.00	8.00	5,428.3	3,028.0	1,763.3	1,535.7	4,053.1
	SB RURAL	288+45.00	24.0		289+27.50	24.0	82.50	24.0	220.0	6.0	10.0	146.7	2.38	2.25	2.00	6.63	110.0	31.1	28.6	24.9	54.4
TRANSITION	SB RURAL	289+27.50	24.0		289+95.00	24.0	67.50	24.0	180.0	6.0	10.0	120.0	0.00	2.13	2.00	4.13	60.0	0.0	22.1	20.4	27.7
TRANSITION	SB RURAL	289+95.00	24.0		290+25.00	24.0	30.00	24.0	80.0	6.0	10.0	53.3	0.00	0.00	2.50	2.50	13.3	0.0	0.0	11.3	7.5
CLASS A VARIABLE DEPTH PATCH	SB RURAL	290+25.00	24.0		290+85.00	24.0	60.00	24.0	160.0	6.0	10.0	106.7	0.00	0.00	0.00	2.00	10.7	0.0	0.0	0.0	11.9
TRANSITION	SB RURAL	290+85.00	24.0		290+91.00	24.0	6.00	24.0	16.0	6.0	10.0	10.7	0.00	0.00	0.00	0.00	0.0	0.0	0.0	0.0	0.0
OMISSION S.N. 057-0210		290+91.00			293+09.00		218.00										0.0	0.0	0.0	0.0	0.0
																TOTALS	5,805.6	3,090.2	1,864.7	1,648.9	4,244.2

* APPLICATION RATE FOR BITUMINOUS MATERIALS (PRIME COAT) IS 0.1 GAL/SQ YD FOR EACH COAT.
RUBBLIZED PAVEMENT WILL NOT BE PRIMED.