

REMOVAL SCHEDULE

LOCATION STATION TO STATION	LENGTH	PAVEMENT REMOVAL	HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2"	PAVED SHOULDER REMOVAL	REMARKS
	FOOT	SQ YD	SQ YD	FOOT	
RUSHING DRIVE					
162+67.29 TO 162+92.38	25.09		67		
162+92.38 TO 166+05.66	313.28		766		
162+92.38 LT TO 166+05.66 LT	313.28	42			
162+92.38 RT TO 166+05.66 RT	313.28	55			
166+05.66 TO 166+67.93	62.27	368			
IL 148					
59+95.81 LT TO 62+28.75 LT	232.94	186		116	
62+28.75 LT TO 64+80. LT	251.25			98	
66+00.8 LT TO 66+11.53 LT	10.73			5	
SUBTOTALS					
	1522	650	833	219	

EARTHWORK SCHEDULE

LOCATION STATION TO STATION	EARTH EXCAVATION	EXCAVATION TO BE USED IN EMBANKMENT ADJUSTED FOR SHRINKAGE	EMBANKMENT	EARTHWORK BALANCE WASTE (+) OR SHORTAGE (-)
	CU YD	CU YD	CU YD	CU YD
IL 148				
60+00 LT TO 64+00 LT	195	146.25	175	-29
SOUTH RADIUS				
0+00 RT TO 1+40 RT	75	56.25	192	-136
NORTH RADIUS				
0+00 RT TO 1+40 RT	0	0	76	-76
TOTALS				
	75	56	268	-241

25% Shrinkage Factor for Earth Excavation